

Article

Not peer-reviewed version

Single, Double, Triple, Quadruple, Quintuple-valued IndetermSoft Set

[Takaaki Fujita](#)*

Posted Date: 1 October 2025

doi: 10.20944/preprints202510.0017.v1

Keywords: soft set; indetermsoft set; double indetermsoft set; triple indetermsoft set; quadruple indetermsoft set; quintuple-valued indetermsoft set



Preprints.org is a free multidisciplinary platform providing preprint service that is dedicated to making early versions of research outputs permanently available and citable. Preprints posted at Preprints.org appear in Web of Science, Crossref, Google Scholar, Scilit, Europe PMC.

Copyright: This open access article is published under a Creative Commons CC BY 4.0 license, which permit the free download, distribution, and reuse, provided that the author and preprint are cited in any reuse.

Disclaimer/Publisher's Note: The statements, opinions, and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions, or products referred to in the content.

Article

Single, Double, Triple, Quadruple, Quintuple-Valued IndetermSoft Set

Takaaki Fujita

Independent Researcher, Tokyo, Japan; takaaki.fujita060@gmail.com

Abstract

Soft sets are parameterized families of subsets of a universe, where each parameter selects elements relevant under a condition. This paper develops *IndetermSoft sets*, a class designed to treat indeterminacy explicitly through structured value slices. We define five variants: (i) Single-valued, mapping each attribute value to one subset capturing undirected indeterminacy; (ii) Double-valued, splitting into truth-leaning and falsity-leaning slices; (iii) Triple-valued, adding a neutral slice; (iv) Quadruple-valued, refining polarity by distinguishing strong and ordinary truth/falsity leanings; and (v) Quintuple-valued, further introducing a central neutral band between the two strengths. These constructions yield a uniform framework for modeling ambiguous evidence, conflicts, and missing context.

Keywords: soft set; indetermsoft set; double indetermsoft set; triple indetermsoft set; quadruple indetermsoft set; quintuple-valued indetermsoft set

1. Preliminaries

We collect the basic terminology and notation used in what follows. The definitions in this paper are assumed to be finite.

1.1. Soft Set and IndetermSoft Set

The definitions of the Soft Set and the IndetermSoft Set are provided below. Soft Set is a parameterized family of subsets where each parameter selects relevant elements from a universe for decision modeling [1–3].

Definition 1 (Soft Set). [1] Let U be a universal set and E a set of parameters. A soft set over U is defined as an ordered pair (F, E) , where F is a mapping from E to the power set $\mathcal{P}(U)$:

$$F : E \rightarrow \mathcal{P}(U).$$

For each parameter $e \in E$, $F(e) \subseteq U$ represents the set of e -approximate elements in U , with (F, E) forming a parameterized family of subsets of U .

Example 1 (Soft Set — Apartment Search by Parameters). A renter filters apartments using simple binary conditions. Let the universe be the set of available listings

$$U = \{u_1, u_2, u_3, u_4, u_5, u_6, u_7, u_8\}.$$

Let the parameter set be

$$E = \{\text{near_subway}, \text{pet_friendly}, \text{balcony}, \text{under\$1500}, \text{new_build}\}.$$

Define a soft set (F, E) with $F : E \rightarrow \mathcal{P}(U)$:

$$\begin{aligned} F(\text{near_subway}) &= \{u_1, u_2, u_5, u_6, u_8\}, \\ F(\text{pet_friendly}) &= \{u_2, u_3, u_6, u_7\}, \\ F(\text{balcony}) &= \{u_1, u_3, u_4, u_6\}, \\ F(\text{under\$1500}) &= \{u_2, u_4, u_5, u_7\}, \\ F(\text{new_build}) &= \{u_1, u_5, u_8\}. \end{aligned}$$

Each $F(e) \subseteq U$ collects listings relevant under parameter e .

Concrete queries with explicit computations.

- (i) *near_subway & under\$1500*: $F(\text{near_subway}) \cap F(\text{under\$1500}) = \{u_1, u_2, u_5, u_6, u_8\} \cap \{u_2, u_4, u_5, u_7\} = \{u_2, u_5\}, \quad |\cdot| = 2.$
- (ii) *pet_friendly or balcony*: $F(\text{pet_friendly}) \cup F(\text{balcony}) = \{u_2, u_3, u_6, u_7\} \cup \{u_1, u_3, u_4, u_6\} = \{u_1, u_2, u_3, u_4, u_6, u_7\}, \quad |\cdot| = 6.$
- (iii) *new_build & balcony*: $F(\text{new_build}) \cap F(\text{balcony}) = \{u_1, u_5, u_8\} \cap \{u_1, u_3, u_4, u_6\} = \{u_1\}, \quad |\cdot| = 1.$

These set-theoretic combinations show how a soft set supports multi-constraint filtering with exact results.

Single-valued IndermSoft Set maps each attribute value to one subset capturing undirected, non-unique indeterminacy over H ; domain/codomain may be indeterminate [4–8].

Definition 2 ((Single-valued) IndermSoft set). [9–12] Let U be a universe of discourse, $H \subseteq U$ a non-empty subset, and $P(H)$ the powerset of H . Let A be the set of attribute values for an attribute a . A function $F : A \rightarrow P(H)$ is called an IndermSoft Set if at least one of the following conditions holds:

1. A has some indeterminacy.
2. $P(H)$ has some indeterminacy.
3. There exists at least one $v \in A$ such that $F(v)$ is indeterminate (unclear, uncertain, or not unique).
4. Any two or all three of the above conditions.

An IndermSoft Set is represented mathematically as:

$$F : A \rightarrow H(\cap, \cup, \oplus, \neg),$$

where $H(\cap, \cup, \oplus, \neg)$ represents a structure closed under the IndermSoft operators.

Example 2 ((Single-valued) IndermSoft Set — Identity Verification Queue). **Context.** A hiring team triages applicants whose identity documents have quality issues. Let the review subset be

$$H = \{a_1, a_2, a_3, a_4, a_5, a_6, a_7\} \subseteq U,$$

and let the attribute be “document condition” with values

$$A = \{\text{low_light_photo}, \text{partial_scan}, \text{metadata_mismatch}\}.$$

We define a single-valued IndermSoft mapping $F : A \rightarrow \mathcal{P}(H)$, where $F(v)$ collects cases with undirected indeterminacy under v (neither truth- nor falsity-leaning).

Determinately specified slices.

$$\begin{aligned} F(\text{low_light_photo}) &= \{a_1, a_3, a_6\}, \quad |F| = 3, \\ F(\text{partial_scan}) &= \{a_2, a_4\}, \quad |F| = 2. \end{aligned}$$

Indeterminate slice (explicit non-uniqueness). For $v^* = \text{metadata_mismatch}$, conflicting HR and ATS logs produce two admissible subsets:

$$S_1 = \{a_5\} \quad (\text{only the strict mismatch}), \quad S_2 = \{a_5, a_7\} \quad (\text{strict} + \text{borderline timestamp drift}).$$

Hence $F(v^*)$ is not uniquely determined:

$$F(\text{metadata_mismatch}) \in \{S_1, S_2\} = \{\{a_5\}, \{a_5, a_7\}\}.$$

This satisfies condition (3) of the IndetermSoft definition (indeterminate image).

Let the determinate union be

$$L := F(\text{low_light_photo}) \cup F(\text{partial_scan}) = \{a_1, a_2, a_3, a_4, a_6\}.$$

Including the indeterminate value yields an upper bound

$$U := L \cup F(\text{metadata_mismatch}) \in \{L \cup S_1, L \cup S_2\} = \{\{a_1, a_2, a_3, a_4, a_5, a_6\}, \{a_1, a_2, a_3, a_4, a_5, a_6, a_7\}\}.$$

Therefore the review queue size is bounded as

$$|L| = 5 \leq |U| \in \{6, 7\}.$$

This concrete non-uniqueness of $F(v^*)$ exemplifies a (single-valued) IndetermSoft set: one subset per value, with explicit indeterminacy captured by alternative admissible images.

1.2. Double-Valued Neutrosophic Set

Neutrosophic Set assigns to each element independent degrees of truth, indeterminacy, and falsity, enabling nuanced uncertainty modeling beyond fuzzy sets [13–15]. Double-Valued Neutrosophic Set records truth, truth-leaning indeterminacy, falsity-leaning indeterminacy, and falsity degrees for each element, capturing polarized ambiguous evidence effectively [16–18]. We consider Double-Valued Neutrosophic Logic, as outlined below (cf. [16,18,19]). Related concepts, such as the Multi-Valued Neutrosophic Set [20,21], are also well known.

Definition 3 (Double-Valued Neutrosophic Set). [16] Let X be a space of points (or objects) where each $x \in X$ represents an element. A Double-Valued Neutrosophic Set (DVNS) A is characterized by:

$$A = \{(x, T_A(x), I_T(x), I_F(x), F_A(x)) : x \in X\},$$

where:

- $T_A(x) \in [0, 1]$ is the truth membership value,
- $I_T(x) \in [0, 1]$ is the indeterminacy leaning towards truth,
- $I_F(x) \in [0, 1]$ is the indeterminacy leaning towards falsity,
- $F_A(x) \in [0, 1]$ is the falsity membership value.

These values satisfy the condition:

$$0 \leq T_A(x) + I_T(x) + I_F(x) + F_A(x) \leq 4.$$

Example 3 (Double-Valued Neutrosophic Set — Phishing Email Screening). **Universe and target.** Let X be the set of incoming emails and let $A \subseteq [0, 1]^4$ encode a DVNS for the concept LegitimateMail. For each email $x \in X$ we assign

$$(T_A(x), I_T(x), I_F(x), F_A(x)),$$

where T_A is truth (legitimate), F_A is falsity (phishing), I_T leans toward legitimacy, and I_F leans toward phishing.

Signals. We aggregate authentication (SPF/DKIM/DMARC), sender reputation, URL/attachment analysis, and writing-style features. Ambiguous signals (e.g., one pass and one fail) contribute to I_T or I_F ; consistent evidence contributes to T_A or F_A .

Concrete assignments (three emails).

email	T_A	I_T	I_F	F_A
e_1	0.72	0.14	0.06	0.08
e_2	0.38	0.20	0.22	0.20
e_3	0.10	0.08	0.27	0.55

Justification. e_1 : known domain, DMARC pass $\Rightarrow$ large T_A ; single shortened URL $\Rightarrow$ small I_F . e_2 : mixed signals (fresh domain, but no payload) $\Rightarrow$ comparable I_T and I_F . e_3 : macro-enabled attachment and domain spoof patterns $\Rightarrow$ large F_A .

Numerical verification. Row sums:

$$e_1 : 0.72 + 0.14 + 0.06 + 0.08 = 1.00 \leq 4,$$

$$e_2 : 0.38 + 0.20 + 0.22 + 0.20 = 1.00 \leq 4,$$

$$e_3 : 0.10 + 0.08 + 0.27 + 0.55 = 1.00 \leq 4.$$

Thus each quadruple satisfies the DVNS constraint $0 \leq T_A + I_T + I_F + F_A \leq 4$.

1.3. Triple-Valued Neutrosophic Set (TVNS)

A Triple-Valued Neutrosophic Set assigns each element degrees for truth, truth-leaning indeterminacy, neutral indeterminacy, falsity-leaning indeterminacy, and falsity, within limits. In this subsection, we examine the concept of the Triple-Valued Neutrosophic Set (TVNS) [22–24].

Definition 4 (Triple-Valued Neutrosophic Set (TVNS)). [24] A Triple-Valued Neutrosophic Set A on X is defined as

$$A = \left\{ \left(x, T_A(x), I_T(x), I_N(x), I_F(x), F_A(x) \right) : x \in X \right\},$$

where

- $T_A(x) \in [0, 1]$ is the truth membership degree,
- $I_T(x) \in [0, 1]$ is the indeterminacy leaning towards truth,
- $I_N(x) \in [0, 1]$ is the neutral indeterminacy (i.e., completely indeterminate, neither leaning towards truth nor falsity),
- $I_F(x) \in [0, 1]$ is the indeterminacy leaning towards falsity,
- $F_A(x) \in [0, 1]$ is the falsity membership degree.

For each $x \in X$, we have

$$0 \leq T_A(x) + I_T(x) + I_N(x) + I_F(x) + F_A(x) \leq 5.$$

Example 4 (Triple-Valued Neutrosophic Set — Loan Approval Under Missing Evidence). **Universe and target.** Let X be the set of loan applications and consider the TVNS for the concept Creditworthy. For each applicant $x \in X$ we assign

$$(T_A(x), I_T(x), I_N(x), I_F(x), F_A(x)),$$

where I_N is neutral indeterminacy due to missing or non-informative evidence.

Evidence channels. Credit score and repayment history (push T_A), soft positives such as stable address (push I_T), missing employer verification or frozen bureau file (push I_N), soft negatives like recent inquiries (push I_F), and hard negatives such as charge-offs (push F_A).

Concrete assignments (three applicants).

applicant	T_A	I_T	I_N	I_F	F_A
a_1	0.55	0.15	0.10	0.08	0.12
a_2	0.32	0.18	0.30	0.10	0.10
a_3	0.12	0.08	0.20	0.25	0.35

Justification. a_1 : strong score and verified income $\Rightarrow$ larger T_A ; a minor document issue $\Rightarrow$ small I_N . a_2 : acceptable score but employer response pending $\Rightarrow$ elevated I_N ; mixed soft signals split between I_T and I_F . a_3 : prior delinquency and high utilization $\Rightarrow$ large F_A ; some uncollected data adds to I_N .

Numerical verification. Row sums:

$$a_1 : 0.55 + 0.15 + 0.10 + 0.08 + 0.12 = 1.00 \leq 5,$$

$$a_2 : 0.32 + 0.18 + 0.30 + 0.10 + 0.10 = 1.00 \leq 5,$$

$$a_3 : 0.12 + 0.08 + 0.20 + 0.25 + 0.35 = 1.00 \leq 5.$$

Hence each quintuple satisfies the TVNS constraint $0 \leq T_A + I_T + I_N + I_F + F_A \leq 5$.

1.4. Quadruple-Valued Neutrosophic Set (QVNS)

A Quadruple-Valued Neutrosophic Set assigns each element truth, strongly truth-leaning indeterminacy, truth-leaning indeterminacy, falsity-leaning indeterminacy, strongly falsity-leaning indeterminacy, and falsity. The definition of the Quadruple-Valued Neutrosophic Set (QnVNS) is provided below [24,25].

Definition 5 (Quadruple-Valued Neutrosophic Set (QVNS)). [24] Let X be a universe of discourse. A Quadruple-Valued Neutrosophic Set A on X is defined as

$$A = \left\{ (x, T_A(x), I_T^s(x), I_T(x), I_F(x), I_F^s(x), F_A(x)) : x \in X \right\},$$

where:

- $T_A(x) \in [0, 1]$ is the truth membership degree,
- $I_T^s(x) \in [0, 1]$ is the indeterminacy strongly leaning towards truth,
- $I_T(x) \in [0, 1]$ is the indeterminacy leaning towards truth,
- $I_F(x) \in [0, 1]$ is the indeterminacy leaning towards falsity,
- $I_F^s(x) \in [0, 1]$ is the indeterminacy strongly leaning towards falsity,
- $F_A(x) \in [0, 1]$ is the falsity membership degree.

For each $x \in X$, it holds that

$$0 \leq T_A(x) + I_T^s(x) + I_T(x) + I_F(x) + I_F^s(x) + F_A(x) \leq 6.$$

Example 5 (Quadruple-Valued Neutrosophic Set — E-commerce Product Authenticity). **Universe and target.** Let X be items listed on a marketplace. Consider the QVNS for the concept *AuthenticItem*. For each item $x \in X$ we assign

$$(T_A(x), I_T^s(x), I_T(x), I_F(x), I_F^s(x), F_A(x)),$$

where T_A/F_A are truth/falsity memberships (authentic vs. counterfeit), and I_T^s, I_T, I_F, I_F^s are indeterminacy slices (strong/ordinary truth- or falsity-leaning).

Evidence channels. Manufacturer serial check (pushes I_T^s or T_A when strongly positive), invoice validation (pushes I_T), packaging/label anomalies (push I_F), known counterfeit patterns (push I_F^s), and third-party lab confirmation (boosts T_A or F_A).

Concrete assignments (three items).

item	T_A	I_T^s	I_T	I_F	I_F^s	F_A
i_1	0.60	0.15	0.10	0.05	0.03	0.07
i_2	0.30	0.05	0.20	0.25	0.10	0.10
i_3	0.08	0.02	0.10	0.25	0.35	0.20

Justification. i_1 : serial verified and lab spot-check $\Rightarrow$ large T_A , some I_T^s ; a minor label scuff $\Rightarrow$ small I_F . i_2 : mixed invoice and seller history $\Rightarrow$ comparable I_T and I_F ; moderate T_A . i_3 : hallmark counterfeit indicators $\Rightarrow$ large I_F^s and F_A .

Numerical verification. For each row,

$$i_1 : 0.60 + 0.15 + 0.10 + 0.05 + 0.03 + 0.07 = 1.00 \leq 6,$$

$$i_2 : 0.30 + 0.05 + 0.20 + 0.25 + 0.10 + 0.10 = 1.00 \leq 6,$$

$$i_3 : 0.08 + 0.02 + 0.10 + 0.25 + 0.35 + 0.20 = 1.00 \leq 6.$$

Thus each sextuple satisfies $0 \leq T_A + I_T^s + I_T + I_F + I_F^s + F_A \leq 6$.

1.5. Quintuple-Valued Neutrosophic Set (QnVNS)

A Quintuple-Valued Neutrosophic Set assigns each element truth; strong truth-leaning, truth-leaning, neutral, falsity-leaning, strong falsity-leaning indeterminacies; and falsity, with bounds. The definition of the Quintuple-Valued Neutrosophic Set (QnVNS) is provided below. [24]

Definition 6 (Quintuple-Valued Neutrosophic Set (QnVNS)). [24] Let X be a universe of discourse. A Quintuple-Valued Neutrosophic Set A on X is defined as

$$A = \left\{ (x, T_A(x), I_T^s(x), I_T(x), I_N(x), I_F(x), I_F^s(x), F_A(x)) : x \in X \right\},$$

where:

- $T_A(x) \in [0, 1]$ is the truth membership degree,
- $I_T^s(x) \in [0, 1]$ is the indeterminacy strongly leaning towards truth,
- $I_T(x) \in [0, 1]$ is the indeterminacy leaning towards truth,
- $I_N(x) \in [0, 1]$ represents neutral indeterminacy (i.e., completely indeterminate, neither leaning towards truth nor falsity),
- $I_F(x) \in [0, 1]$ is the indeterminacy leaning towards falsity,
- $I_F^s(x) \in [0, 1]$ is the indeterminacy strongly leaning towards falsity,
- $F_A(x) \in [0, 1]$ is the falsity membership degree.

For each $x \in X$, it holds that

$$0 \leq T_A(x) + I_T^s(x) + I_T(x) + I_N(x) + I_F(x) + I_F^s(x) + F_A(x) \leq 7.$$

Example 6 (Quintuple-Valued Neutrosophic Set — Product Recall Impact Assessment). **Universe and target.** Let X be purchased product units. Consider the QnVNS for the concept AffectedByRecall. For each unit $x \in X$ we assign

$$(T_A(x), I_T^s(x), I_T(x), I_N(x), I_F(x), I_F^s(x), F_A(x)),$$

where I_N is neutral indeterminacy (e.g., missing batch code).

Evidence channels. Lot/batch match (push I_T^s/T_A), weak cues such as packaging date proximity (push I_T), missing or unreadable label (push I_N), retailer confirmation of safe lot (push I_F), and manufacturer certificate of unaffected series (push I_F^s/F_A).

Concrete assignments (three units).

unit	T_A	I_T^s	I_T	I_N	I_F	I_F^s	F_A
b_1	0.55	0.20	0.10	0.05	0.05	0.02	0.03
b_2	0.20	0.05	0.15	0.30	0.15	0.05	0.10
b_3	0.08	0.02	0.10	0.10	0.20	0.25	0.25

Justification. b_1 : exact lot match and vendor alert $\Rightarrow$ large T_A and I_T^s . b_2 : label unreadable $\Rightarrow$ elevated I_N ; weak context on both sides. b_3 : certificate proves different series $\Rightarrow$ higher I_F^s and F_A .

Numerical verification. For each row,

$$b_1 : 0.55 + 0.20 + 0.10 + 0.05 + 0.05 + 0.02 + 0.03 = 1.00 \leq 7,$$

$$b_2 : 0.20 + 0.05 + 0.15 + 0.30 + 0.15 + 0.05 + 0.10 = 1.00 \leq 7,$$

$$b_3 : 0.08 + 0.02 + 0.10 + 0.10 + 0.20 + 0.25 + 0.25 = 1.00 \leq 7.$$

Hence each septuple satisfies $0 \leq T_A + I_T^s + I_T + I_N + I_F + I_F^s + F_A \leq 7$.

1.6. Double-Valued Indeterminsoft Set

Double-valued Indeterminsoft Set maps each attribute value to two subsets: truth-leaning indeterminacy and falsity-leaning indeterminacy within a universe, allowing overlaps. The definition of the Double-valued Indeterminsoft Set is provided below. [24]

Definition 7 (Double-valued Indeterminsoft Set). [24] Let U be a universe of discourse, $H \subseteq U$ a non-empty subset, and $\mathcal{P}(H)$ the power set of H . Let A be a set of attribute values associated with a specific attribute a . A function

$$F : A \rightarrow \mathcal{P}(H) \times \mathcal{P}(H)$$

is called a Double-valued Indeterminsoft Set if any of the following conditions hold:

1. The set A exhibits some degree of indeterminacy.
2. The power set $\mathcal{P}(H)$ exhibits some level of indeterminacy.
3. There exists at least one attribute value $v \in A$ such that the ordered pair

$$F(v) = (F_T(v), F_F(v))$$

is indeterminate, in the sense that either $F_T(v)$ or $F_F(v)$ (or both) is unclear, uncertain, or not uniquely defined.

4. Any combination of the above conditions holds.

Here, for each $v \in A$,

- $F_T(v) \subseteq H$ represents the indeterminacy leaning towards truth associated with v , and
- $F_F(v) \subseteq H$ represents the indeterminacy leaning towards falsity associated with v .

Example 7 (Double-valued Indeterminsoft Set — Warranty Claims Triage). Let the universe H be a finite set of consumer-electronics warranty claims

$$H = \{c_1, c_2, c_3, c_4, c_5, c_6, c_7\}.$$

Fix an attribute “document reliability,” with attribute values

$$A = \{\text{blurred_receipt}, \text{third_party_repair}, \text{serial_OCR_error}\}.$$

Define a Double-valued Indeterminsoft Set $F : A \rightarrow \mathcal{P}(H) \times \mathcal{P}(H)$ by

$$\begin{aligned} F(\text{blurred_receipt}) &= (F_T, F_F) = (\{c_1, c_2, c_5\}, \{c_3\}), \\ F(\text{third_party_repair}) &= (\{c_5\}, \{c_4, c_6\}), \\ F(\text{serial_OCR_error}) &= (\{c_2, c_6\}, \{c_7\}). \end{aligned}$$

Interpretation.

- $F_T(v)$ (truth-leaning indeterminacy): claims whose evidence likely supports validity under v , but is still indeterminate (e.g., other documents corroborate a blurred receipt).
- $F_F(v)$ (falsity-leaning indeterminacy): claims whose evidence likely undermines validity under v (e.g., non-authorized third-party repair), yet not conclusively.

Concrete checks (cardinalities and overlaps across different v):

$$\begin{aligned} |F_T(\text{blurred_receipt})| &= 3, & |F_F(\text{blurred_receipt})| &= 1, & |F_T \cup F_F| &= 4, \\ |F_T(\text{third_party_repair})| &= 1, & |F_F(\text{third_party_repair})| &= 2, & |F_T \cup F_F| &= 3, \\ |F_T(\text{serial_OCR_error})| &= 2, & |F_F(\text{serial_OCR_error})| &= 1, & |F_T \cup F_F| &= 3. \end{aligned}$$

Cross-attribute tension is visible: for instance, $c_6 \in F_F(\text{third_party_repair})$ but $c_6 \in F_T(\text{serial_OCR_error})$, capturing conflicting indeterminate signals that motivate a second-stage manual review.

2. Main Results

In this section, we present the main contributions of this paper, focusing on the concepts of ContraSoft Set and ContraRough Set.

2.1. Triple-Valued Indeterminsoft Set

Triple-valued Indeterminsoft Set maps each attribute value to three subsets: truth-leaning, neutral, and falsity-leaning indeterminacy over a universe, allowing overlaps.

Definition 8 (Triple-valued Indeterminsoft Set (TV-ISS)). Let U be a universe, $H \subseteq U$ nonempty, and A a set of attribute values. A TV-ISS is a mapping

$$G : A \longrightarrow \mathcal{P}(H)^3, \quad G(v) = (G_T(v), G_N(v), G_F(v)),$$

with the following intended semantics for each $v \in A$:

- $G_T(v) \subseteq H$: indeterminacy leaning to truth,
- $G_N(v) \subseteq H$: neutral indeterminacy (neither leaning to truth nor to falsity),
- $G_F(v) \subseteq H$: indeterminacy leaning to falsity.

No exclusivity is imposed a priori; intersections are allowed if the application dictates. When needed, one may assume $G_T(v), G_N(v), G_F(v)$ are pairwise disjoint to model a partition of the indeterminate region.

Example 8 (Concrete TV-ISS, its projection, and the embedding). Let the finite universe and attribute-values be

$$H = \{h_1, h_2, h_3, h_4\}, \quad A = \{\text{easy}, \text{hard}\}.$$

Define a TV-ISS $G : A \rightarrow \mathcal{P}(H)^3$ by

$$\begin{aligned} G(\text{easy}) &= (\{h_1, h_2\}, \{h_3\}, \{h_4\}), \\ G(\text{hard}) &= (\{h_1\}, \{h_2, h_3\}, \{h_4\}). \end{aligned}$$

Cardinalities are

$$\begin{aligned} |G_T(\text{easy})| &= 2, & |G_N(\text{easy})| &= 1, & |G_F(\text{easy})| &= 1, \\ |G_T(\text{hard})| &= 1, & |G_N(\text{hard})| &= 2, & |G_F(\text{hard})| &= 1. \end{aligned}$$

The canonical DV-ISS projection $\Pi(G)$ and upper envelope $\bar{\Pi}(G)$ are

$$\begin{aligned} \Pi(G)(\text{easy}) &= (\{h_1, h_2\}, \{h_4\}), & \bar{\Pi}(G)(\text{easy}) &= (\{h_1, h_2, h_3\}, \{h_3, h_4\}), \\ \Pi(G)(\text{hard}) &= (\{h_1\}, \{h_4\}), & \bar{\Pi}(G)(\text{hard}) &= (\{h_1, h_2, h_3\}, \{h_2, h_3, h_4\}), \end{aligned}$$

and one checks the coordinatewise inclusions

$$\Pi(G) \preceq \bar{\Pi}(G),$$

since, for instance, $\{h_1, h_2\} \subseteq \{h_1, h_2, h_3\}$ and $\{h_4\} \subseteq \{h_3, h_4\}$ at $v = \text{easy}$.

Now apply the DV $\rightarrow$ TV embedding ι to the DV-ISS $F := \Pi(G)$:

$$(\iota(F))(\text{easy}) = (\{h_1, h_2\}, \emptyset, \{h_4\}), \quad (\iota(F))(\text{hard}) = (\{h_1\}, \emptyset, \{h_4\}).$$

By construction,

$$(\Pi \circ \iota)(F) = F$$

holds pointwise and componentwise, e.g.,

$$(\Pi \circ \iota)(F)(\text{easy}) = \Pi(\{h_1, h_2\}, \emptyset, \{h_4\}) = (\{h_1, h_2\}, \{h_4\}) = F(\text{easy}).$$

This verifies, with explicit sets and equalities, the identity $\Pi \circ \iota = \text{id}$ from Theorem 1.

Example 9 (Triple-valued Indeterminsoft Set — Hiring Degree Verification). Let the universe H be a finite set of applicants

$$H = \{a_1, a_2, a_3, a_4, a_5, a_6\}.$$

Consider the attribute “credential verification,” with attribute values

$$A = \{\text{degree_email_unreplied}, \text{transcript_low_quality}\}.$$

Define a Triple-valued Indeterminsoft Set $G : A \rightarrow \mathcal{P}(H)^3$ by

$$\begin{aligned} G(\text{degree_email_unreplied}) &= (G_T, G_N, G_F) = (\{a_1, a_3\}, \{a_2, a_5\}, \{a_6\}), \\ G(\text{transcript_low_quality}) &= (\{a_3, a_4\}, \{a_5\}, \{a_2\}). \end{aligned}$$

Semantics for each $v \in A$:

- $G_T(v)$: truth-leaning indeterminacy (signals suggest the claim is likely true but not definitive yet; e.g., alumni registry hints).
- $G_N(v)$: neutral indeterminacy (insufficient information; e.g., awaiting registrar reply).
- $G_F(v)$: falsity-leaning indeterminacy (signals suggest likely false; e.g., domain mismatch, inconsistent graduation dates).

Concrete verifications (sizes and disjointness here by design):

$$\begin{aligned} |G_T(\text{degree_email_unreplied})| &= 2, & |G_N| &= 2, & |G_F| &= 1, & |G_T \cup G_N \cup G_F| &= 5, \\ |G_T(\text{transcript_low_quality})| &= 2, & |G_N| &= 1, & |G_F| &= 1, & |G_T \cup G_N \cup G_F| &= 4. \end{aligned}$$

If one wishes to compare with a Double-valued view, the canonical projection that discards the neutral slice is

$$F^\downarrow(v) := (G_T(v), G_F(v)),$$

so, for example, $F^\downarrow(\text{degree_email_unreplied}) = (\{a_1, a_3\}, \{a_6\})$, which is ready for two-queue downstream handling (provisional accept vs. provisional reject) while cases in G_N await additional evidence.

Theorem 1 (TV-ISS generalizes DV-ISS). *There exist mappings*

$$\iota : \text{ISS}_2(A, H) \rightarrow \text{ISS}_3(A, H), \quad \Pi : \text{ISS}_3(A, H) \rightarrow \text{ISS}_2(A, H)$$

defined pointwise by

$$(\iota(F))(v) := (F_T(v), \emptyset, F_F(v)), \quad (\Pi(G))(v) := (G_T(v), G_F(v)),$$

such that

$$\Pi \circ \iota = \text{id}_{\text{ISS}_2(A, H)}.$$

Consequently, $\text{ISS}_2(A, H)$ is isomorphic to the sub-class

$$\text{ISS}_3^{(0)}(A, H) := \left\{ G \in \text{ISS}_3(A, H) : G_N(v) = \emptyset \text{ for all } v \in A \right\} \subseteq \text{ISS}_3(A, H),$$

and every DV-ISS is a special case of a TV-ISS (obtained by taking all neutral slices empty).

Proof. Fix $F \in \text{ISS}_2(A, H)$. By definition,

$$F : A \rightarrow \mathcal{P}(H) \times \mathcal{P}(H), \quad v \mapsto (F_T(v), F_F(v)).$$

Define $\iota(F) : A \rightarrow \mathcal{P}(H)^3$ by $(\iota(F))(v) = (F_T(v), \emptyset, F_F(v))$. This lies in $\text{ISS}_3(A, H)$ since $\emptyset \in \mathcal{P}(H)$.

Next, for $G \in \text{ISS}_3(A, H)$ with $G(v) = (G_T(v), G_N(v), G_F(v))$, define $\Pi(G)(v) = (G_T(v), G_F(v))$. Then $\Pi(G) \in \text{ISS}_2(A, H)$.

We compute the composition explicitly, for each $v \in A$:

$$((\Pi \circ \iota)(F))(v) = \Pi(\iota(F))(v) = \Pi(F_T(v), \emptyset, F_F(v)) = (F_T(v), F_F(v)) = F(v).$$

Hence $\Pi \circ \iota = \text{id}_{\text{ISS}_2(A, H)}$.

Injectivity of ι : if $\iota(F) = \iota(F')$, then for every v ,

$$(F_T(v), \emptyset, F_F(v)) = (F'_T(v), \emptyset, F'_F(v)),$$

whence $F_T(v) = F'_T(v)$ and $F_F(v) = F'_F(v)$, so $F = F'$.

Moreover, the image of ι is precisely $\text{ISS}_3^{(0)}(A, H)$. Indeed, for any $G \in \text{ISS}_3^{(0)}(A, H)$ one has $G_N(v) = \emptyset$ for all v , and setting $F(v) = (G_T(v), G_F(v))$ yields $G = \iota(F)$.

Therefore DV-ISS is canonically identified with the neutral-empty sub-class of TV-ISS, so TV-ISS strictly generalizes DV-ISS. $\square$

2.2. Quadruple-Valued Indeterminsoft Set

Quadruple-valued Indeterminsoft Set assigns *four* indeterminacy slices per attribute value, mirroring Quadruple-valued Neutrosophic:

(strong truth-leaning), truth-leaning, falsity-leaning, strong falsity-leaning.

Definition 9 (Quadruple-valued Indeterminsoft Set (QV-ISS)). *Let U be a universe, $H \subseteq U$ nonempty, and A a set of attribute values. A QV-ISS is a mapping*

$$Q : A \longrightarrow \mathcal{P}(H)^4, \quad Q(v) = (Q_T^s(v), Q_T(v), Q_F(v), Q_F^s(v)),$$

where, for each $v \in A$:

- $Q_T^s(v) \subseteq H$: **strong truth-leaning indeterminacy** (very strong evidence toward truth, yet not fully resolved),
- $Q_T(v) \subseteq H$: **truth-leaning indeterminacy** (moderate evidence toward truth, still inconclusive),
- $Q_F(v) \subseteq H$: **falsity-leaning indeterminacy** (moderate evidence toward falsity, still inconclusive),
- $Q_F^s(v) \subseteq H$: **strong falsity-leaning indeterminacy** (very strong evidence toward falsity, yet not fully resolved).

Theorem 2 (QV-ISS generalizes TV-ISS). *Define maps*

$$\iota : (\mathcal{P}(H)^3)^A \longrightarrow (\mathcal{P}(H)^4)^A, \quad (\iota(G))(v) := (\emptyset, G_T(v) \cup G_N(v), G_F(v) \cup G_N(v), \emptyset),$$

and

$$\Pi : (\mathcal{P}(H)^4)^A \longrightarrow (\mathcal{P}(H)^3)^A, \quad (\Pi(Q))(v) := (T(v), N(v), F(v)),$$

where, writing $S_T(v) := Q_T^s(v) \cup Q_T(v)$ and $S_F(v) := Q_F^s(v) \cup Q_F(v)$,

$$T(v) := S_T(v) \setminus S_F(v), \quad N(v) := S_T(v) \cap S_F(v), \quad F(v) := S_F(v) \setminus S_T(v).$$

Then for every TV-ISS G in partition form, one has

$$(\Pi \circ \iota)(G) = G.$$

Consequently, TV-ISS embeds injectively into QV-ISS; hence QV-ISS (canonically) generalizes TV-ISS.

Proof. Fix G and $v \in A$. By definition of ι ,

$$Q_T^s = \emptyset, \quad Q_T = G_T \cup G_N, \quad Q_F = G_F \cup G_N, \quad Q_F^s = \emptyset.$$

Hence

$$S_T = Q_T^s \cup Q_T = G_T \cup G_N, \quad S_F = Q_F^s \cup Q_F = G_F \cup G_N.$$

Using the pairwise disjointness $G_T \cap G_N = G_N \cap G_F = G_T \cap G_F = \emptyset$, we compute:

$$T = S_T \setminus S_F = (G_T \cup G_N) \setminus (G_F \cup G_N) = (G_T \setminus (G_F \cup G_N)) \cup \underbrace{(G_N \setminus (G_F \cup G_N))}_{=\emptyset} = G_T,$$

$$N = S_T \cap S_F = (G_T \cup G_N) \cap (G_F \cup G_N) = \underbrace{(G_T \cap G_F)}_{=\emptyset} \cup \underbrace{(G_T \cap G_N)}_{=\emptyset} \cup \underbrace{(G_N \cap G_F)}_{=\emptyset} \cup G_N = G_N,$$

$$F = S_F \setminus S_T = (G_F \cup G_N) \setminus (G_T \cup G_N) = (G_F \setminus (G_T \cup G_N)) \cup \underbrace{(G_N \setminus (G_T \cup G_N))}_{=\emptyset} = G_F.$$

Therefore $(\Pi \circ \iota)(G)(v) = (G_T(v), G_N(v), G_F(v)) = G(v)$ for every $v \in A$, i.e., $(\Pi \circ \iota)(G) = G$. Since $\Pi \circ \iota = \text{id}$ on TV-ISS, ι is injective, providing an embedding of TV-ISS into QV-ISS. $\square$

2.3. Quintuple-Valued Indeterminacy Set

Quintuple-valued Indeterminacy Set assigns *five* indeterminacy slices per value, mirroring Quintuple-valued Neutrosophic:

(strong truth-leaning), truth-leaning, neutral, falsity-leaning, (strong falsity-leaning).

Definition 10 (Quintuple-valued Indeterminacy Set (5V-ISS)). *A 5V-ISS is a mapping*

$$R : A \rightarrow \mathcal{P}(H)^5, \quad R(v) = (R_T^s(v), R_T(v), R_N(v), R_F(v), R_F^s(v)),$$

with semantics, for each $v \in A$:

- $R_T^s(v) \subseteq H$: **strong truth-leaning indeterminacy**,
- $R_T(v) \subseteq H$: **truth-leaning indeterminacy**,
- $R_N(v) \subseteq H$: **neutral indeterminacy** (neither leaning toward truth nor falsity),
- $R_F(v) \subseteq H$: **falsity-leaning indeterminacy**,
- $R_F^s(v) \subseteq H$: **strong falsity-leaning indeterminacy**.

Theorem 3 (5V-ISS generalizes QV-ISS). Define the maps

$$\iota : \text{ISS}_4(A, H) \rightarrow \text{ISS}_5(A, H), \quad (\iota(Q))(v) := (Q_T^s(v), Q_T(v), \emptyset, Q_F(v), Q_F^s(v)),$$

$$\Pi : \text{ISS}_5(A, H) \rightarrow \text{ISS}_4(A, H), \quad (\Pi(R))(v) := (R_T^s(v), R_T(v), R_F(v), R_F^s(v)).$$

Then

$$\Pi \circ \iota = \text{id}_{\text{ISS}_4(A, H)}.$$

Consequently, $\text{ISS}_4(A, H)$ is canonically isomorphic to the subclass

$$\text{ISS}_5^{(0)}(A, H) := \{ R \in \text{ISS}_5(A, H) : R_N(v) = \emptyset \text{ for all } v \in A \} \subset \text{ISS}_5(A, H),$$

hence 5V-ISS strictly extends QV-ISS whenever some $R_N(v) \neq \emptyset$.

Proof. Let $Q \in \text{ISS}_4(A, H)$ and $v \in A$. By definition of ι and Π ,

$$(\Pi \circ \iota)(Q)(v) = \Pi(Q_T^s(v), Q_T(v), \emptyset, Q_F(v), Q_F^s(v)) = (Q_T^s(v), Q_T(v), Q_F(v), Q_F^s(v)) = Q(v).$$

Thus $\Pi \circ \iota = \text{id}$ pointwise and componentwise. Injectivity of ι : if $\iota(Q) = \iota(Q')$, then for every v

$$(Q_T^s, Q_T, \emptyset, Q_F, Q_F^s) = (Q_T'^s, Q_T', \emptyset, Q_F', Q_F'^s),$$

which forces $Q = Q'$. The image of ι is exactly $\text{ISS}_5^{(0)}(A, H)$ because $R \in \text{ISS}_5(A, H)$ belongs to $\text{ISS}_5^{(0)}(A, H)$ iff $R_N \equiv \emptyset$, in which case $R = \iota(Q)$ with $Q(v) = (R_T^s(v), R_T(v), R_F(v), R_F^s(v))$. To see the extension is strict, fix any $h^* \in H$ and $v^* \in A$ and define $R \in \text{ISS}_5(A, H)$ by $R_N(v^*) = \{h^*\}$ and the remaining coordinates as in $\iota(Q)$ for some Q ; then $R \notin \text{ISS}_5^{(0)}(A, H)$, so R is not in the image of ι . $\square$

Example 10 (Concrete embedding and equality check with counts). Let

$$H = \{h_1, h_2, h_3, h_4, h_5\}, \quad A = \{\text{easy}, \text{hard}\}.$$

Define a QV-ISS $Q \in \text{ISS}_4(A, H)$ by

$$\begin{aligned} Q(\text{easy}) &= (\{h_1\}, \{h_2\}, \{h_4\}, \{h_5\}), \\ Q(\text{hard}) &= (\{h_1, h_3\}, \{h_2\}, \{h_4\}, \{h_5\}). \end{aligned}$$

Cardinalities:

$$\begin{aligned} |Q_T^s(\text{easy})| &= 1, |Q_T(\text{easy})| = 1, |Q_F(\text{easy})| = 1, |Q_F^s(\text{easy})| = 1; \\ |Q_T^s(\text{hard})| &= 2, |Q_T(\text{hard})| = 1, |Q_F(\text{hard})| = 1, |Q_F^s(\text{hard})| = 1. \end{aligned}$$

Embed via ι to obtain a 5V-ISS $R := \iota(Q)$:

$$\begin{aligned} R(\text{easy}) &= (\{h_1\}, \{h_2\}, \emptyset, \{h_4\}, \{h_5\}), \\ R(\text{hard}) &= (\{h_1, h_3\}, \{h_2\}, \emptyset, \{h_4\}, \{h_5\}). \end{aligned}$$

Project back:

$\Pi(R)(\text{easy}) = (\{h_1\}, \{h_2\}, \{h_4\}, \{h_5\}) = Q(\text{easy}), \quad \Pi(R)(\text{hard}) = (\{h_1, h_3\}, \{h_2\}, \{h_4\}, \{h_5\}) = Q(\text{hard}).$

Hence $(\Pi \circ \iota)(Q) = Q$ with literal set equality in all coordinates. To witness strict extension, define R' by taking $R'_N(\text{easy}) = \{h_3\}$ and all other coordinates equal to R ; then $R' \notin \text{ISS}_5^{(0)}(A, H)$, so there is no Q' with $R' = \iota(Q')$.

3. Conclusions

In this paper, we defined five variants: (i) **Single-valued**, mapping each attribute value to one subset capturing undirected indeterminacy; (ii) **Double-valued**, splitting into truth-leaning and falsity-leaning slices; (iii) **Triple-valued**, adding a neutral slice; (iv) **Quadruple-valued**, refining polarity by distinguishing strong and ordinary truth/falsity leanings; and (v) **Quintuple-valued**, further introducing a central neutral band between the two strengths. For clarity, the overall summary of the IndetermSoft sets discussed in this paper is presented in Table 1.

Table 1. Overview of IndetermSoft Set variants (per attribute value)

Variant	Mapping	Indeterminacy slices	Notes / Generalization
Single-valued	$F : A \rightarrow \mathcal{P}(H)$	undirected	Minimal form: one subset capturing ambiguity without truth/falsity polarity.
Double-valued	$F : A \rightarrow \mathcal{P}(H)^2$	T -leaning; F -leaning	Splits ambiguity by polarity; allows intersections for conflicting signals.
Triple-valued	$G : A \rightarrow \mathcal{P}(H)^3$	T -leaning; neutral; F -leaning	Extends Double by adding a neutral band; projects to Double by dropping neutral.
Quadruple-valued	$Q : A \rightarrow \mathcal{P}(H)^4$	strong- T ; T ; F ; strong- F	Refines polarity strength; recovers Triple by merging strong/ordinary on each side.
Quintuple-valued	$R : A \rightarrow \mathcal{P}(H)^5$	strong- T ; T ; neutral; F ; strong- F	Strict extension of Quadruple; inserts neutral between strengths for finer control.

In the future, we intend to extend the concepts developed in this paper by employing HyperSoft Sets [26–28], SuperHyperSoft Sets [29–31], TreeSoft Sets [32,33], ForestSoft Sets [34–36], HyperNeutrosophic Sets [37], Plithogenic Sets [38–40], Graphs [41], HyperGraphs [42,43], and SuperHyperGraphs [44,45].

Author Contributions: Conceptualization, Takaaki Fujita; Investigation, Takaaki Fujita; Methodology, Takaaki Fujita; Writing – original draft, Takaaki Fujita; Writing – review & editing, All authors.

Funding: This study did not receive any financial or external support from organizations or individuals.

Institutional Review Board Statement: As this research is entirely theoretical in nature and does not involve human participants or animal subjects, no ethical approval is required.

Data Availability Statement: This research is purely theoretical, involving no data collection or analysis. We encourage future researchers to pursue empirical investigations to further develop and validate the concepts introduced here.

Use of Artificial Intelligence: I use generative AI and AI-assisted tools for tasks such as English grammar checking, and I do not employ them in any way that violates ethical standards.

Acknowledgments: We extend our sincere gratitude to everyone who provided insights, inspiration, and assistance throughout this research. We particularly thank our readers for their interest and acknowledge the authors of the cited works for laying the foundation that made our study possible. We also appreciate the support

from individuals and institutions that provided the resources and infrastructure needed to produce and share this paper. Finally, we are grateful to all those who supported us in various ways during this project.

Conflicts of Interest: The authors confirm that there are no conflicts of interest related to the research or its publication.

References

1. Maji, P.K.; Biswas, R.; Roy, A.R. Soft set theory. *Computers & mathematics with applications* **2003**, *45*, 555–562.
2. Fujita, T.; Smarandache, F. An introduction to advanced soft set variants: Superhypersoft sets, indeterminsuperhypersoft sets, indetermintreesoft sets, bihypersoft sets, graphisoft sets, and beyond. *Neutrosophic Sets and Systems* **2025**, *82*, 817–843.
3. Jose, J.; George, B.; Thumbakara, R.K. Soft directed graphs, their vertex degrees, associated matrices and some product operations. *New Mathematics and Natural Computation* **2023**, *19*, 651–686.
4. Marfetan, V.d.R.M.; Chicaiza, L.G.T.; Chicaiza, S.A.P.; Sanchez, E.M.O. Classification of cases of animal abuse in Ecuador using IndetermSoft and C4. 5 algorithms. *Neutrosophic Sets and Systems* **2025**, *92*, 121–133.
5. Caballero, E.G.; Moscoso-Paucarchuco, K.M.; Hernandez, N.B.; Torres, L.J.C.; Leyva, M.; Rodríguez, V.G.G. Algorithms of Designing Decision Trees From Indeterm Soft Sets. In *Neutrosophic and Plithogenic Inventory Models for Applied Mathematics*; IGI Global Scientific Publishing, 2025; pp. 561–586.
6. Wei, W.; Peng, P. Weighted IndetermSoft Set for Prioritized Decision-Making with Indeterminacy and Its Application to Green Competitiveness Evaluation in Equipment Manufacturing Enterprises. *Neutrosophic Sets and Systems* **2025**, *85*, 1018–1026.
7. Yang, H.; Lin, C. A Recursive IndetermTree Soft Set (RIT-Soft Set) for Dynamic and Uncertain Performance Evaluation in College Competitive Sports. *Neutrosophic Sets and Systems* **2025**, *85*, 874–886.
8. Shen, T.; Mao, C. Sustainability Impact of Online Consumption Behavior from the Perspective of Digital Empowerment: IndetermSoft Set with Application. *Neutrosophic Sets and Systems* **2025**, *82*, 24.
9. Smarandache, F. New Types of Soft Sets: HyperSoft Set, IndetermSoft Set, IndetermHyperSoft Set, and TreeSoft Set. *International Journal of Neutrosophic Science* **2023**.
10. Krishnamurthy, B.; Shiva, S.G. Indetermsoft-Set-Based D* Extra Lite Framework for Resource Provisioning in Cloud Computing. *Algorithms* **2024**, *17*, 479.
11. Smarandache, F. *Introduction to the n-SuperHyperGraph-the most general form of graph today*; Infinite Study, 2022.
12. Smarandache, F. *New types of soft sets "hypersoft set, indetermsoft set, indetermhypersoft set, and treesoft set": an improved version*; Infinite Study, 2023.
13. Wang, H.; Smarandache, F.; Zhang, Y.; Sunderraman, R. *Single valued neutrosophic sets*; Infinite study, 2010.
14. Broumi, S.; Talea, M.; Bakali, A.; Smarandache, F. Single valued neutrosophic graphs. *Journal of New theory* **2016**, pp. 86–101.
15. Broumi, S.; Bakali, A.; Bahnasse, A. Neutrosophic sets: An overview. *Infinite Study* **2018**.
16. Kandasamy, I. Double-valued neutrosophic sets, their minimum spanning trees, and clustering algorithm. *Journal of Intelligent systems* **2018**, *27*, 163–182.
17. Lin, L. Double-Valued Neutrosophic Offset for Enhancing Humanistic Competence: An Effectiveness Study of Humanities Instruction in Vocational College Students. *Neutrosophic Sets and Systems* **2025**, *88*, 680–689.
18. Du, K.; Du, Y. Research on performance evaluation of intangible assets operation and management in sports events with double-valued neutrosophic sets. *J. Intell. Fuzzy Syst.* **2023**, *45*, 2813–2822.
19. Guo, Y. Enhancing DVNN-WCSM Technique for Double-Valued Neutrosophic Multiple-Attribute Decision-Making in Digital Economy: A Case Study on Enhancing the Quality of Development of Henan's Cultural and Tourism Industry. *Neutrosophic Sets and Systems* **2025**, *75*, 391–407.
20. Peng, H.g.; Zhang, H.y.; Wang, J.q. Probability multi-valued neutrosophic sets and its application in multi-criteria group decision-making problems. *Neural Computing and Applications* **2018**, *30*, 563–583.
21. Peng, J.j.; Wang, J.q. Multi-valued neutrosophic sets and its application in multi-criteria decision-making problems. *Neutrosophic Sets and Systems* **2015**, *10*, 6.
22. Wang, H. Professional Identity Formation in Traditional Chinese Medicine Students: An Educational Perspective using Triple-Valued Neutrosophic Set. *Neutrosophic Sets and Systems* **2025**, *88*, 83–92.
23. Fujita, T. Triple-, Quadruple-, and Quintuple-Valued Neutrosophic Offsets: Extended Models for Off Uncertainty Representation **2025**.

24. Fujita, T. Triple-Valued Neutrosophic Set, Quadruple-Valued Neutrosophic Set, Quintuple-Valued Neutrosophic Set, and Double-valued Indeterministic Set. *Neutrosophic Systems with Applications* **2025**, *25*, 3. <https://doi.org/10.61356/2993-7159.1276>.
25. Meng, W. Quintuple-Valued Neutrosophic Offset for Quality Evaluation of Cross-Border E-Commerce Talent Training Based on Artificial Intelligence. *Neutrosophic Sets and Systems* **2025**, *88*, 834–844.
26. Smarandache, F. Extension of soft set to hypersoft set, and then to plithogenic hypersoft set. *Neutrosophic sets and systems* **2018**, *22*, 168–170.
27. Ihsan, M.; Rahman, A.U.; Saeed, M.H. Hypersoft Expert Set With Application in Decision Making for Recruitment Process. 2021.
28. Musa, S.Y.; Asaad, B.A. Topological structures via bipolar hypersoft sets. *Journal of Mathematics* **2022**, *2022*, 2896053.
29. Salamai, A.A. A SuperHyperSoft Framework for Comprehensive Risk Assessment in Energy Projects. *Neutrosophic Sets and Systems* **2025**, *77*, 614–624.
30. Mohamed, M.; AbdelMouty, A.M.; Mohamed, K.; Smarandache, F. SuperHyperSoft-Driven Evaluation of Smart Transportation in Centroidous-Moosra: Real-World Insights for the UAV Era. *Neutrosophic Sets and Systems* **2025**, *78*, 149–163.
31. Smarandache, F. Foundation of the SuperHyperSoft Set and the Fuzzy Extension SuperHyperSoft Set: A New Vision. *Neutrosophic Systems with Applications* **2023**, *11*, 48–51.
32. Myvizhi, M.; A Metwaly, A.; Ali, A.M. TreeSoft Approach for Refining Air Pollution Analysis: A Case Study. *Neutrosophic Sets and Systems* **2024**, *68*, 17.
33. Smarandache, F. TreeSoft Set vs. HyperSoft Set and Fuzzy-Extensions of TreeSoft Sets. *HyperSoft Set Methods in Engineering* **2024**.
34. Song, L.; Liu, J.; Ding, H.; Zhang, W. ForestSoft Set for Mechanical Automation Production Control Systems Analysis Based on an Intelligent Manufacturing Environment. *Neutrosophic Sets and Systems* **2025**, *85*, 229–254.
35. Luo, H. ForestSoft Set Approach for Estimating Innovation and Entrepreneurship Education in Universities through a Hierarchical and Uncertainty-Aware Analytical Framework. *Neutrosophic Sets and Systems* **2025**, *86*, 332–342.
36. Jin, H. Valuation of Building Facade Design Effects Using ForestSoft Hypergraphs and Virtual Simulation Technology. *Neutrosophic Sets and Systems* **2025**, *86*, 171–183.
37. Fujita, T. *Advancing Uncertain Combinatorics through Graphization, Hyperization, and Uncertainization: Fuzzy, Neutrosophic, Soft, Rough, and Beyond*; Biblio Publishing, 2025.
38. Smarandache, F. *Plithogenic set, an extension of crisp, fuzzy, intuitionistic fuzzy, and neutrosophic sets-revisited; Infinite study*, 2018.
39. Azeem, M.; Rashid, H.; Jamil, M.K.; Gütmen, S.; Tirkolaei, E.B. Plithogenic fuzzy graph: A study of fundamental properties and potential applications. *Journal of Dynamics and Games* **2024**, pp. 0–0.
40. Kandasamy, W.V.; Ilanthenral, K.; Smarandache, F. *Plithogenic Graphs*; Infinite Study, 2020.
41. Diestel, R. *Graph theory*; Springer (print edition); Reinhard Diestel (eBooks), 2024.
42. Berge, C. *Hypergraphs: combinatorics of finite sets*; Vol. 45, Elsevier, 1984.
43. Bretto, A. Hypergraph theory. *An introduction. Mathematical Engineering*. Cham: Springer **2013**, *1*.
44. Smarandache, F. *Extension of HyperGraph to n-SuperHyperGraph and to Plithogenic n-SuperHyperGraph, and Extension of HyperAlgebra to n-ary (Classical-/Neutro-/Anti-) HyperAlgebra*; Infinite Study, 2020.
45. Hamidi, M.; Smarandache, F.; Davneshvar, E. Spectrum of superhypergraphs via flows. *Journal of Mathematics* **2022**, *2022*, 9158912.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.