

In Vitro Quantified Determination of β -Amyloid 42 Peptides, a Biomarker of Neuro-Degenerative Disorders, in PBS and Human Serum Using a Simple, Cost-effective Thin Gold Film Biosensor

Yifan Dai¹, Alireza Molazemhosseini² and Chung Chiun Liu^{1*}

¹ Department of Chemical & Biomolecular Engineering and Electronics Design Center, Case Western Reserve University, 10900 Euclid Avenue, Cleveland, OH 44106, USA; yxd176@case.edu

² Dip. Chimica Materiali e Ing. Chimica "Giulio Natta", Politecnico di Milano, Via Mancinelli 7, 20131, Italy; axm1058@case.edu

*Correspondence: cxl9@case.edu; Tel: +1-216-368-2935

Abstract

A simple *in vitro* biosensor for the detection of β -amyloid 42 in phosphate-buffer saline (PBS) and undiluted human serum was fabricated and tested based on our platform sensor technology. The bio-recognition mechanism of this biosensor was based on the effect of the interaction between antibody and antigen of β -amyloid 42 to the redox couple probe of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$. Differential pulse voltammetry (DPV) served as the transduction mechanism measuring the current output derived from the redox coupling reaction. The biosensor was a three-electrode electrochemical system, and the working and counter electrodes were 50 nm thin gold film deposited by sputtering technique. The reference electrode was a thick-film printed Ag/AgCl electrode. Laser ablation technique was used to define the size and structure of the biosensor. Cost-effective roll-to-roll manufacturing process was employed in the fabrication of the biosensor making it simple and relatively inexpensive. Self-assembled monolayers (SAM) of 3-Mercaptopropionic acid (MPA) was employed to covalently immobilize the thiol group on the gold working electrode. A carbodiimide conjugation approach using N-(3-dimethylaminopropyl)-N'-ethylcarbodiimide hydrochloride (EDC) and N-hydroxysuccinimide (NHS) was undertaken for cross-linking antibody of β -amyloid 42 to the carboxylic groups on one end of the MPA. The antibody concentration of β -amyloid 42 used was 18.75 $\mu\text{g/mL}$. The concentration range of β -amyloid 42 in this study was from 0.0675 $\mu\text{g/mL}$ to 0.5 $\mu\text{g/mL}$ for both PBS and undiluted human serum. DPV measurements showed excellent response in this antigen concentration range. Interference study of this biosensor was carried out in the presence of Tau protein antigen. Excellent specificity of this β -amyloid 42 biosensor was demonstrated without interference by other species such as T-tau protein.

Keywords

β -amyloid 42; differential pulse voltammetry; Neuro-degenerative disorders; ferrocyanide/ferricyanide redox couple

1. Introduction

Diagnosis of neuro-degenerative disorders, particularly Alzheimer's Disease (AD), is difficult and inconclusive. Brain imaging and biomarkers of cerebrospinal fluid (CSF) have been advocated for technical diagnosis of AD [1]. The CSF biomarkers include total tau (T-tau), hyperphosphorylated tau (P-tau), and the 42 amino acid isoforms of amyloid β (β -amyloid 42) [1-3]. β -amyloid 42 pathophysiology leads to plaque deposition and it also can accelerate antecedent limbic and brain tauopathy [4-6]. Scientifically, the diagnosis of AD follows two pathways: the tauopathy and the amyloidopathy. In the tauopathy, the detection of T-tau and P-tau proteins are considered to be essential [7]. In the amyloidopathy, the measurement of β -amyloid 42 is important [8]. In practical assessment, the examination of β -amyloid 42 accumulated in senile plaques and intracellular neurofibrillary tangles of P-tau is considered the hallmark of identification of AD [2, 3]. Unfortunately, the assessment of the β -amyloid 42 accumulations is often performed post mortem without providing an early and meaningful assessment of β -amyloid 42 for the progression of AD [2, 7, 8] and other amyloid related diseases.

Therefore, it will be advantageous to detect β -amyloid 42 and use it as a biomarker for the assessment of the progression or the pathological process at an early stage of AD. β -amyloid 42 has been used as a biomarker in CSF for AD. Detection of β -amyloid 42 has been exploited using different analytical techniques, such as mass spectrometry [9], surface plasmon resonance [10], scanning tunneling microscopy [11], electrophoresis [12, 13], the enzyme-linked immunosorbent assay (ELISA) [14], and others. Detection of β -amyloid 42 by the ELISA technique is commonly used in liquid-based test samples. However, various research groups have reported that the standard ELISA test technique can give a very high measurement background resulting in flawed and inconclusive assessment of β -amyloid [10, 15-17]. Furthermore, the ELISA technique is elaborate and requires a skilled operator. Measurement of β -amyloid 42 in CSF is valuable, however, the collection of CSF remains to be a complicate and expensive procedure. It will be more attractive and practical for β -amyloid 42 to be detected in other physiological fluid including plasma, serum, and others. Consequently, research efforts have been devoted to detecting β -amyloid 42 in physiological fluid other than CSF [17-21]. Therefore, it is desirable to have a simple-use detection method for β -amyloid 42 in a physiological fluid other than CSF, such as serum and others. It is necessary that this detection technique for β -amyloid 42 has the needed sensitivity and selectivity to make the quantification of β -amyloid 42 meaningful for practical applications, such as the production, accumulation and clearance of β -amyloid 42 under the physiological and patho-physiological scenarios [21].

Biosensors provide a potential opportunity in this advancement. Researchers have explored the use of different modified electrodes for bio-sensing applications, such as graphene and graphene-based materials, graphene hybrids, chemical doping, as well as magnetic doping materials including Fe_3O_4 nano-magnetic particles [22-27]. These modifications are elegant and elaborate but with limited sensor uniformity and reproducibility; calibration of individual biosensor is often required and time-consuming. Consequently, practical and extensive use of the modified sensors for β -amyloid 42 measurement remains limited.

In this study, a single-use, disposable, cost-effective *in vitro* miniature biosensor capable of detecting β -amyloid 42 in serum was developed. The bio-recognition mechanism was based on the interaction of antibody and antigen of β -amyloid 42. The effect of this interaction on a well-established redox couple reaction, $\text{Fe}^{+2}/\text{Fe}^{+3}$, as $\text{K}_4\text{Fe}(\text{CN})_6$ and $\text{K}_3\text{Fe}(\text{CN})_6$ in solution form, was used as the transduction

mechanism in this development. Differential pulse voltammetry (DPV) measured the current output resulting from the electrochemical reaction of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$ which was influenced by the interaction between the antibody and the antigen of β -amyloid 42. This current output can then be used to quantify β -amyloid 42 level at a known quantity of the antibody of β -amyloid 42. DPV applied a linear sweep voltammetry with a series of regular voltage pulses superimposed on the linear potential sweep. The current was then measured immediately before each potential change. Thus, the effect of the charging current could be minimized, achieving a higher sensitivity. The biosensors were manufactured by the industrial roll-to-roll process which was very cost-effective. The thin gold film electrodes were deposited by sputtering physical vapor deposition at atomic level. Thus, the working and counter thin gold film electrode elements were uniform and highly reproducible. In this study, a concentration range of 0.0625 μ g/mL to 0.5 μ g/mL of β -amyloid 42 antigens was investigated. Both phosphate buffered saline (PBS) of 0.1 M and human serum were used as the test media. The selectivity of this biosensor was examined using an interference study by the T-Tau in the concentrations of 0.125 μ g/mL and 0.5 μ g/mL at corresponding β -amyloid 42 antigen concentrations. The interference study results showed excellent selectivity. All measurements were carried out at room temperature (23° C).

2. Materials and Equipment

2.1 Reagents and Apparatus

Anti- β amyloid 1-42 (#ab180956) and recombinant human β -amyloid 1-42 protein (#ab82795) was purchased from Abcam (Cambridge, MA, USA). Tau protein ladder (#T7951) was purchased from Sigma Aldrich (St. Louis, MO, USA). Phosphate buffered saline (PBS) 1.0 M (pH=7.4), 3-Mercaptopropionic acid (MPA), N-(3-dimethylaminopropyl)-N'-ethylcarbodiimide hydrochloride (EDC) and N-hydroxysuccinimide (NHS) were also purchased from Sigma-Aldrich (St. Louis, MO, USA). Concentrated H_2SO_4 (95.0 to 98.0 w/w %), concentrated HNO_3 (70% w/w %) were received from Fisher Scientific (Pittsburgh, PA, USA). Human serum (Cat. # 3667), $K_3Fe(CN)_6$ and $K_4Fe(CN)_6$ (Cat# P3289 and P3667) were obtained from Sigma-Aldrich (St. Louis, MO, USA). All the chemicals were used without further purification. A CHI 660C (CH Instrument, Inc., Austin, TX) Electrochemical Workstation was used for DPV and the electrochemical impedance spectroscopy (EIS) characterization investigations.

2.2 Design and Fabrication of the Biosensor

This β -amyloid 42 biosensor was based on our platform sensor design and fabrication. The biosensor was a three-electrode configuration electrochemical sensor. Both the working and counter electrodes were thin gold film in 50 nm thickness, and the reference electrode was a thick-film printed Ag/AgCl electrode. The thin gold film was deposited by sputtering physical vapor deposition on the atomic level, without any binder as done in thick film printing. Consequently, the electrodes were very uniform and highly reproducible. Laser ablation technique was used to define the design structure and size of the biosensor and each electrode elements. Nazdar APL 34 silicone-free dielectric thick film ink was used for the insulation layer defining the biosensor structure. Polyethylene terephthalate (PET) was used as the substrate for the fabrication of the biosensor. The overall dimensions of an individual biosensor were 33.0 x 8.0 mm². The working electrode area was 1.54 mm² accommodating 15-25 μ L of liquid test sample. The manufacturing of the biosensor was accomplished on a cost-effective roll-to-roll process resulting in a cost-effective, single-use, disposable *in vitro* biosensor for β -amyloid 42 detection. Typically, each sheet of PET substrate (355 x 280 mm²) would produce 100 individual biosensors in 4 rows. More detailed explanation of the design and fabrication of this platform biosensor were reported elsewhere [28, 29].

3. Functionalization of the Biosensor

3.1 Chemical cleaning of the Biosensor

Chemical cleaning was the first step of the functionalization of the biosensor. This cleaning step eliminated any oxidized compounds and residue from the gold film electrode minimizing the electrode charge transfer resistance, thereby enhancing the sensitivity and reproducibility of the biosensor. This process was a 3-step chemical pretreatment procedure and it was based on the study by others [30, 31] as well as in our own previous studies [29, 32] with minor modifications. Typically, a batch of 8 thin gold film based biosensors were immersed in a 2M KOH solution for 15min. After rinsing with copious amounts of DI water for about 30 seconds, the biosensors were placed in a 0.05 M H₂SO₄ solution (95.0 to 98.0 w/w %) for another 3-5 min. DI water was then used to rinse the biosensor prototypes for another 30 seconds. The biosensors were then placed in a 0.05 M HNO₃ solution (70% w/w %) for another 3-5 minutes. The biosensors were rinsed one more time with DI water for 30 seconds and dried gently in a stream of nitrogen. Electrochemical Impedance Spectroscopy (EIS) was employed to assess the success of this cleaning process. A solution of K₄Fe (CN)₆ and K₃Fe (CN)₆ of 5 mM in each component, was prepared in 0.1 M PBS and used for EIS tests. Typically, two groups of the biosensors were used in this test. One group of the biosensors were subjected to the cleaning protocol described above, whereas another group of the biosensors were cleaned by ethanol and deionized water (DIW) sequentially. 20 µL of the redox couple, K₄Fe (CN)₆ and K₃Fe (CN)₆ solution prepared was placed on top of the sensing area of each biosensor for electrochemical impedance spectroscopy (EIS) test. The EIS study of the pretreated biosensors showed excellent reproducibility identical to the results reported in our previous studies [28, 29].

3.2 Functionalization of the Biosensor

The functionalization of the biosensor was accomplished in two steps. The first step was to establish a thiol bond which provided an excellent affinity to the gold film electrode surface. The second step was to functionalize the carboxylic group at the other end of the thiol bond for the attachment of the antibody of β-amyloid 42. Thiol modification of the gold electrode surface used in this study is a well-acknowledged technique (33-37).

Self-assembled monolayers (SAM) of 3-Mercaptopropionic acid (MPA) were used in the first step of this procedure (33-37). Typically, 8 biosensors were prepared in this immobilization step as a batch. 1 mM solution of 3-MPA in ethanol was first prepared and the biosensors were immersed in this solution for 24 h in the dark, then the biosensors were rinsed with DI water and dried gently in a stream of N₂. The second step of this functionalization process was then carried out. In this second step, the carboxylic groups on the other end of the 3-MPA-modified gold film electrodes (AuEs) were then functionalized by incubating in a 0.1 M PBS (pH = 7.4) solution containing 0.25 M EDC and 0.05 M NHS for 5 h. The activated AuEs were then rinsed by 0.1 M PBS and dried by N₂ flow gently. 20 µL of 18.75 µg/mL anti-β-amyloid 42 was placed on the sensing area of each AuE and left to dry overnight at 4 °C. Antibody immobilized biosensors were rinsed with 0.1 M PBS and stored at 4 °C.

3.3 Differential Pulse Voltammetry (DPV) Measurement

Cyclic voltammetry (CV) and chronoamperometry (CA) are generally used in biomedical measurements. CV and CA provide sufficient sensitivity in practical biomedical applications. The required electronic interface for CV and CA are relatively simple. Differential Pulse Voltammetry (DPV) is a well-established

electroanalytical technique [38], however, its applications to biomedical measurement has not been fully exploited. DPV applies a series of regular potential pulse superimposed on the potential stair steps. The current is then measured immediately prior to each potential change. Consequently, the charging current can be minimized resulting in a higher sensitivity. DPV has shown effective and sensitive measurement in our previous studies of hemoglobin A1c (HbA1c), T-tau and 17 β -estradiol detections (29, 32, 39), and it is also used in this β -amyloid 42 study. In this study, the antibody of β -amyloid 42 was first bonded and functionalized as described above. The biosensors were then immersed in β -amyloid 42 antibody solution for 20 h at 4°C. For testing, the antigen solutions of β -amyloid 42 were prepared both in 0.1 M PBS, and undiluted human serum. After the incubation, the biosensors were rinsed with 0.1M PBS removing any unbounded antibody of β - amyloid 42. A solution of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$, 5 mM in each component, was prepared in 0.1 M PBS and 20 μ L of this redox probe was placed on top of the sensing area of the biosensor, and DPV measurements were then took place.

4. Results and Discussion

4.1 Preparation of β -amyloid 42 Antigen Solutions

Self-assembly of β -amyloid 42 peptides was well-recognized in previous studies [40, 41]. In order to prevent aggregation of β -amyloid 42 peptides, dimethyl sulfoxide (DMSO) was first applied for dissolving β -amyloid 42 peptides directly. Previous reports proved that DMSO solvent was effective in slowing the aggregation rate of β -amyloid peptides, and our previous study proved that DMSO has no interference with PBS solution [39]. After dissolving the peptides with DMSO, 0.1M PBS solution or human serum was used for further dilution to different antigen concentrations. Detectable concentration range of β -amyloid 42 was determined by the structure of immunoglobulin G (IgG) type antibody used in this study. High affinity of IgG antibody to human peptides antigen was shown in a previous study [44]. IgG type antibody contained two moles of binding sites for each mole of antibody, so a maximum of 1 to 2 mole ratio of antibody to antigen could be reached by using IgG antibody for human peptides. Therefore, the highest concentration of β -amyloid 42 antigens was determined based on the mole ratio of antibody to antigen. Detectable concentration of β -amyloid 42 in this study ranged from 0.0625 μ g/mL to 0.5 μ g/mL.

4.2 Detection of β -amyloid 42 in PBS solution

The incubation time of β -amyloid 42 was pivotal to the success of the detection. An ideal incubation time should produce the strongest current signal without interference from aggregation of antigen during the incubating process. Thus, the optimized incubation time was investigated using a 0.5 μ g/mL β -amyloid 42 antigen solution and then the DPV measurement was conducted at the presence of 5 mM of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$ on the electrode surface at different incubation times. The volume of both the β -amyloid 42 solution and $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$ redox solution on the sensor were 20 μ L. Figure 1 shows the different current outputs based on different incubation times. A relatively high signal was produced after 30min incubation at room temperature. For an incubation time longer than 30 min, the width of the DPV curve became larger, which may indicate an inhomogeneous distribution of surface particles due to aggregation of β -amyloid 42. The results of this study was consistent with previous research reported [27, 45, 46]. Therefore, an Incubation time of β -amyloid 42 antigen for 30 minutes was chosen for this study.




Figure1. Optimized incubation time of β -amyloid 42

For DPV measurement, 20 μ L of prepared β -amyloid 42 antigen solution was placed on top of each biosensor for 30 min at room temperature. After incubation for 30 minutes, the biosensor was rinsed by PBS. 20 μ L of a redox probe couple solution containing 5mM each of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$ was then added on top of the biosensor after the incubation of the antigen of β -amyloid 42 and DPV measurement was then made. Based on the radicalization of β -amyloid 42 thin film after incubation, larger concentration of β -amyloid 42 sample produced a higher conductivity or lower resistance on the electrode surface with the use of redox probe couple [27, 45]. Figure2a shows the DPV measurements of β -amyloid 42 ranging from 0.0675 μ g/mL to 0.5 μ g/mL with a decreasing sequence of current output. Figure2b shows the calibration curve of the DPV measurements based on the concentration of β -amyloid 42 antigen and the corresponding current outputs with a linear fit equation of $Y=7.74X+6.28$. The R square value of 0.85 shows a high reproducibility of the biosensor with $n=3$.




Figure2. a) DPV measurement of β -amyloid 42 antigens with concentrations ranging from 0.0675 μ g/mL to 0.5 μ g/mL in PBS and b) Calibration curve based on the DPV measurement of β -amyloid 42 in PBS ($n=3$).

4.3 Detection of β -amyloid 42 in Human Serum

Measurements based on β -amyloid 42 in human serum sample were also conducted. Instead of diluting the pre-dissolved DMSO β -amyloid 42 sample in PBS, human serum was used for further dilution for testing. The β -amyloid 42 antigen concentrations range was $0.0675\mu\text{g/mL}$ to $0.5\mu\text{g/mL}$. First, $20\mu\text{L}$ of the prepared β -amyloid 42 solution in human serum was placed on top of the biosensor for 30 min at room temperature. The sensor was rinsed with PBS before testing. Similar to the DPV measurement in PBS solution testing described above, $20\mu\text{L}$ of a redox probe couple solution containing 5mM each of $\text{K}_4\text{Fe}(\text{CN})_6$ and $\text{K}_3\text{Fe}(\text{CN})_6$ was then added on top of the biosensor after the incubation of the antigen of β -amyloid 42 and DPV measurement was then made. A calibration curve of $Y=6.55X+6.70$ with R square value of 0.94 showed a good reproducibility of the biosensors in human serum testing media with $n=3$.




Figure3. a) DPV measurement of β -amyloid 42 antigens with concentrations ranging from $0.0675\mu\text{g/mL}$ to $0.5\mu\text{g/mL}$ in human serum and b) Calibration curve based on the DPV measurement of β -amyloid 42 in human serum ($n=3$).

4.4 Interference Study of β -amyloid 42 Sensor against Tau Protein Antigen

Tau protein antigen was also a significant biomarker for neuro-degenerative disease [1, 2, 3]. Tau protein was investigated in another study conducted with a similar platform binding technique [32]. In order to evaluate the selectivity of our biosensor, Tau protein antigen was used as the potential interference chemical. For preparation of the antigen solution, $0.125\mu\text{g/mL}$ and $0.5\mu\text{g/mL}$ of β -amyloid 42 antigen solutions were mixed with the same amount of Tau protein antigen. $20\mu\text{L}$ of the mixture of β -amyloid 42 antigen and Tau protein antigen was dropped on the sensor for incubation for 30 minutes and then $20\mu\text{L}$ of 5mM redox solution of $\text{K}_4\text{Fe}(\text{CN})_6$ and $\text{K}_3\text{Fe}(\text{CN})_6$ was dropped on the sensor for testing. Figure 4 shows the responses from pure beta-amyloid sample and mixed Tau protein and amyloid sample. Similar current outputs were observed from the DPV measurements, indicating that

Tau protein amyloid sample. Similar current outputs were observed from the DPV measurements, indicating that Tau protein antigen did not contribute to the DPV measurement of β -amyloid 42 antigen. This interference study demonstrated the high selectivity of our β -amyloid 42 biosensor.




Figure4. Interference study based on Tau protein antigen.

5. Conclusion

A cost-effective single-use, *in vitro* biosensor for the detection of a biomarker of neuro-degenerative disorder, β -amyloid 42 has been designed, manufactured and evaluated in phosphate-buffer saline and in undiluted human serum. The bio-recognition mechanism of this biosensor was based on the effect of the interaction between antibody and antigen of β -amyloid 42 to the redox couple probe of $K_4Fe(CN)_6$ and $K_3Fe(CN)_6$. Differential pulse voltammetry (DPV) was the transduction mechanism and used as the measurement technique. Measurements of β -amyloid 42 antigens in both 0.1M PBS and undiluted human serum over the concentration range of $0.0675\mu\text{g/mL}$ to $0.5\mu\text{g/mL}$ showed excellent results and good linearity of the calibration curves. The antibody concentration of β -amyloid 42 used was $18.75\mu\text{g/mL}$. Tau protein antigen was used in the interference study, and this β -amyloid 42 biosensor demonstrated excellent specificity as shown without interference by Tau protein antigen. This biosensor platform technology can be further optimized and can be applied to detect other biomarkers of neuro-degenerative disorders.

Acknowledgments: Alireza Molazemhosseini, gratefully acknowledges Italian Ministry of Education, Universities and Research (MIUR) for his PhD scholarship and Electronics Design Center of CWRU for their financial support. Financial support by Wallace R. Persons research fund from Case Alumni Association (CAA) for this research is also acknowledged.

Author Contributions: C.C.L. and A.M. conceived and designed the experiments; Y.D. and A.M. performed the experiments; C.C.L., A.M. and Y.D. analyzed the data; Y.D., A.M. and C.C. L. all contributed to prepare this manuscript.

Conflicts of Interest: The authors confirm that this article content has no conflict of interest

References:

- (1) Rosen C, Hansson O, Blennow K, Zetterberg H. Fluid biomarkers in Alzheimer's diseases-current concepts, *Molecular Neurodegeneration* (2013), 8:20; <http://www.molecularneurodegeneration.com/content/8/1/20>.
- (2) McKhann G, Drachman D, Folstein M, Katzman R, Price D, Stadlan EM. Clinical diagnosis of Alzheimer's disease: report of the NINCDS-ADRDA work group under the auspices of department of health and human services task force on Alzheimer's disease. *Neurology*, (1984), 34: 939–944.
- (3) Blennow K, de Leon MJ, Zetterberg H: Alzheimer's disease. *Lancet*, (2006) 368:387-403.
- (4) Jack CR, Jr. et al. Tracking pathophysiological process in Alzheimer's disease: an updated hypothetical model of dynamic biomarkers, *The Lancet Neurology*, (2013) 12: 207-216.
- (5) Hardy J, Higgins G. Alzheimer's diseases: the amyloid cascade hypothesis, *Science*, (1992) 256:184-185.
- (6) Golde TE, Eckman CB, Younkin SG. Biochemical detection of A β isoforms: implications for pathogenesis, diagnosis and treatment of Alzheimer's diseases, *Biochimica et Biophysica Acta(BBA)-Molecular Basis of Diseases*, (2000)1502:172-187.
- (7) Hampel H, Blennow K, Shaw LM, Hoessler YC, Zetterberg H, Trojanowski JQ. Total and phosphorylated tau protein as biological markers of Alzheimer's disease, *Exp. Gerontol.* (2010) 43(1):30-51; doi: 10.1016/j.exger.2009.10.010. and the references within.
- (8) Funke SA, Birkmann E, Willbold D. Detection of amyloid-beta aggregated in bodyfluids: a suitable method for early diagnosis of Alzheimer's diseases? *Current Alzheimer Research* (2009)6(3):285-289. and the references within
- (9) Wang R, Sweeney D, Gandy SE, Sisodia SS. The profile of soluble amyloid beta protein in cultured cell media-detection and quantification of amyloid protein and variants by immunoprecipitation mass spectrometry, *Journal of Biological Chemistry*, (1996) 271: 31894-31902.
- (10) Haes AJ, Chang L, Klein WL, Van Duyne RP. Detection of a biomarker for Alzheimer's disease from synthetic and clinical samples using a nanoscale optical biosensor, *J. Am. Chem. Soc.* (2005)127:2264-2271.
- (11) Kang DY, Lee JH, Oh BK, Choi JW. Ultra-sensitive immunosensor for beta-amyloid (1-42) using scanning tunneling microscopy β -based electrical detection, *Biosens. Bioelectron.* (2009) 24:1431-1436.
- (12) Picou R, Moses JP, Wellman AD, Kheterpal I, Gilman SD. Analysis of monomeric A β (1-40) peptide by capillary electrophoresis *Analyst*, (2010)135: 1631-1635.
- (13) Hestekin C, Kurtz J, Lutz-Rechtin T. Microchannel electrophoresis for rapid, low concentration detection of early amyloid-beta aggregation *Alzheimer & Dementia* (2014) 10: 794-795.
- (14) Gravina SA et al. Amyloid β protein (A β) in Alzheimer's diseases brain biochemical and immunocytochemical analysis with antibodies specific for forms ending at A β 40 or A β 42 (43), *Journal of*

- Biological Chemistry, 270 (1995), 7013-7016. (10) Teich AF, Patel M, Arancio O. A reliable way to detect endogenous murine β -amyloid, PLoS ONE, (2013) 8(2): e55647; doi: 10.1371/journal.pone.0055647.
- (15) Best JD, Jay MT, Out F, Ma J, Nadin A et al. Quantitative measurement of changes in amyloid-beta 40 in the rat brain and cerebrospinal fluid following treatment with the gamma-secretase inhibitor LY-411575[N2-[(2S)-2-(3, 5-difluorophenyl)-2-hydroxyethanoyl]-NJ-[(7S)-5-methyl-6-oxo-6,7-dihydro-5H-dibenzo[b,d]azepin-7-yl]-L-alaninamide], J. Pharmacol Exp Ther (2005) 313:902-908.
- (16) Lanz TA, Schachter JB. Demonstration of a common artifact in immunosorbent assays of brain extracts: development of a solid-phase extraction protocol to enable measurement of amyloid-beta from wild-type rodent brain, J Neurosci. Methods (2006)157: 71-81.
- (17) Lanz TA, Schachter JB. Solid-phase extraction enhances detection of beta-amyloid peptide in plasma and enables abeta quantification following passive immunization with a beta antibodies, j. Neurosci. Methods, (2008)169: 16-22.
- (18) Janelidze, S.Stomrud E, Palmqvist S, Zetterberg , van Western D *et al.* Plasma β -amyloid in Alzheimer's disease and vascular disease. *Sci. Rep.* (2016)6: 26801; doi: 10.1038/srep26801 (2016).
- (19) Choi JW, Islam AT, Lee JH, Song JM, Oh BK. Detection of beta-amyloid (1-42) on protein array based on electrical detection technique using scanning tunneling microscopy, J. Nanosci. Nanotechnol. (2011) 11(5):4200-4204.
- (20) Takata M, Nakashime M, Takehara T, Baba H, Machida et al, Detection of amyloid beta protein in the urine of Alzheimer's disease patients and healthy individuals Neurosci. Lett. (2008)435(2): 126-130; doi: 10.1016/j.neulet.2008.02.019.
- (21) Prabhulkar S, Piatyszek R, Cirrito JR, Wu ZZ, Li CZ. Microbiosensor for Alzheimer's disease diagnostics: detection of amyloid beta biomarkers, J. of Neurochemistry, (2012)122:374-381.
- (22) Kang XH et al. Glucoseoxidase-graphene –chitosan modified electrode for direct electrochemistry and glucose sensing, Biosens. Bioelectron, (2009) 25:901-905.
- (23) Yang HW.et al. Combined detection of cancer cells and a tumor biomarker using an immunomagnetic sensor for the improvement of prostate cancer diagnosis Adv. Mater (2014) 26:3662-3666.
- (24) Yang XY. et al. Superparamagnetic graphene oxide-Fe₃O₄ nanoparticles hybrid for controlled targeted drug carriers J. Mater. Chem, (2009)19: 2710-2714.
- (25) Vickery JL, Patil AJ, Mann S. Fabrication of graphene-polymer nanocomposites with higher-order three-dimensional architectures, Adv. Mater (2009)21: 2180
- (26) Carrero-Sanchez JC, et al. Biocompatibility andvtoxicological studies of carbon nanotubes doped with nitrogen Nano Lett, (2006) 6: 1609-1616.
- (27) Li SS.et al. Non-invasive screening for early Alzheimer's disease diagnosis by a sensitively immunomagnetic biosensor Sci Rep. (2016) 6:25155; doi: 10.1038/srep25155 (2016)

(28) Janyasupab M, Lee Y, Zhang Y, Liu CW, Cai J, Popa A, et al., Detection of lysyl oxidase-like 2 (LOXL2) a biomarker of metastasis from breast cancers using human blood samples, *Recent Patents on Biomarkers*, (2015)5(2): 93–100.eISSN:2210-3104.

(29) Molazemhosseini A, Magagni L, Vena P, Liu CC. Single-use disposable electrochemical label-free immunosensor for detection of glycated hemoglobin (HbA1c) using differential pulse voltammetry (DPV), *Sensors*, (2016)16: 1024; doi:10.3390/s16071024.

(30) Willner I, Riklin A. Electrical communication between electrode and NAD (P) +-dependent enzymes using pyrroloquinolinequinone-electrodes in a self-assembled monolayer configuration: design of a new class of amperometric biosensors, *Anal Chem*, (1994) 66:1535-1539; Doi:10.1021/ac 008a028.

(31) Campuzano S, Glavez R, Dedrero M, DeVillena FJM, Pingarron JM. Preparation characterization and application of alkanethiol self-assembled monolayers modified with tetrathiafulvalene and glucose oxidase at a gold disk electrode, *J. Electroanal Chem* (2002) 526:92-100; doi: 10.1016/S0022 0728(2) 00753-2.

(32) Dai Y, Molazemhosseini A, Liu CC. A single-use, in vitro biosensor for the detection of T-tau protein, a biomarker of neuro-degenerative disorders, in PBS and human serum using differential pulse voltammetry (DPV), *Biosensors*, (2017) 7: 10; doi:10.3390/bios7010010.

(33) Braiek M, Rokbani KB, Chrouda A, MrabetB, Bakhrouf A, Maaref A, Jaffrezic-Renault N. An electrochemical immunosensor for detection of staphylococcus aureus bacteria based on immobilization of antibodies on self-assembled monolayers-functionalized gold electrode, *Biosensors*, (2012)2:417-426; doi:10.3390/bios2040417.

(34) Vericat C, Vela ME, Benitez G, Carro P, Salvarezza RC. Self-assembled monolayers of thiols and dithiols on gold: new challenges for a well-known system, *Chem. Soc. Rev.* (2010), 39:1805-1834.

(35) Karyakin AA, Presnova GV, Rubtsova MY, Egorow AM. Oriented immobilization of antibodies onto the gold surface via their native thiol groups, *Anal Chem* (2000), 72:3805-3811.

(36) Yoon M, Hwang HJ, Kim JH. Immobilization of antibodies on the self-assembled monolayer by antigen-binding site protection and immobilization kinetic control, *J. Biomedical Science and Engineering* (2011)4:242-247; doi:10.4236/jbise.2011.44033.

(37) Tanaka G, Funabashi H, Mie M, Kobatake E. Fabrication of an antibody microwell array with self-adhering antibody binding protein, *Analytical Biochemistry*, (2006)350:298-303; doi: 10.1016/j.ab.2005.12.034.

(38) Bard AJ, Faulkner LR. *Electrochemical Methods: Fundamentals and Applications* (2 Ed.). (2001), John Wiley & Sons. New York, NY, USA ISBN 0-471-04372-9.

(39) Dai Y, Liu CC. Detection of 17 β -estradiol in environmental samples and for health care using a single-use, cost-effective biosensor based on differential pulse voltammetry (DPV), *Biosensors*, (2017) 7(2), 15-27; doi:10.3390/bios7020015.

- (40) Bartolini M, Naldi M, Fiori J, Valle F, Biscarini F, et al. Kinetic characterization of amyloid-beta 1-42 aggregation with a multimethod logical approach, *Analytical Biochemistry* (2011), 414(2), 215-225.
- (41) Stine WB, Jungbauer L, Yu C, LaDu MJ. Preparing Synthetic A β in Different Aggregation States, *Methods Mol Biol* (2011), 670: 13-32; doi: 10.1007/978-1-60761-744-0_2.
- (42) Shen CL, Murphy RM. Solvent effects on self-assembly of beta-amyloid peptide, *Biophysics Journal* (1995), 69(2): 640-651; doi: 10.1016/S0006-3495(95)79940-4
- (43) Hellstrand E, Boland B, Walsh DM, Linse S. Amyloid β -Protein Aggregation Produces Highly Reproducible Kinetic Data and Occurs by a Two-Phase Process, *ACS Chemical Neuroscience* (2010), 1(1): 13-18.
- (44) Jacobsen C, Steensgaard J. Binding properties of monoclonal anti-IgG antibodies: analysis of binding curves in monoclonal antibody systems, *Immunology* (1984), 51(3):423-30.
- (45) Rama EC, Gonzalez-Garcia MB, Costa-Garcia A. Competitive electrochemical immunosensor for amyloid-beta 1-42 detection based on gold nanostructured Screen-Printed Carbon Electrodes, *Sensors and Actuators B: Chemical* (2014), 201(1): 567-571
- (46) Kaushik A, et al. A label-free electrochemical immunosensor for beta-amyloid detection, *Analytical Methods* (2016), 8, 6115-6120; doi: 10.1039/c6ay01910b