

Logarithmic Space Verifiers on NP-complete

Frank Vega 

Joysonic, Uzun Mirkova 5, Belgrade, 11000, Serbia
vega.frank@gmail.com

Abstract

P versus NP is considered as one of the most important open problems in computer science. This consists in knowing the answer of the following question: Is P equal to NP ? A precise statement of the P versus NP problem was introduced independently by Stephen Cook and Leonid Levin. Since that date, all efforts to find a proof for this problem have failed. NP is the complexity class of languages defined by polynomial time verifiers M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in P . Another major complexity classes are L and NL . The certificate-based definition of NL is based on logarithmic space Turing machine with an additional special read-once input tape: This is called a logarithmic space verifier. NL is the complexity class of languages defined by logarithmic space verifiers M such that when the input is an element of the language with its certificate, then M outputs 1. To attack the P versus NP problem, the NP -completeness is a useful concept. We demonstrate there is an NP -complete language defined by a logarithmic space verifier M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in L . In this way, we obtain if L is not equal to NL , then $P = NP$. In addition, we show that L is not equal to NL . Hence, we prove the complexity class P is equal to NP .

2012 ACM Subject Classification Theory of computation \rightarrow Complexity classes; Theory of computation \rightarrow Problems, reductions and completeness

Keywords and phrases complexity classes; completeness; verifier; reduction; polynomial time; logarithmic space

1 Introduction

In previous years there has been great interest in the verification or checking of computations [15]. Interactive proofs introduced by Goldwasser, Micali and Rackoff and Babai can be viewed as a model of the verification process [15]. Dwork and Stockmeyer and Condon have studied interactive proofs where the verifier is a space bounded computation instead of the original model where the verifier is a time bounded computation [15]. In addition, Blum and Kannan has studied another model where the goal is to check a computation based solely on the final answer [15]. More about probabilistic logarithmic space verifiers have been shown on a technique of Lipton [15]. In this work, we show some results about the logarithmic space verifiers applied to the class NP which solve one of the most important open problems in computer science, that is P versus NP .

The P versus NP problem is a major unsolved problem in computer science [5]. This is considered by many to be the most important open problem in the field [5]. It is one of the seven Millennium Prize Problems selected by the Clay Mathematics Institute to carry a US\$1,000,000 prize for the first correct solution [5]. It was essentially mentioned in 1955 from a letter written by John Nash to the United States National Security Agency [1]. However, the precise statement of the $P = NP$ problem was introduced in 1971 by Stephen Cook in a seminal paper [5]. In 2012, a poll of 151 researchers showed that 126 (83%) believed the answer to be no, 12 (9%) believed the answer is yes, 5 (3%) believed the question may be independent of the currently accepted axioms and therefore impossible to prove or disprove, 8 (5%) said either do not know or do not care or don't want the answer to be yes nor the problem to be resolved [10]. It is fully expected that $P \neq NP$ [19]. Indeed, if $P = NP$ then

2 Logarithmic Space Verifiers on NP-complete

there are stunning practical consequences [19]. For that reason, $P = NP$ is considered as a very unlikely event [19]. Certainly, P versus NP is one of the greatest open problems in science and a correct solution for this incognita will have a great impact not only in computer science, but for many other fields as well [1]. Whether $P = NP$ or not is still a controversial and unsolved problem [1]. We show some results that prove this outstanding problem with the unexpected solution of $P = NP$.

2 Theory and Methods

2.1 Preliminaries

In 1936, Turing developed his theoretical computational model [22]. The deterministic and nondeterministic Turing machines have become in two of the most important definitions related to this theoretical model for computation [22]. A deterministic Turing machine has only one next action for each step defined in its program or transition function [22]. A nondeterministic Turing machine could contain more than one action defined for each step of its program, where this one is no longer a function, but a relation [22].

Let Σ be a finite alphabet with at least two elements, and let Σ^* be the set of finite strings over Σ [3]. A Turing machine M has an associated input alphabet Σ [3]. For each string w in Σ^* there is a computation associated with M on input w [3]. We say that M accepts w if this computation terminates in the accepting state, that is $M(w) = 1$ (when M outputs 1 on the input w) [3]. Note that M fails to accept w either if this computation ends in the rejecting state, that is $M(w) = 0$, or if the computation fails to terminate, or the computation ends in the halting state with some output, that is $M(w) = y$ (when M outputs the string y on the input w) [3].

Another relevant advance in the last century has been the definition of a complexity class. A language over an alphabet is any set of strings made up of symbols from that alphabet [6]. A complexity class is a set of problems, which are represented as a language, grouped by measures such as the running time, memory, etc [6]. The language accepted by a Turing machine M , denoted $L(M)$, has an associated alphabet Σ and is defined by:

$$L(M) = \{w \in \Sigma^* : M(w) = 1\}.$$

We denote by $t_M(w)$ the number of steps in the computation of M on input w [3]. For $n \in \mathbb{N}$ we denote by $T_M(n)$ the worst case run time of M ; that is:

$$T_M(n) = \max\{t_M(w) : w \in \Sigma^n\}$$

where Σ^n is the set of all strings over Σ of length n [3]. We say that M runs in polynomial time if there is a constant k such that for all n , $T_M(n) \leq n^k + k$ [3]. In other words, this means the language $L(M)$ can be decided by the Turing machine M in polynomial time. Therefore, P is the complexity class of languages that can be decided by deterministic Turing machines in polynomial time [6]. A verifier for a language L_1 is a deterministic Turing machine M , where:

$$L_1 = \{w : M(w, c) = 1 \text{ for some string } c\}.$$

We measure the time of a verifier only in terms of the length of w , so a polynomial time verifier runs in polynomial time in the length of w [3]. A verifier uses additional information, represented by the symbol c , to verify that a string w is a member of L_1 . This information is called certificate. NP is the complexity class of languages defined by polynomial time verifiers [19].

► **Lemma 1.** *Given a language $L_1 \in P$, a language L_2 is in NP if there is a deterministic Turing machine M , where:*

$$L_2 = \{w : M(w, c) = y \text{ for some string } c \text{ such that } y \in L_1\}$$

and M runs in polynomial time in the length of w . In this way, NP is the complexity class of languages defined by polynomial time verifiers M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in P .

Proof. If L_1 can be decided by the Turing machine M' in polynomial time, then the deterministic Turing machine $M''(w, c) = M'(M(w, c))$ will output 1 when $w \in L_2$. Consequently, M'' is a polynomial time verifier of L_2 and thus, L_2 is in NP . ◀

2.2 Hypothesis

A function $f : \Sigma^* \rightarrow \Sigma^*$ is a polynomial time computable function if some deterministic Turing machine M , on every input w , halts in polynomial time with just $f(w)$ on its tape [22]. Let $\{0, 1\}^*$ be the infinite set of binary strings, we say that a language $L_1 \subseteq \{0, 1\}^*$ is polynomial time reducible to a language $L_2 \subseteq \{0, 1\}^*$, written $L_1 \leq_p L_2$, if there is a polynomial time computable function $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$ such that for all $x \in \{0, 1\}^*$:

$$x \in L_1 \text{ if and only if } f(x) \in L_2.$$

An important complexity class is NP -complete [9]. A language $L_1 \subseteq \{0, 1\}^*$ is NP -complete if:

- $L_1 \in NP$, and
- $L' \leq_p L_1$ for every $L' \in NP$.

If L_1 is a language such that $L' \leq_p L_1$ for some $L' \in NP$ -complete, then L_1 is NP -hard [6]. Moreover, if $L_1 \in NP$, then $L_1 \in NP$ -complete [6]. A principal NP -complete problem is SAT [9]. An instance of SAT is a Boolean formula ϕ which is composed of:

1. Boolean variables: x_1, x_2, \dots, x_n ;
2. Boolean connectives: Any Boolean function with one or two inputs and one output, such as \wedge (AND), \vee (OR), \neg (NOT), \Rightarrow (implication), \Leftrightarrow (if and only if);
3. and parentheses.

A truth assignment for a Boolean formula ϕ is a set of values for the variables in ϕ . A satisfying truth assignment is a truth assignment that causes ϕ to be evaluated as true. A formula with a satisfying truth assignment is a satisfiable formula. The problem SAT asks whether a given Boolean formula is satisfiable [9]. We define a CNF Boolean formula using the following terms:

A literal in a Boolean formula is an occurrence of a variable or its negation [6]. A Boolean formula is in conjunctive normal form, or CNF , if it is expressed as an AND of clauses, each of which is the OR of one or more literals [6]. A Boolean formula is in 3-conjunctive normal form or $3CNF$, if each clause has exactly three distinct literals [6].

For example, the Boolean formula:

$$(x_1 \vee \neg x_1 \vee \neg x_2) \wedge (x_3 \vee x_2 \vee x_4) \wedge (\neg x_1 \vee \neg x_3 \vee \neg x_4)$$

4 Logarithmic Space Verifiers on NP-complete

is in $3CNF$. The first of its three clauses is $(x_1 \vee \neg x_1 \vee \neg x_2)$, which contains the three literals x_1 , $\neg x_1$, and $\neg x_2$. Another relevant NP -complete language is $3CNF$ satisfiability, or $3SAT$ [6]. In $3SAT$, it is asked whether a given Boolean formula ϕ in $3CNF$ is satisfiable.

A logarithmic space Turing machine has a read-only input tape, a write-only output tape, and read/write work tapes [22]. The work tapes may contain at most $O(\log n)$ symbols [22]. In computational complexity theory, L is the complexity class containing those decision problems that can be decided by a deterministic logarithmic space Turing machine [19]. NL is the complexity class containing the decision problems that can be decided by a nondeterministic logarithmic space Turing machine [19].

A logarithmic space transducer is a Turing machine with a read-only input tape, a write-only output tape, and read/write work tapes [22]. The work tapes must contain at most $O(\log n)$ symbols [22]. A logarithmic space transducer M computes a function $f : \Sigma^* \rightarrow \Sigma^*$, where $f(w)$ is the string remaining on the output tape after M halts when it is started with w on its input tape [22]. We call f a logarithmic space computable function [22]. We say that a language $L_1 \subseteq \{0, 1\}^*$ is logarithmic space reducible to a language $L_2 \subseteq \{0, 1\}^*$, written $L_1 \leq_l L_2$, if there exists a logarithmic space computable function $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$ such that for all $x \in \{0, 1\}^*$,

$$x \in L_1 \text{ if and only if } f(x) \in L_2.$$

The logarithmic space reduction is frequently used for L and NL [19]. A Boolean formula is in 2-conjunctive normal form, or $2CNF$, if it is in CNF and each clause has exactly two distinct literals. There is a problem called $2SAT$, where we asked whether a given Boolean formula ϕ in $2CNF$ is satisfiable. $2SAT$ is complete for NL [19]. Another special case is the class of problems where each clause contains XOR (i.e. exclusive or) rather than (plain) OR operators. This is in P , since an $XOR SAT$ formula can also be viewed as a system of linear equations mod 2, and can be solved in cubic time by Gaussian elimination [17]. We denote the XOR function as \oplus . The $XOR 2SAT$ problem will be equivalent to $XOR SAT$, but the clauses in the formula have exactly two distinct literals. $XOR 2SAT$ is in L [2], [20].

We can give a certificate-based definition for NL [3]. The certificate-based definition of NL assumes that a logarithmic space Turing machine has another separated read-only tape [3]. On each step of the machine the machine's head on that tape can either stay in place or move to the right [3]. In particular, it cannot reread any bit to the left of where the head currently is [3]. For that reason this kind of special tape is called "read-once" [3].

► **Definition 2.** A language L_1 is in NL if there exists a deterministic logarithmic space Turing machine M with an additional special read-once input tape polynomial $p : \mathbb{N} \rightarrow \mathbb{N}$ such that for every $x \in \{0, 1\}^*$,

$$x \in L_1 \Leftrightarrow \exists u \in \{0, 1\}^{p(|x|)} \text{ such that } M(x, u) = 1$$

where by $M(x, u)$ we denote the computation of M where x is placed on its input tape and u is placed on its special read-once tape, and M uses at most $O(\log |x|)$ space on its read/write tapes for every input x where $|\dots|$ is the bit-length function [3]. M is called a logarithmic space verifier [3].

We state the following Hypothesis:

▷ **Hypothesis 3.** Given a language $L_1 \in L$, there is a language L_2 in NP -complete with a deterministic Turing machine M , where:

$$L_2 = \{w : M(w, u) = y \text{ for some string } u \text{ such that } y \in L_1\}$$

when M runs in logarithmic space in the length of w , u is placed on the special read-once tape of M , and u is polynomially bounded by w . In this way, there is an NP -complete language defined by a logarithmic space verifier M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in L .

2.3 Consequences

From the early days of automata and complexity theory, two different models of Turing machines are considered, the offline and online machines [14]. Each model has a read-only input tape and some work tapes [14]. The offline machines may read their input two-way while the online machines are not allowed to move the input head to the left [14]. In the terminology of the (generalized) Turing machine models are called two-way and one-way Turing machines, respectively [14].

Hartmanis and Mahaney have investigated the classes $1L$ and $1NL$ of languages recognizable by deterministic one-way logarithmic space Turing machine and nondeterministic one-way logarithmic space Turing machine, respectively [11]. They have shown that $1L \neq 1NL$ (by looking at a uniform variant of the string non-equality problem from communication complexity theory) and have defined a natural complete problem for $1NL$ under deterministic one-way logarithmic space reductions [11]. Furthermore, they have proven that $1NL \subseteq L$ if and only if $L = NL$ [11].

► **Theorem 4.** *If the Hypothesis 3 is true, therefore if $L \neq NL$, then $P = NP$.*

Proof. We can simulate the computation $M(w, u) = y$ in the Hypothesis 3 by a nondeterministic logarithmic space Turing machine N , such that $N(w) = y$ since we can read the certificate string u within the read-once tape by a work tape in a nondeterministic logarithmic space generation of symbols contained in u [19]. Certainly, we can simulate the reading of one symbol from the string u into the read-once tape just nondeterministically generating the same symbol in the work tapes using a logarithmic space [19].

If we suppose that $L \subset 1NL$, then we can accept the elements of the language $L_1 \in L$ by a nondeterministic one-way logarithmic space Turing machine M' . In this way, there is a nondeterministic logarithmic space Turing machine $M''(w) = M'(N(w))$ which will output 1 when $w \in L_2$. Consequently, M'' is a nondeterministic logarithmic space Turing machine which decides the language L_2 . The reason is because we can simulate the output string of $N(w)$ within a read-once tape and thus, we can compute in a nondeterministic logarithmic space the logarithmic space composition using the same techniques of the logarithmic space composition reduction, but without any reset of the computation [19]. Certainly, we do not need to reset the computation of $N(w)$ for the reading at once of a symbol in the output string of $N(w)$ by the nondeterministic one-way logarithmic space Turing machine M' . Therefore, L_2 is in NL and thus, $L_2 \in P$ due to $NL \subseteq P$ [19]. If any single NP -complete problem can be solved in polynomial time, then $P = NP$ [6]. Since $L_2 \in P$ and $L_2 \in NP$ -complete, then we obtain the complexity class P is equal to NP under the assumption that $L \subset 1NL$.

Hartmanis and Mahaney have also shown with their result that if $1NL \subseteq L$ or even $1NL \subset L$, then $L = NL$, because they proved there is a complete problem for both $1NL$ and NL at the same time [11]. If this way, if $L \neq NL$, then $L \subset 1NL$ by contraposition [19]. Since we already obtained that $P = NP$ under the assumption that $L \subset 1NL$, therefore if $L \neq NL$, then $P = NP$. ◀

6 Logarithmic Space Verifiers on NP-complete

► **Definition 5.** *The class LNL contains those languages that are decided by a nondeterministic logarithmic space Turing machine N such that for every element $x = yz$ of these languages, there are a prefix and suffix substrings y and z where N moves strictly deterministically on y and strictly nondeterministically on z when strictly deterministically means there is no a possible nondeterministic step and strictly nondeterministically means there is at least one nondeterministic step on the computation.*

Sauerhoff has investigated the class BNL of languages recognizable by nondeterministic logarithmic space Turing machine, that only use nondeterministic moves before reading their input (“nondeterminism at the beginning”) [21].

► **Theorem 6.** $L \neq NL$.

Proof. We have that $NL \subseteq LNL$, because the prefix substring y of an instance $x = yz$ could be the empty string. Certainly, all the languages in the class NL could be decided by nondeterministic logarithmic space Turing machines such that they always do a single nondeterministic step after the original acceptance state choosing nondeterministically the same acceptance state within two equals choices from the original and modified deterministic or nondeterministic logarithmic space Turing machines which decide these languages (this is assuming the prefix substring y is the empty string in the elements $x = yz$). Moreover, we have that $LNL \subseteq NL$, because the languages in LNL are decided by nondeterministic logarithmic space Turing machines. Since $NL \subseteq LNL$ and $LNL \subseteq NL$, then the complexity class LNL is equal to NL . However, we can state that $BNL \neq LNL$, because there is no possible way over the Definition 5 of LNL for an element $x = yz$ in some languages in BNL when the prefix substring y is the empty string, such that we could move strictly nondeterministically on y (that would be a “nondeterminism at the beginning”) and move strictly deterministically on the nonempty string z . Hence, we obtain that $BNL \neq NL$ by transitivity. Nevertheless, Sauerhoff has also shown that $L \subseteq BNL \subseteq NL$ [21]. Consequently, we prove the complexity class L is not equal to NL . ◀

► **Theorem 7.** *If the Hypothesis 3 is true, then $P = NP$.*

Proof. This is a direct consequence of Theorems 4 and 6. ◀

3 Results

We show a previous known NP -complete problem:

► **Definition 8. $NAE\ 3SAT$**

INSTANCE: A Boolean formula ϕ in $3CNF$.

QUESTION: Is there a truth assignment for ϕ such that each clause has at least one true literal and at least one false literal?

REMARKS: $NAE\ 3SAT \in NP$ -complete [9].

We define a new problem:

► **Definition 9. $MINIMUM\ EXCLUSIVE-OR\ 2-SATISFIABILITY$**

INSTANCE: A positive integer K and a Boolean formula ϕ that is an instance of $XOR\ 2SAT$.

QUESTION: Is there a truth assignment in ϕ such that at most K clauses are unsatisfiable?

REMARKS: We denote this problem as $MIN \oplus 2SAT$.

► **Theorem 10.** $MIN \oplus 2SAT \in NP$ -complete.

Proof. It is trivial to see $MIN \oplus 2SAT \in NP$ [19]. Given a Boolean formula ϕ in $3CNF$ with n variables and m clauses, we create three new variables a_{c_i} , b_{c_i} and d_{c_i} for each clause $c_i = (x \vee y \vee z)$ in ϕ , where x , y and z are literals, in the following formula:

$$P_i = (a_{c_i} \oplus b_{c_i}) \wedge (b_{c_i} \oplus d_{c_i}) \wedge (a_{c_i} \oplus d_{c_i}) \wedge (x \oplus a_{c_i}) \wedge (y \oplus b_{c_i}) \wedge (z \oplus d_{c_i}).$$

We can see P_i has at most one unsatisfiable clause for some truth assignment if and only if at least one member of $\{x, y, z\}$ is true and at least one member of $\{x, y, z\}$ is false for the same truth assignment. Hence, we can create the Boolean formula ψ as the conjunction of the P_i formulas for every clause c_i in ϕ , such that $\psi = P_1 \wedge \dots \wedge P_m$. Finally, we obtain that

$$\phi \in NAE\ 3SAT \text{ if and only if } (\psi, m) \in MIN \oplus 2SAT.$$

Consequently, we prove $NAE\ 3SAT \leq_p MIN \oplus 2SAT$ where we already know the language $NAE\ 3SAT \in NP$ -complete [9]. To sum up, we show $MIN \oplus 2SAT \in NP$ -hard and $MIN \oplus 2SAT \in NP$ and thus, $MIN \oplus 2SAT \in NP$ -complete. ◀

► **Theorem 11.** There is a deterministic Turing machine M , where:

$$MIN \oplus 2SAT = \{w : M(w, u) = y \text{ for some string } u \text{ such that } y \in XOR\ 2SAT\}$$

when M runs in logarithmic space in the length of w , u is placed on the special read-once tape of M , and u is polynomially bounded by w .

Proof. Given a valid instance (ψ, K) for $MIN \oplus 2SAT$ when ψ has m clauses, we can create a certificate array A which contains K different natural numbers in ascending order which represents the indexes of the clauses in ψ that we are going to remove from the instance. We read at once the elements of the array A and we reject whether this is not a valid certificate: That is when the numbers are not sorted in ascending order, or the array A does not contain exactly K elements, or the array A contains a number that is not between 1 and m . While we read the elements of the array A , we remove the clauses from the instance (ψ, K) for $MIN \oplus 2SAT$ just creating another instance ϕ for $XOR\ 2SAT$ where the Boolean formula ϕ does not contain the K different indexed clauses ψ represented by the numbers in A . Therefore, we obtain the array A should be valid according to the Theorem 11 when:

$$(\psi, K) \in MIN \oplus 2SAT \text{ if and only if } \phi \in XOR\ 2SAT.$$

Furthermore, we can make this verification in logarithmic space such that the array A is placed on the special read-once tape, because we read at once the elements in the array A and we assume the clauses in the input ψ are indexed from left to right. Hence, we only need to iterate from the elements of the array A to verify whether the array is a valid certificate and also remove the K different clauses from the Boolean formula ψ when we write the final clauses to the output. This logarithmic space verification will be the Algorithm 1. We assume whether a value does not exist in the array A into the cell of some position i when $A[i] = \text{undefined}$. In addition, we reject immediately when the following comparisons

$$A[i] \leq \max \vee A[i] < 1 \vee A[i] > m$$

hold at least into one single binary digit. Note, in the loop j from \min to $\max - 1$, we do not output any clause when $\max - 1 < \min$. ◀

8 **Logarithmic Space Verifiers on NP-complete**

Algorithm 1 Logarithmic space verifier

```

1: /*A valid instance for  $MIN \oplus 2SAT$  with its certificate*/
2: procedure VERIFIER(( $\psi, K$ ),  $A$ )
3:   /*Initialize minimum and maximum values*/
4:    $min \leftarrow 1$ 
5:    $max \leftarrow 0$ 
6:   /*Iterate for the elements of the certificate array  $A$ */
7:   for  $i \leftarrow 1$  to  $K + 1$  do
8:     if  $i = K + 1$  then
9:       /*There exists a  $K + 1$  element in the array*/
10:      if  $A[i] \neq \text{undefined}$  then
11:        /*Reject the certificate*/
12:        return 0
13:      end if
14:      /* $m$  is the number of clauses in  $\psi$ */
15:       $max \leftarrow m + 1$ 
16:      else if  $A[i] = \text{undefined} \vee A[i] \leq max \vee A[i] < 1 \vee A[i] > m$  then
17:        /*Reject the certificate*/
18:        return 0
19:      else
20:         $max \leftarrow A[i]$ 
21:      end if
22:      /*Iterate for the clauses of the Boolean formula  $\psi$ */
23:      for  $j \leftarrow min$  to  $max - 1$  do
24:        /*Output the indexed  $j$  clause in  $\psi$ */
25:        output “  $\wedge c_j$  ”
26:      end for
27:       $min \leftarrow max + 1$ 
28:    end for
29: end procedure

```

► **Theorem 12.** *The Hypothesis 3 is true.*

Proof. This is a consequence of Theorems 10 and 11. ◀

► **Theorem 13.** $P = NP$.

Proof. This is a direct consequence of Theorems 7 and 12. ◀

3.1 Codes

This work is implemented into a Project programmed in Scala [23]. In this Project, we use the Assertion on the properties of the instances of each problem and the Unit Test for checking the correctness of every reduction [23]. We need to install JDK 8 in order to test the Scala Project [18]. In addition, we need to install SBT to run the unit test (we could run the unit test with the `sbt test` command) [18].

4 Conclusions

No one has been able to find a polynomial time algorithm for any of more than 300 important known *NP-complete* problems [9]. A proof of $P = NP$ will have stunning practical consequences, because it leads to efficient methods for solving some of the important problems in *NP* [5]. The consequences, both positive and negative, arise since various *NP-complete* problems are fundamental in many fields [5]. All the following consequences are assuming that we have a practical solution for the *NP-complete* problems where such existence was proven with our result:

Cryptography, for example, relies on certain problems being difficult. A constructive and efficient solution to an *NP-complete* problem such as *3SAT* will break most existing cryptosystems including: Public-key cryptography [12], symmetric ciphers [16] and one-way functions used in cryptographic hashing [7]. These would need to be modified or replaced by information-theoretically secure solutions not inherently based on P -*NP* equivalence.

There are enormous positive consequences that will follow from rendering tractable many currently mathematically intractable problems. For instance, many problems in operations research are *NP-complete*, such as some types of integer programming and the traveling salesman problem [9]. Efficient solutions to these problems have enormous implications for logistics [5]. Many other important problems, such as some problems in protein structure prediction, are also *NP-complete*, so this will spur considerable advances in biology [4].

Since all the *NP-complete* optimization problems become easy, everything will be much more efficient [8]. Transportation of all forms will be scheduled optimally to move people and goods around quicker and cheaper [8]. Manufacturers can improve their production to increase speed and create less waste [8].

Learning becomes easy by using the principle of Occam's razor: We simply find the smallest program consistent with the data [8]. Near perfect vision recognition, language comprehension and translation and all other learning tasks become trivial [8]. We will also have much better predictions of weather and earthquakes and other natural phenomenon [8].

The economy would become vastly more efficient. There would be disruption, including maybe displacing programmers [13]. The practice of programming itself would be more about gathering training data and less about writing code [13]. Google would have the resources to excel in such a world [13].

But such changes may pale in significance compared to the revolution an efficient method for solving *NP-complete* problems will cause in mathematics itself. Research mathematicians

10 **Logarithmic Space Verifiers on NP-complete**

spend their careers trying to prove theorems, and some proofs have taken decades or even centuries to find after problems have been stated. For instance, Fermat's Last Theorem took over three centuries to prove. A method that is guaranteed to find proofs to theorems, should one exist of a "reasonable" size, would essentially end this struggle [5].

References

- 1 Scott Aaronson. $P \stackrel{?}{=} NP$. *Electronic Colloquium on Computational Complexity, Report No. 4*, 2017.
- 2 Carme Álvarez and Raymond Greenlaw. A Compendium of Problems Complete for Symmetric Logarithmic Space. *Computational Complexity*, 9(2):123–145, 2000. doi:10.1007/PL00001603.
- 3 Sanjeev Arora and Boaz Barak. *Computational complexity: a modern approach*. Cambridge University Press, 2009.
- 4 Bonnie Berger and Tom Leighton. Protein Folding in the Hydrophobic-Hydrophilic (HP) Model is NP-complete. *Journal of Computational Biology*, 5(1):27–40, 1998. doi:10.1145/279069.279080.
- 5 Stephen A. Cook. The P versus NP Problem, April 2000. In Clay Mathematics Institute at <http://www.claymath.org/sites/default/files/pvsnp.pdf>.
- 6 Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms*. The MIT Press, 3rd edition, 2009.
- 7 Debapratim De, Abishek Kumarasubramanian, and Ramarathnam Venkatesan. Inversion Attacks on Secure Hash Functions Using SAT Solvers. In *International Conference on Theory and Applications of Satisfiability Testing*, pages 377–382. Springer, 2007. doi:10.1007/978-3-540-72788-0_36.
- 8 Lance Fortnow. The Status of the P Versus NP Problem. *Commun. ACM*, 52(9):78–86, September 2009. doi:10.1145/1562164.1562186.
- 9 Michael R. Garey and David S. Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. San Francisco: W. H. Freeman and Company, 1 edition, 1979.
- 10 William I. Gasarch. Guest column: The second $P \stackrel{?}{=} NP$ poll. *ACM SIGACT News*, 43(2):53–77, 2012. doi:10.1145/2261417.2261434.
- 11 Juris Hartmanis and Stephen R. Mahaney. Languages Simultaneously Complete for One-Way and Two-Way Log-Tape automata. *SIAM Journal on Computing*, 10(2):383–390, 1981. doi:10.1137/0210027.
- 12 Satoshi Horie and Osamu Watanabe. Hard instance generation for SAT. *Algorithms and Computation*, pages 22–31, 1997. doi:10.1007/3-540-63890-3_4.
- 13 Russell Impagliazzo. A personal view of average-case complexity. In *Proceedings of Structure in Complexity Theory. Tenth Annual IEEE Conference*, pages 134–147. IEEE, 1995. doi:10.1109/SCT.1995.514853.
- 14 Martin Kutrib, Julien Provillard, György Vaszil, and Matthias Wendlandt. Deterministic One-Way Turing Machines with Sublinear Space. *Fundamenta Informaticae*, 136(1-2):139–155, 2015. doi:10.3233/FI-2015-1147.
- 15 Richard J. Lipton. Efficient checking of computations. In *STACS 90*, pages 207–215. Springer Berlin Heidelberg, 1990. doi:10.1007/3-540-52282-4_44.
- 16 Fabio Massacci and Laura Marraro. Logical Cryptanalysis as a SAT Problem. *Journal of Automated Reasoning*, 24(1):165–203, 2000. doi:10.1023/A:1006326723002.
- 17 Christopher Moore and Stephan Mertens. *The Nature of Computation*. Oxford University Press, 2011.
- 18 Martin Odersky, Lex Spoon, and Bill Venners. *Programming in Scala: Updated for Scala 2.12*. Artima Incorporation, USA, 3rd edition, 2016.
- 19 Christos H. Papadimitriou. *Computational complexity*. Addison-Wesley, 1994.
- 20 Omer Reingold. Undirected Connectivity in Log-space. *J. ACM*, 55(4):1–24, September 2008. doi:10.1145/1391289.1391291.

- 21 Martin Sauerhoff. Guess-and-verify versus unrestricted nondeterminism for OBDDs and one-way Turing machines. *Journal of Computer and System Sciences*, 66(3):473 – 495, 2003. doi:10.1016/S0022-0000(03)00037-0.
- 22 Michael Sipser. *Introduction to the Theory of Computation*, volume 2. Thomson Course Technology Boston, 2006.
- 23 Frank Vega. VerifyReduction, August 2019. In a GitHub repository at <https://github.com/frankvegadelgado/VerifyReduction>.