

## Article

# Classification of chest x-ray images using machine learning techniques

Abdelmoty M. Ahmed<sup>\*1,3</sup>, Gamal Tharwat<sup>3</sup>, Belgacem Bouallegue<sup>1</sup>, Mahmoud M. Khattab<sup>2</sup>, Ahmad M. J. Al Moustafa<sup>2</sup> and Safaa S. Matter<sup>2</sup>

<sup>1</sup>Department of Computer Engineering, King Khalid University, Abha, Saudi Arabia; abd2005moty@yahoo.com; belgacem.bouallegue2015@gmail.com

<sup>2</sup>Department of Computer Science, King Khalid University, Abha, Saudi Arabia; mmkhattab2000@gmail.com; ahmad200000@hotmail.com; safaamatter2010@gmail.com

<sup>3</sup>Department of Computers and Systems Engineering, Faculty of Engineering, Al-Azhar University, Egypt; abd2005moty@yahoo; gamaltharwat@gmail.com

\* Correspondence: abd2005moty@yahoo.com; Tel.: (00966504538402;

**Abstract:** Machine Learning has completely transformed health care system, which transmits medical data through IOT sensors. So it is very important to encrypt them to protect patient data. encrypting medical images from a performance perspective consumes time; hence the use of an auto encoder is essential. An auto encoder is used in this work to compress the image as a vector prior to the encryption process. The digital image passes across description function and a decoder to get back the image in the proposed work; various experiments are carried out on hyper parameters to achieve the highest outcome of the classification. The findings demonstrate that the combination of Mean Square Logarithmic Error as the loss function, ADA grad as an optimizer, two layers for the encoder, and another reverse for the decoder, RELU as the activation function generates the best auto encoder results. The combination of Mean square error (lose function), RMS prop (optimizer), three layers for the encoder and another reverse for the decoder, and RELU (activation function) has the best classification result. All the experiments with different hyper parameter has run almost very close to each other even when changing the number of layers. The running time is between 9 and 16 second for each epoch.


**Keywords:** Auto encoder, IoT, Image encryption, Artificial Neural Network. Machine Learning

## 1. Introduction

Health care systems use IoT sensors to collect patient's data from the cloud to analyse the data for giving useful recommendation. Unfortunately, IoT servers suffer from hacking [1][2][3] regularly, hence encryption is needed for such type of data [4][5]. Several techniques are developed for image encryption [6] using different algorithms like Chaotic Based Artificial Neural Network which has a complex design and neural network-based stream image encryption which is expensive in run time.

Data set :Our dataset is extracted from the clinical PACS database within the National Institutes of Physical fitness Clinical Center and consists of ~60% of all informed chest x-rays in the particular hospital.

Auto encoders: Auto encoders are basic learning circuits aimed at transforming inputs into outputs with the least amount of possible distortion.



**Figure.1:** Structure of auto encoder.

Figure1 shows AEs that consist of an input layer and a layer of output that are connected by one or more hidden layers. AEs have the same number of units for input and output. The goal of this network is to recreate the input by converting inputs into outputs in the simplest way possible so that the input is not very distorted. In AEs, the training method requires minimizing reconstruction errors, i.e. the output and input showing the minimal difference. The structure of a standard AEE is described in Figure 1[16].

Transfer data on the IoT network is unsecure practice that needs a lot of effort to be done to secure all the stages of transferring data. Machine learning or deep learning is a very powerful tool in the field of security. The image encryption transforms an original image to the encrypted image in which people cannot recognize contents in the original image.

In this work, we focus on decreasing the amount of time needed for training and testing the model. Simply this can be accomplished by designing the neural network as an auto encoder to solve those issue. This paper used auto encoder [7][8] which is a convolution neural network to compress the x-ray image, after which a specific function is executed for encryption to secure the sent image. On the other side for decryption the reverse of the encryption function is used and decoding is also required to get the original image back with some accepted loss in its features. In this paper we will discuss the effect of the hyper parameter [9] of the auto encoder also the encryption function on the image loss and how can it be accepted through classification algorithm. The classification algorithm used is a Convolution Neural Network [10][11]. The rest of the paper is organized as follows: Section 2 gives related work. Section 3 introduces the proposed methodology. Section 4 focuses on the results that have been achieved in this paper. And finally, conclusions are drawn in Section 5.


## 2. EXISTING METHODS

In previous studies [12], using Stacked Auto-Encoder (SAE) and chaotic logistic map, an application of image compression and encryption is suggested. Experiments show that this application is viable and successful. It can be used simultaneously on the internet for picture transmission and picture safety. It has established a five-layer SAE model. In [13] a method of X-ray image compression is presented based on a Recurrent Neural Networks Convolution (RNN-Conv). During implementation, the proposed architecture can provide variable compression rates while requiring each network to be trained only once for a particular X-ray image dimension. In [14] a learning-based method of image compression that uses wavelet decomposition is provided as a pre-processing stage. The proposed convolution auto encoder is trained end-to-end to achieve a target bitrate smaller than 0.15 bits per pixel across the complete CLIC2019 test range.

A new method of representation learning is proposed in [15] which describes unknown attacks more predicatively, enabling supervised methods of identification of learning-based anomalies. Specifically, to learn a latent representation from the input data, the author created three regularized versions of Auto Encoders (AEs). The bottleneck layers of these regularized AEs will then be used as the new classification algorithm input features, trained in a controlled way using normal data and known IoT attacks. A proposed new method of representation learning to more predicatively "describe" unknown attacks, allowing supervised methods of learning-based anomaly detection. Specifically, the author developed three regularized versions of Auto Encoders (AEs) to learn a latent representation from the input data. They also conduct experiments to explore the features of the models proposed and the effect on their output of hyper parameters.

### 3. PROPOSED WORK

Figure 2 shows the block diagram of the modified auto encoder. The input is a 200 X 200 image to the encoder. The result feature vector from the encoder represents the input to the encryption block and gives the output as an encrypted feature vector which is used by the decryption and makes decryption to it and then decoded to retrieve the original image. After retrieving the original image. Two layers CNN are used to see how the change in modified auto encoder hyperparameters can affect the results of the classification stage.



**Figure.2:** Proposed System Model

The proposed system consists of three layers (three convolution and two max pooling) as an encoder and another three for the decoder.

The first layer in the encoder is the input layer which has 200 X 200 input image, (3, 3) filter, each image has the same padding and 32 nodes. The second layer is MaxPooling2D layer with (2, 2) pool size. It uses (3,3) filter, relu activation function, using the same padding for the image, and 64 nodes. The third layer is the Conv2D layer with the same criteria of the convolution layers but has 128 nodes.

The decoder consists of three layers also which is the reverse to the encoder. The first layer is the input layer of the decoder. The second layer is the conv2D layer with the same criteria in the convolution layer in the encoder with 128 nodes. Then there is UpSampling2D layer with (2, 2) filter. The third layer is the convolution layer with 64 nodes. The final layer is the convolution layer with one node and sigmoid activation function.




Figure.3: Modified Auto Encoder

The figure3 shows the update in the auto encoder. The result feature vector from the encoder is handled by the encryption as an input. In this stage, an encryption mechanism used is by adding another image to the sent image and takes the square of the feature vector as follows.

$$\left( \begin{bmatrix} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \\ 16 & 17 & 18 & 19 & 20 \end{bmatrix} + \begin{bmatrix} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \\ 16 & 17 & 18 & 19 & 20 \end{bmatrix} \right)^2 = \begin{bmatrix} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \\ 16 & 17 & 18 & 19 & 20 \end{bmatrix}$$

Figure.4: Sample of the feature vector

In the decryption step, the encrypted image is used and subtracte the added image from it then takes the square root of it to get the feature vector to be fed to the decoder to retrieve the original image.




Figure.5: A is the original image B is the encrypted image C is the retrieved image

Figure 5 shows the original image - B is the encrypted image after applying encoding and encryption - C is the retrieved equation after applying the decryption and decoding.

Our algorithm for the x-ray image can be summarized as follow:

1. The x-ray image is decoded using a CNN auto encoder.
2. The encoder output which is encoded matrix is then encrypted by adding it to another image then use the power function on the feature vector.
3. In the decryption step the power function is reversed using the square root function.
4. The decrypted image is then decoded to retrieve the original image.

4. SIMULATION RESULTS

The data set consists of 9000 images for training the auto encoder and for the prediction and training of the classifier. Figure 6 shows the number of negative cases is 5800 and positive cases are 3200.




Figure.6: Comparison of Positive and Negative X-Rays

The effect of different hyper parameters like lose function, optimizer, number of layers, number of nodes, number of epochs, and activation function is examined on the auto encoder. Some different measure matrices are calculated.






Figure.7: The mean square error (MSE) and the mean absolute error (MEA) for the different hyper parameter combination in the auto encoder

Figure 7 shows the different matrices in evaluating the auto encoder like the mean square error(MSE) and the mean absolute error (MAE). In the different parameter used by this research. the combination of the loss function (mean square logarithmic error), optimizer (ADAM), activation function (relu) and 3 layers in auto encoder model have given the less MSE and MAE which mean the best result.




**Figure.8:** The loss function in different number of epochs (10, 25, 50) for the different hyper parameter combination in the auto encoder

Figure 8 shows the loss function of the auto encoder with different hyper parameters. This loss function is in 10, 25, and 50 epochs. As shown in the graph more than one combination gives a little loss function as the last five combinations from the right.



**Figure.9:** The recall, precision.F1 measure and area under the curve (AUC) for the classifier on the retrieved images after applying different hyper parameter combination in the auto encoder.

Figure 9 shows the different matrices like recall, precision, F1, and AUC of the classification algorithm after applying different hyper parameters on the auto encoder. In other words, applying different hyper parameters' on the auto encoder and save the retrieved images from the auto encoder then try to classify it using another CNN classifier to see the effect of the different hyper parameters on the classification step.



**Figure.10:** The training accuracy and the test accuracy of the classifier on the retrieved images after applying different hyper parameter combination on the auto encoder

Figure 10 shows the training and the test accuracy of the classification algorithm on the images from the auto encoder also for different hyper parameters.

**Table1:** The results of the best auto encoder





A			B																			
			<table><tr><th>Epoch.no</th><th>MSE</th><th>MAE</th><th>Lose</th></tr><tr><td>10</td><td>9.3314e-04</td><td>.022</td><td>9.3314e-04</td></tr><tr><td>25</td><td>4.7267e-04</td><td>.015</td><td>2.2814e-04</td></tr><tr><td>50</td><td>2.5894e-04</td><td>.011</td><td>1.2790e-04</td></tr></table>	Epoch.no	MSE	MAE	Lose	10	9.3314e-04	.022	9.3314e-04	25	4.7267e-04	.015	2.2814e-04	50	2.5894e-04	.011	1.2790e-04	<p><i>Mean square logarithmicerror</i> As the lose function, <i>ADAGrad</i> as an optimizer, <i>two layers</i> for the encoder, and another reverse for the decoder, he used <i>relu</i> as the activation function. The run time per each epoch is 10s.</p>		
Epoch.no	MSE	MAE	Lose																			
10	9.3314e-04	.022	9.3314e-04																			
25	4.7267e-04	.015	2.2814e-04																			
50	2.5894e-04	.011	1.2790e-04																			
<table><tr><th>T.acc</th><th>Te.acc</th><th>recall</th></tr><tr><td>73.08</td><td>69.74</td><td>.478</td></tr><tr><th>Precision</th><th>F1</th><th>AUC</th></tr><tr><td>.461</td><td>.154</td><td>.523</td></tr></table>			T.acc	Te.acc	recall	73.08	69.74	.478	Precision	F1	AUC	.461	.154	.523								
T.acc	Te.acc	recall																				
73.08	69.74	.478																				
Precision	F1	AUC																				
.461	.154	.523																				
C			D		E																	

Table 1 shows the combination with the best auto encoder results. The upper row shows the matrices of the auto encoder. The second row shows the matrices of the classi-



fication. A show the loss parameter of the training and validation iterations the loss in the training is decreasing by increasing the epochs also in the validation set. B shows the mean square error is getting decrease when increasing the epoch's number also the loss and the mean absolute error getting decrease. In the second row, C shows the different parameters of the classification (which is not the best one). D shows the confusion matrix of the classification stage which shows the performance of the classification model and the relation between the predicted and the actual values. E shows the iterations in the classification step.



**Figure.11:** The roc curve of the classifier on the retrieved images

Figure 10 shows the roc curve which shows the classification algorithm with reflects of different hyper parameters on the classification result. The mean square logarithmic error lose function, ADAGRAD optimizer, relu activation function and two CNN( MSLE+ADAGrad+relu+2 layers) have the best curve mean square logarithmic error lose function, ADAM optimizer, relu activation function and two CNN (MSLE+ADAM+relu+2 layers) and mean square logarithmic error lose function, ADAM optimizer, relu activation function and five CNN (MSLE+ADAM+relu+3 layers).

## 5. CONCLUSION

Simulation of the proposed Auto encoder for real time IoT systems by Combining Hyper parameter is validated and the effect of different parameters on the auto encoder and the matrices of the classification algorithm is done. From this investigation, we concludes that changing the algorithm hyperparameters may affect the algorithm matrices and the number of epochs also. The results shows that by increasing the number of epochs decrease the loss function but by increasing the number of layers does not increase the evaluation matrices. The optimizer (ADAM and ADAGrad) gives the best re-



sults when applying on the auto encoder with relu activation function and loss function Mean Square Logarithmic error. An early stopping can gives good results also.

**Acknowledgment:** The authors extend their appreciation to the Institute for Research and Consulting Studies at King Khalid University through Corona Research (Fast Track)

**Disclosure Statement:** No potential conflict of interest was reported by the author(s).

**Funding:** The funding was provided by the Institute for Research and Consulting Studies at King Khalid University through Corona Research (Fast Track) [grant number 3-103S-2020].

## References

1. Subha, R., Study on Cardiovascular Disease Classification Using Machine Learning Approaches. International Journal of Engineering and Computer Science, 2015. 4(12).
2. Shin, H.-C., et al., Deep convolutional neural networks for computer-aided detection: CNN architectures, dataset characteristics and transfer learning. IEEE transactions on medical imaging, 2016. 35(5): p. 1285-1298.
3. Hussein, A.S., et al. Efficient chronic disease diagnosis prediction and recommendation system. in 2012 IEEE-EMBS Conference on Biomedical Engineering and Sciences. 2012. IEEE.
4. Abubakar, F.M., A study of region-based and contour-based image segmentation. Signal & Image Processing, 2012. 3(6): p. 15.
5. Smith, P. and C. Chen. Transfer learning with deep CNNs for gender recognition and age estimation. in 2018 IEEE International Conference on Big Data (Big Data). 2018. IEEE.
6. Saranyadevi, S., R. Murugeswari, and S. Bathrinath. Fuzzy Logic based Recommendation System for Road Accident Data Analysis. in 2019 IEEE International Conference on Intelligent Techniques in Control, Optimization and Signal Processing (INCOS). 2019. IEEE.
7. Tammina, S., Transfer learning using VGG-16 with Deep Convolutional Neural Network for Classifying Images. International Journal of Scientific and Research Publications, 2019. 9(10): p. 143-150.
8. Wang, L. and A. Wong, COVID-Net: A Tailored Deep Convolutional Neural Network Design for Detection of COVID-19 Cases from Chest X-Ray Images. arXiv preprint arXiv:2003.09871, 2020.
9. Yas, Q.M. and M. Khalaf. A Trusted MANET Routing Algorithm Based on Fuzzy Logic. in International Conference on Applied Computing to Support Industry: Innovation and Technology. 2019. Springer.
10. Buslaev, A., et al., Albumentations: fast and flexible image augmentations. Information, 2020. 11(2): p. 125.
11. Shorten, C. and T.M. Khoshgoftaar, A survey on image data augmentation for deep learning. Journal of Big Data, 2019. 6(1): p. 60.
12. Mikołajczyk, A. and M. Grochowski. Data augmentation for improving deep learning in image classification problem. in 2018 international interdisciplinary PhD workshop (IIPhDW). 2018. IEEE.
13. Takahashi, R., T. Matsubara, and K. Uehara, Data augmentation using random image cropping and patching for deep cnns. IEEE Transactions on Circuits and Systems for Video Technology, 2019.
14. Bloice, M.D., C. Stocker, and A. Holzinger, Augmentor: an image augmentation library for machine learning. arXiv preprint arXiv:1708.04680, 2017.
15. Perez, L. and J. Wang, The effectiveness of data augmentation in image classification using deep learning. arXiv preprint arXiv:1712.04621, 2017.
16. Tellez, D., et al., Quantifying the effects of data augmentation and stain color normalization in convolutional neural networks for computational pathology. Medical image analysis, 2019. 58: p. 101544.
17. Zhang, X., et al., Accelerating very deep convolutional networks for classification and detection. IEEE transactions on pattern analysis and machine intelligence, 2015. 38(10): p. 1943-1955.
18. Jain, A. and C. Gupta, Fuzzy logic in recommender systems, in Fuzzy Logic Augmentation of Neural and Optimization Algorithms: Theoretical Aspects and Real Applications. 2018, Springer. p. 255-273.

## BIOGRAPHY



**Abdelmoty M. Ahmed** received his B.Sc., M.Sc. degrees from Systems and Computers Engineering , Faculty of Engineering, Al- Azhar University in Cairo, Egypt, He is currently PHD student in Systems and computer Engineering in Al-Azhar University ,His research interests include Digital image processing, Artificial intelligent, pattern recognition, Human Computer Interaction, Computer Graphics, machine learning ,Deep Learning , Intelligent e-Learning, Intelligence Systems Engineering , Computer Vision and IOT systems.

\*Corresponding author E-mail:-[abd2005moty@yahoo.com](mailto:abd2005moty@yahoo.com) ; phone:-00966504538402 ; Abha; Saudi Arabia.



**Gamal Tharwat** received his B.Sc., M.Sc. And Ph.D. degrees from Al-Azhar University in Cairo,

Egypt. He is currently an Instructor in Computers and Systems Engineering Department at Faculty of Engineering in Cairo, Al-Azhar University, Egypt. His research interests include Artificial Intelligence, Intelligent e-Learning, Intelligence Systems Engineering, Computer Vision, Software Engineering, Database System, Data Mining, Semantic Web, Parallel Computers, Embedded Systems and IoT, Machine Learning, Deep Learning, Computer Networks, Wireless and Mobile Networks, Modeling and Simulation, Information Security.

E-mail:- [gamaltharwat@gmail.com](mailto:gamaltharwat@gmail.com)



**Belgacem Bouallegue** received his B.Sc. and M.Sc. degrees from University of Monastir, Tunisia, and Ph.D. from Graduate School of Engineering Science and Technology, University of Southern Brittany in Lorient, France with the cooperation of University of Monastir, Tunisia. He is currently an Assistant Professor in Department of Computer Engineering at College of Computer Science, King Khalid University, Saudi Arabia. His research interests include Integrated System Design, Fault Tolerance, HW/SW Co-design, Parallel Computers, Embedded Systems and IoT, Network on Chip NoC, AI, IPs and MPSoCs, Machine Learning, Deep Learning, Homogeneous/Heterogeneous Systems, Wireless Sensor Networks Security, and Cryptography. He is working in collaboration with Lab-STICC Laboratory, Lorient, France and LIP6, Computer Science Research Laboratory, PARIS Cedex 05, France.

E-mail:- [belgacem.bouallegue2015@gmail.com](mailto:belgacem.bouallegue2015@gmail.com).



**Mahmoud M. Khattab**, he received his B.Sc. and M.Sc. degrees in Computer Science from Menofiya University, Egypt. Currently he is a Ph.D. candidate at International Islamic University Malaysia. The area of his research interest lies in Super-Resolution Image Reconstruction. He is also working as a lecturer in Computer Science department, at King Khalid University, Saudi Arabia Kingdom since 2010.

E-mail:- [mmkhattab2000@gmail.com](mailto:mmkhattab2000@gmail.com).



**Ahmad M.J. Al Moustafa** he received his B.Sc. from Sudan University of Science & Technology, Khartoum, Sudan in 2004 and M.Sc. degrees from UNIVERSITI TEKNOLOGI MALAYSIA, Johor, Malaysia in 2007. He worked for King Khalid University in college of computer science in Saudi Arabia since 2008. He is currently a Ph.D. student in UNIVERSITI TEKNOLOGI MALAYSIA, Johor, Malaysia. His research interests include Computer Vision, Sign Recognition, Pattern Recognition, Smart Systems, Machine Learning, Deep Learning and Artificial intelligence.

E-mail:- [ahmad200000@hotmail.com](mailto:ahmad200000@hotmail.com).

**Safaa S. Matter**, she received her Bachelor's degree in Information Technology from Menofiya University, Egypt. She obtained her Master's degree in Information Technology from Menofiya University, Egypt. Currently she is a Ph.D. candidate at International Islamic University Malaysia. The area of her research interest lies in Wireless Computer Networks, Evaluating and improving routing protocols performance using network simulators. She is also working as a lecturer in Computer Science department, at King Khalid University, Saudi Arabia Kingdom since 2010. She has been Head of Computer Science department since 2013 till 2017. She is a member in Quality and Academic development committee.

E-mail:- [safaamatter2010@gmail.com](mailto:safaamatter2010@gmail.com).