

Article

Severity Predictions for Intercity Bus Crashes on Highway Using a Random Parameter Ordered Probit Model

Kanghyun Kim ¹ and Jungyeol Hong ^{2,*}

¹ Research Assistant, Keimyung University; ggh2803@kmu.kr

² Assistant Professor, Keimyung University

* Correspondence: jyhong9868@kmu.ac.kr

Abstract: As intercity buses are a mode that moves large scaled occupancy between regions, it accounts for the mode share-means for mid to long-distance movement in South Korea. However, the study on intercity bus safety needs to be more extensive, and safety policies are carried out based on traditional probability models without considering the data characteristics of bus accidents. Therefore, in this study, the Random Parameter Ordered Logit model was applied to derive fixed parameter factors that have the same effect on the severity of intercity bus accidents and random parameters that consider the heterogeneity of unique attributes by accident. It also analyzed the marginal effect of intercity bus accident severity. As a result of the study discovered that the influencing factors that reflect heterogeneity with Random Parameters were driver's condition: drowsiness, vehicle size: medium, crash type: vehicle-pedestrian accident, road condition: wet pavement, and log form of AADT. The random parameter ordered logit model was traditionally found to be more suitable than the ordinal logit model, which only reflects fixed factors and more reliable predictions considering the heterogeneity of accident characteristics for each observation.

Keywords: intercity bus; accident; severity; probability model; random parameter; ordered logit; heterogeneity

1. Introduction

Intercity buses driving on highways are a means of transportation that moves more Occupancies than passenger cars, causing numerous casualties and enormous socioeconomic losses in the event of a traffic accident. According to the Korea Expressway Corporation's highway accident report (2022), There were 258 highway bus accidents as of 2021. The accidents resulted in 179 victims, including 77 Minor injuries, five serious injuries, and 15 fatal crashes.

It represents 0.208 human damage per accident, higher than 0.12 per passenger car accident. Therefore, to prepare for highway bus accidents that cause such high human damage, it is necessary to analyze existing accident data to discover factors and marginal effects that affect the severity of traffic accidents and need highway bus safety and policies based on these results.

Existing studies conducted on several studies related to traffic accident prediction and severity analysis, but studies focused on buses need to be more comprehensive. In addition, each bus accident was insufficient to consider the heterogeneity of the accident impact depending on the road environment, traffic conditions, vehicle characteristics, human behavior, and spatiotemporal characteristics exposed by accident.

Many studies that discover the influencing factors of accident probability and severity assume that the influence of each independent variable in all accident observations is fixed. Thus, restricting variables that have different influences for each bus accident to one fixed coefficient value has the limitation of the biased result value.

Thus, to improve the model's limitations built from existing references related to bus accidents, this study was expected to find more consistent analysis results by applying a random parameter

methodology that can discover coefficient values considering the heterogeneity of variables affecting dependent variables.

This study collected raw data on highway bus accidents in Korea for five years, from 2012 to 2016, and explored factors that affect the severity of accidents by using the Random Parameter Ordered Probit Model methodology. In addition, we tried to identify Fixed Parameters that have the same effect on the severity of bus accidents regardless of the individual characteristics of all observations and Random Parameters that reflect heterogeneity and analyze the marginal effect of each variable to present findings for bus safety.

Existing studies on bus accidents mainly used the ordinal logit (or probit) method of the probability model to analyze the probability and severity of traffic accidents. Various methodologies have been applied, such as association rule mining, meta-analysis, random parameter multi-logit model, and multiple-level mixed-effect logit model. Bhin and Son [1] discovered factors affecting the severity of accidents according to the gender of bus drivers (all men and women) using decision trees and ordinal logit models. As a result, the factors that increase the severity of accidents for all drivers and male drivers are vehicle-to-vehicle accidents, speeding, and median enforcement. For female drivers, Minimum safety distance was a factor affecting the severity. Kim et al. [2] conducted a meta-analysis to find factors affecting the severity of city bus accidents. Variables such as speed violation, drunk, speed limit (100km/h or higher), vehicle-vehicle, nighttime, drowsiness, curved alignments, and driver's age were found to have a significant impact on the severity of city bus accidents. Using the ordinal logit model, Bhin and Son [3] analyzed the factors influencing the severity of accidents according to bus type and repetitive accident, and variables such as vehicle-person, speed violation, and signal violation were found to have a significant impact. Lee et al. [4] tried to contribute to establishing safer intercity bus policies by developing an accident model for each type of expressway bus accident (driver factor, road, environmental factor, and other factors) through the probability regression model. As a result, in the human factor model, the driver's age and driving experience (more than ten years) were found to be influential factors; significant factors of road and environmental factor models are road conditions (wet and freezing), weather (cloud), nighttime, longitudinal gradients (longer than 5%), and straight (500m or more). In other factor models, the number of vehicles and vehicle-vehicle variables affects the severity of the highway bus accident. Samrei et al. [5] discovered variables related to fatal bus accidents in Australia by applying association rule mining techniques. They found that the presence of pedestrians, female drivers, and road sections with dark vision was highly related to fatal bus accidents on weekends. Nguyen et al. [6], using the ordinal logit model, presented nighttime, the number of lanes (above the third lane), weather(rain), and local areas as factors affecting the severity of bus accidents in Hanoi, Vietnam. Yoon et al. [7] tried to find the cause affecting the severity of city bus accidents by applying an ordinal logit model. As a result, it was found that the factors increasing the severity of the city bus accident were speed (less than 70km/h), lane width (less than 3m), curve alignments (left, right), and road conditions(wet). In contrast, the factors that reduced the accident's severity were peak hours, snow, or road conditions(freezing).

Shen et al. [8] used an ordered probit model to find factors influencing the severity of bus accidents in the U.K., and it suggested variables with significant effects on collisions(head-on), road(wet), and speed limits. Wang et al. [9] analyzed the impact of collision accidents among the characteristics of individual bus drivers by applying a random effect two-level (level1-driver, level2-vehicle) logit model methodology. The result of the model establishment represents that drivers' age (46–55), aggressive and violent drivers, and the presence of insomnia were influencing factors at the driver level, and weather condition variables at the vehicle level affected bus accidents. Kaplan and Prato [10] used an ordered logit model to extract risk factors for the severity of British bus accidents. The analysis showed variables such as driver's age (under 25, over 65), speed limit (over 65 mph, less than 20 mph), and intersection were found to affect the severity of the bus accident. Finally, Damsere-Derry et al. [11] analyzed Ghana's severity of intercity bus accidents using a random parameter multi-logit model. The result suggested variables such as driver's age (60 or older), speeding, poor overtaking, careless driving, and inexperienced driver's career were found to be influencing factors.

In addition, research was conducted using ordered (probit) random parameters to consider the characteristics of each type of accident, such as vehicle type (truck, general vehicle), accident type (backward collision, single accident-left and right road departure, rollover accident, angle collision), road type (two-lane rural road), and age (elderly and youth) [12–21].

As a result of the existing literature review, studies related to accident severity according to various bus types have been attempted. However, most of them focused on the factors influencing the severity of bus accidents and the development of a prediction model based on traditional probability models. In particular, in-depth studies were conducted to reflect the heterogeneity of accident-influencing factors in various accident-related studies. For intercity buses, it was found that research was necessary considering the traffic characteristics of the studied area spatial and environmental affecting effects for each accident. Therefore, this study collected and analyzed data on various potential factors such as spatiotemporal characteristics, vehicle and human characteristics, road environment, and traffic environment of highway sections that affect highway bus severity. Furthermore, to consider the heterogeneity of the impact of highway bus accidents, the random parameter ordered probit model is applied to find variables with fixed probability parameters and random probability parameters of highway bus accident severity and define each effect.

2. Methods

In order to analyze the characteristics of factors affecting each severity of intercity bus accidents, the level of accidents was classified into physical damage and injury (serious injury & fatal), and a random parameter ordered probit model was used to explain the indexed characteristics of the severity of the accident. Existing studies have used a probit model that assumes the variance of the error term distribution is the same, and a normal distribution with zero covariance follows the covariance [22–28]. Since the probit model predicts binomial ($y = 0$ or 1), it was based on the random parameter ordinal probit model to be found through dependent variables y' considering random probabilities based on modeling the accident severity of each observation of the ordinal ($y = 0, 1, 2, 3 \dots$). Then, equation (1) is a random parameter ordered probit model.

$$y' = \beta'X + \varepsilon \quad (1)$$

Here, X is the vector value of the independent variable, β' is the Vector value of the estimable parameter, and ε is a random error term assumed to follow a normal distribution of observations with mean 0 and variance 1.

In Equation (2), the independent variable y is defined as follows by the unobserved variable y' .

$$y = \begin{cases} 3 & \text{if } y' \geq \mu_2 & (\text{severe injury}) \\ 2 & \text{if } \mu_1 < y' \leq \mu_2 & (\text{evident injury}) \\ 1 & \text{if } \mu_0 < y' \leq \mu_1 & (\text{possible injury}) \\ 0 & \text{if } y' < \mu_0 & (\text{no injury}) \end{cases} \quad (2)$$

Here, $\mu_0 = 0$, and μ_2 are thresholds jointly estimated with β' parameters. The probability of severity for each variable may be expressed as a distribution of random error terms ε .

$$\begin{aligned} P(y = 3) &= 1 - \Phi(\mu_2 - \beta'X) \\ P(y = 2) &= \Phi(\mu_2 - \beta'X) - \Phi(\mu_1 - \beta'X) \\ P(y = 1) &= \Phi(\mu_1 - \beta'X) - \Phi(\mu_0 - \beta'X) \\ P(y = 0) &= \Phi(\mu_0 - \beta'X) \end{aligned} \quad (3)$$

However, the standard probit model can treat β' parameters as constant values through observations, resulting in potentially biased results, which limits each variable to have the same effect on all individual observations. Therefore, considering this point, the random parameter ordered

probit model was applied to discover unobserved heterogeneity through randomly distributed error terms Φ .

$$\beta' = \beta + \Phi$$

(4)

Since the interpretation of the estimated coefficient values β for the accident severity is not simple, the effect of a unit-by-unit change in the independent variable on the probability of the accident severity measures the marginal effect. Random-parameter ordered probit models are typically used to measure the effect of variables at the level of accident severity while keeping all other variables constant, and the marginal effects can be expressed as follows.

$$\begin{aligned} \frac{\theta P(y=3)}{\theta X} &= \Phi(\mu_2 - \beta'X)\beta \\ \frac{\theta P(y=2)}{\theta X} &= [\Phi(\mu_1 - \beta'X) - \Phi(\mu_2 - \beta'X)]\beta \\ \frac{\theta P(y=1)}{\theta X} &= [\Phi(\mu_0 - \beta'X) - \Phi(\mu_1 - \beta'X)]\beta \\ \frac{\theta P(y=0)}{\theta X} &= \Phi(\mu_0 - \beta'X)\beta \end{aligned}$$

(5)

3. Results

3.1. Descriptive Statistics

The random parameter ordered probit model was applied to find fixed and random parameters that reflect heterogeneous observation characteristics, and the results showed that the coefficient value of each independent variable might have a variety of values by reflecting the unique characteristics of the variable.

For the analysis of this study, independent variables that potentially affect highway bus accidents were classified into road and traffic environment factors, human and vehicle factors, and spatiotemporal factors, as shown in Table 1. The collected independent variables are dummy variables with binomial values such as 1 (corresponding) or 0 (not applicable), including continuous variables such as Log-AADT. In addition, the dependent variable, Intercity bus Accident Severity, was ordered, and it was defined the value of 0 if the accident was a physical damage accident, 1 if it was an injury accident, and 2 if it was a severe & fatal accident.

Table 1. Summary statistics for effect factors of crash occurrence.

Category		Variables	Percentage of Variables
Spatial-temporal factors	Segment types	Main lane/Ramp/Tollgate/Tunnel /etc.	73%/11%/10%/5%/1%
	Barrier facilities	Guardrail shoulder/Guardrail fence/None of guardrail/Concrete/etc.	43%/1%/35%/9%/11%
		Vehicle	
	The causes of an accident	Defects/negligence/Speeding/Drowsiness/Flat tire/Obstacle/Safety distance violation/etc.	8%/26%/22%/10%/7%/10%/4%/14%
Human and vehicle factors	Driver's conditions	Normal/Tired/Drinking /etc.	92%/4%/2%/2%
	Vehicle sizes	Small/Medium/Large/etc.	49%/28%/21%/2%
	Types of accident	Vehicle-Object/Vehicle-Vehicle/Vehicle-Pedestrian/etc.	55%/24%/1%/20%
	Driver's ages	20s/30s/40s/50s/60s/Over 60 years old	6%/27%/14%/21%/23%/11%
Roadway and environmental factors	Rates of vehicle	Car/Truck/Bus	68%/4%/28%
	Road surface conditions	Moisture/Dry/Snow-Ice	27%/72%/1%

Weather	Snowy/Fine/Rainy/Cloudy/etc.	5%/60%/21%/14%/1%
Seasons	Spring/Summer/Fall/Winter	24%/28%/25%/24%
Annual average daily traffic volumes (vehs/day)	Log (AADT)	10.703

A probability model consisting of Fixed and Random Parameters variables was established by applying various independent variables that can affect the severity of intercity bus accidents, such as AADT and spatiotemporal (segment type, day, and time) factors presented in Table 1. The significance of each parameter was determined at a significance level of 90% ($P\text{-value} \leq 0.1$) in consideration of the number of samples, and probability distributions such as normal distribution, uniform distribution, and exponential distribution were considered to estimate the coefficient of the Random Parameter model. Through applying various probability distributions for each independent variable, this study found that variables were most significant when assumed to be a normal distribution. In addition, variables with the significance of the standard deviation for the Random Parameter distribution were identified, and the hypothesis that the factor variables affecting each observation were heterogeneous was supported through the corresponding result value.

The log-likelihood function was used as an indicator to determine the model’s goodness of fit of the finally selected severity prediction model of intercity bus accidents. The log-likelihood function generally indicates that the closer the value is to 0, the higher the model fit. As a result of the analysis of this study, the Restricted Log-likelihood value, including only the constant term, was -2,374.412, and the log-likelihood of the Fixed parameter model was improved to -2,057.16. In contrast, the log-likelihood of the Random Parameter model was -2,000.367, finding that the model’s suitability was somewhat improved.

Independent variables (ramps, toll gates, negligence, flat tire, obstacle defects, drowsiness, condition of driver (a normal condition), rain, vehicle-vehicle accident, guardrail, vehicle size (small, medium), driver’s age-30s, vehicle type(truck), summer, road condition(wet), and log-AADT) were statistically found to be significant at 90% significance level. Among them, variables (road condition(wet), vehicle size(medium), log-AADT, vehicle-pedestrian accident, and drowsiness) were adopted as significant variables in Random Parameters, which had a heterogeneous effect on the severity of bus accidents. The results of the traditional ordered probit model and the random parameter ordered probit model for the factors affecting the severity of highway bus accidents are shown in Tables 2 and 3, respectively.

Table 2. Ordered Probit Model of Intercity bus crash severity.

Variable	Estimate	Odds Ratio	Std. Err	t-Stat
Constant	-1.473	0.229	0.353	-4.178
Ramp (1 if ramp segment, 0 otherwise)	-0.355	0.701	0.087	-4.074
Tollgate (1 if tollgate, 0 otherwise)	-0.711	0.491	0.098	-7.268
Negligence (1 if driver’s negligence, 0 otherwise)	0.147	1.158	0.060	2.443
Flat tire (1 if bus tire is flatted, 0 otherwise)	0.275	1.317	0.097	2.841
Obstacle (1 if obstacle on the freeway, 0 otherwise)	-0.867	0.420	0.124	-6.995
Drowsiness (1 if driver’s drowsiness, 0 otherwise)	0.226	1.254	0.086	2.619
Small (1 if bus size is small, 0 otherwise)	-0.316	0.729	0.062	-5.078
Medium (1 if bus size is medium, 0 otherwise)	-0.246	0.782	0.068	-3.634
Vehicle-Vehicle (1 if the vehicle to vehicle crash, 0 otherwise)	0.739	2.095	0.060	12.358
Vehicle-Pedestrian (1 if the vehicle to pedestrian crashes, 0 otherwise)	2.134	8.445	0.208	10.255

normal (1 if the driver's condition is normal, 0 otherwise)	-0.342	0.711	0.089	-3.820
Rainy (1 if it rains, 0 otherwise)	0.234	1.264	0.106	2.203
Guardrail fence (1 if guardrail fence exists, 0 otherwise)	-0.639	0.528	0.315	-2.025
30s (1 if driver's age ≥ 30 and < 40 , 0 otherwise)	-0.173	0.841	0.058	-2.981
Rate of Truck volume (truck volume/total volume at the crash point)	2.882	17.843	1.335	2.159
Summer (1 if the season is Summer, 0 otherwise)	-0.160	0.852	0.055	-2.884
Moisture (1 if moisture on the pavement, 0 otherwise)	-0.334	0.716	0.097	-3.434
Log AADT (logarithm of AADT)	0.134	1.143	0.031	4.265
Log-likelihood function = -2,057.160				
Number of observations = 3,064				
Restricted Log-likelihood function = -2,374.412				

Table 3. Random Parameter Ordered Probit Model of Intercity bus crash severity.

Variable	Estimate	Odds Ratio	Std. Err	t-Stat
Constant	-1.534	0.216	0.354	-4.328
Ramp (1 if ramp segment, 0 otherwise)	-0.366	0.693	0.089	-4.130
Tollgate (1 if tollgate, 0 otherwise)	-0.740	0.477	0.097	-7.662
Negligence (1 if driver's negligence, 0 otherwise)	0.149	1.161	0.062	2.399
Flat tire (1 if bus tire is flatted, 0 otherwise)	0.292	1.339	0.093	3.140
Obstacle (1 if obstacle on the freeway, 0 otherwise)	-0.884	0.413	0.126	-6.987
Drowsiness (1 if driver's drowsiness, 0 otherwise)	0.213	1.237	0.088	2.421
Standard deviation of parameter	0.307	1.360	0.074	4.150
Small (1 if bus size is small, 0 otherwise)	-0.322	0.725	0.063	-5.131
Medium (1 if bus size is medium, 0 otherwise)	-0.290	0.748	0.070	-4.156
Standard deviation of parameter	0.326	1.386	0.048	6.825
Vehicle-Vehicle (1 if the vehicle to vehicle crash, 0 otherwise)	0.762	2.143	0.062	12.288
Vehicle-Pedestrian (1 if the vehicle to pedestrian crashes, 0 otherwise)	2.231	9.307	0.219	10.175
Standard deviation of parameter	0.432	1.540	0.212	2.035
normal (1 if the driver's condition is normal, 0 otherwise)	-0.359	0.698	0.087	-4.137
Rainy (1 if it rains, 0 otherwise)	0.243	1.275	0.110	2.206
Guardrail fence (1 if guardrail fence exists, 0 otherwise)	-0.652	0.521	0.384	-1.698
30s (1 if driver's age ≥ 30 and < 40 , 0 otherwise)	-0.178	0.837	0.061	-2.938
Rate of Truck volume (truck volume/total volume at the crash point)	3.008	20.252	1.414	2.128
Summer (1 if the season is Summer, 0 otherwise)	-0.166	0.847	0.057	-2.943
Moisture (1 if moisture on the pavement, 0 otherwise)	-0.377	0.686	0.100	-3.784
Standard deviation of parameter	0.281	1.324	0.050	5.596
Log AADT (Logarithm of AADT)	0.141	1.152	0.032	4.479
Standard deviation of parameter	0.012	1.012	0.002	5.400
Log-likelihood function = -2,000.367				
Number of observations = 3,064				
Restricted Log-likelihood function = -2,374.412				

3.2. Results of the random parameter model

Variables with heterogeneity selected as random parameters under normal distribution can calculate probabilities using statistically significant mean and standard deviation values, confirming the distribution of how each random parameter affects the severity of intercity bus accidents.


The drowsiness variable has an average value of 0.213 standard deviations of 0.037. Based on the normal distribution, it was found that about 75% of intercity bus accidents caused by Drowsiness increased the severity of accidents, and the remaining 25% decreased. These results show that Drowsiness is a factor that increases the severity of accidents such as road departure [29,30], but some drowsiness accidents occur in situations where there is not much traffic, such as nighttime, and In particular, it is expected to have a negative (-) effect on the severity of the accident as it is highly likely to occur in association with single accidents and physical damage accidents such as collisions with road obstacle.

The intercity bus’s vehicle size(medium) variable has an average value of -0.290 standard deviation of 0.326. about 19% of the bus accidents under normal distribution have a positive (+) effect on the severity of the accident, and the remaining 81% have a negative (-) effect. In the case of truck accidents proposed in some existing studies, it can be seen that the degree of impact varies depending on the size of the truck and unit [31,32]. Since the size of vehicles on the highway is proportional to the number of passengers, fatal casualties increase. However, in large buses with many passengers, drivers tend to avoid over-speeding, which can reduce the severity of an unexpected accident.

The vehicle-pedestrian accident variable had an average value of 2.231 and a standard deviation of 0.432, and according to the normal distribution, 100% of bus accidents had a positive (+) effect on the severity of the accident. This result shows consistency with Existing studies that vehicle-pedestrian accidents increase the severity of accidents [33,34]. As the vehicle drives at high speed, the risk of severe injury and fatality in a collision with a pedestrian is expected to be very high.

The road condition(wet) variable has an average value of -0.377 and a standard deviation of 0.281. while 9% of the observations increased the severity of bus accidents, 91% were found to decrease. There are results of existing studies that increase the severity of the accident [35,36], but there are conflicting results that reduce the road conditions (wet), on the contrary [34,37,38]. Although accidents in road conditions(wet) may increase the severity of the accident due to increased braking distance when braking on slippery roads, this can increase the severity of the accident due to a front collision with the median barriers and a rear collision with the car in front, the occurrence and severity of accidents decrease since the driver can give an effect of focusing more on safe driving based on preliminary information on the risk of highway accidents, such as weather forecasts, navigation, and highway information.

The log-AADT variable was significant for Random Parameters under a normal distribution. All observations were found to have a positive (+) relationship with the severity of the bus accident, with an average value of 0.141 and a standard deviation of 0.012 parameters. This result showed contradictory results from existing studies that the impact of traffic on the spatial scope is a factor that increases or decreases the severity of accidents [39,40]. The increase in log-AADT means frequent conflicts between vehicles and buses on highways exist. Therefore, thorough highway reinforcement and control reduce Thorough highway crackdown and control. However, if an accident occurs in proportion to traffic volume, the injuries are expected to be enormous due to secondary accidents such as chain collisions.






Figure 1. Parameter distribution of Random Parameter variable.

3.3. Results of fixed parameter model

Each fixed parameter variable derived through the random parameter ordered probit model has a homogeneity in effect on all observations, and the interpretation of the results is as follows. First, the severity of bus accidents in the ramp and tollgate segment was 0.693 and 0.477 times higher than in other accident segments. According to the results of fundamental statistical analysis, bus accidents in the main-lane segment are the highest at 73% of all accidents. In particular, the main-lane segment is more likely to be various driving risk behaviors such as speeding and negligence of Safe Driving than the ramp and tollgate segment. Hence, the severity of accidents is higher than in other segments.

Second, the severity of bus accidents caused by vehicle-vehicle on highways was 1.953 times higher than vehicle(single). Vehicle-vehicle accidents strongly influence the severity of accidents in proportion to the degree of collision between vehicle-vehicle and the number of passengers in the vehicle. Therefore, they are more likely to have greater severity and damage than a single(vehicle) caused by a collision with facilities.

Third, the probability of bus accident severity according to the small size was 0.7 times higher than large buses. Large buses have many occupancies, which can cause more damage than small buses in the event of an accident. Thus, it is necessary to develop situational awareness and decision abilities for drivers of large vehicles so that passengers can safely escape the dangerous situation.

Fourth, the probability of the severity of a bus accident when the driver's condition is normal was 0.698 times lower than an abnormal driver, such as drinking or illness. In general, drivers in normal conditions instinctively make motions that can minimize the accident's severity when facing unexpected situations, so the accident's severity is higher than abnormal driver conditions such as drinking and diseases.

Fifth, it was found that the severity of bus accidents at guardrails was 0.519 times lower than at other barrier facilities. Guardrail plays a significant role in preventing secondary accidents such as median encroachment and falling in advance. Thus, checking and inspecting road safety facilities such as guardrails in sections with high frequency or high severity of bus accidents should be carried out periodically.

Sixth, it discovered that the probability of the severity of a bus accident in rainy weather was 1.193 times higher than in other weather. Highways have systematically responded to dangerous situations to enable safer driving by expressing lowered speeds depending on road conditions such as road conditions (wet, ice) through variable speed limit (VSL). If it rains on the highway, securing a view with the front vehicle is impossible, which may lead to a secondary accident due to a collision. In addition, it is necessary to induce safe driving behavior of bus drivers to comply with the laws that reduce the speed limit as the available range of view decreases.

Seventh, the driver's age 30s was found to reduce the severity of bus accidents by 0.847 times. Since drivers aged 30s is physically healthier than elderly drivers, they not only accumulate less

fatigue when driving for a long time but also take less time to recognize and operate the situation than elderly drivers. Finally, the summer dummy variable was found to lower the probability of accident severity by 0.841 times. In summer, there is no slippery road surface, such as freezing caused by snow, and heavy snow in winter, so it is lower in severity than in other seasons, such as winter.

Finally, the severity of the bus accident caused by negligence and the flat tire was 1.184 times and 1.278 times higher than other causes of the accident. Since the human cause of most accidents on highways is negligence, policy establishment such as improving safety driving awareness for drivers is needed to address the problem of increasing the severity of the accident.

3.4. Marginal effects

In this study, marginal effects were estimated to intuitively understand the effect of independent variables in the built model on Dependent variables (severity – physical damage, injury, serious injury, and fatal). The marginal effect refers to the degree of change in the dependent variable's severity value when the independent variable's value changes by one unit or the value of the dummy variable changes from 0 to 1, 1 to 0. The values of the marginal effect for each variable through the developed model are summarized as shown in Table 4.

The severity of physical damage accidents in the ramp and tollgate segments increased by 11.56% and 20.75%, respectively. However, the severity of injury accidents decreased by 10.8% in the ramp, 17.8% in the tollgate segment, and 1.6% and 2.2% in each facility.

Vehicle-vehicle accidents increased injury severity by 19.4% and fatal and severe accidents by 5.2%, while physical damage accidents decreased by 24.6%.

Small-size bus accidents increase the severity of injuries, serious injuries, and fatal by 10.4% and 1.9%, while medium-sized buses decrease by 9.6% and 1.6%, respectively. As the proportion of trucks in the highway segment increases, the severity of injuries and fatal and severe accidents for intercity buses increases to 98.7% and 18%, respectively.

When the driver's condition was normal, and the age was the 30s, the severity of physical accidents on the bus increased by 13.3% and 5.6%, respectively. On the other hand, bus severity on guardrails decreased by 16.1% and 1.9%, respectively, for injuries, serious injuries, and fatal.

When it was summer or road conditions(wet), physical damage increased the severity by 5.8% and 10.9%. Nevertheless, injuries, serious injuries, and fatal in the summer were expected to decrease by 5% and 0.9%, and road conditions (wet) by 9.4% and 1.5%, respectively. Contrary to the discovered result earlier, the severity of physical damage accidents in rainy decreases by 6.3% compared to other weather, but injuries, serious injuries, and fatal increase the severity by 5.2% and 1%.

It was found that the increase in log-AADT increased the severity of the injury, serious injury, and fatal accidents, while the severity of physical damage accidents decreased.

Finally, the severity of physical damage accidents caused by negligence, flat tire, and drowsiness decreased by 6%, 8.9%, and 6.9%, respectively, but increased by 24.2% for road obstacles.

Table 4. The marginal effect of random parameter ordered probit prediction model.

Variable	Fatal & Severe Injury	Minor Injury	Property Damage Only
Ramp	-0.013	-0.103	0.116
Tollgate	-0.020	-0.188	0.208
Negligence	0.007	0.045	-0.052
Flat tire	0.018	0.089	-0.107
Obstacle	-0.021	-0.214	0.235
Drowsiness	0.012	0.065	-0.077
Vehicle size-Small	-0.015	-0.096	0.111
Vehicle size-Medium	-0.012	-0.085	0.096
Vehicle-Vehicle	0.055	0.226	-0.281
Vehicle-Pedestrian	0.533	0.132	-0.665
Driver's condition-normal	-0.023	-0.110	0.133

Rainy	0.013	0.074	-0.087
Guardrail fence	-0.016	-0.163	0.179
Driver’s age 30s	-0.008	-0.053	0.060
Rate of Truck	0.139	0.901	-1.040
Summer	-0.007	-0.049	0.056
Pavement-Moisture	-0.015	-0.109	0.124
Log AADT	0.007	0.042	-0.049

4. Conclusions

This study tried to overcome the limited point of existing studies that could not consider the heterogeneity of influencing factors derived from the ordinal logit (or ordinal probit) model and improve the reliability of the severity analysis of highway bus accidents.

Among the factors affecting the severity of highway bus accidents, we identified the difference between the existing probability model by deriving Fixed Parameters with homogeneous effects and Random Parameters with heterogeneity. Raw data on highway bus accidents in Korea for five years, from 2012 to 2016, were used to analyze this study. We identify the difference between the existing probability model and the random parameter probit model, which has Fixed Parameters with homogeneous effects and Random Parameters with heterogeneity.

Among the variables that significantly affect the severity of highway bus accidents, it was founded that drowsiness, vehicle size(medium), vehicle-pedestrian accident, road condition (wet), and log-AADT had a heterogeneous effect on highway bus accident severity.

Based on the Random Parameter variable results, the severity of the intercity bus accident and the implications derived from each variable are as follows.

The vehicle-pedestrian accident and log-AADT were found to have a 100% positive (+) effect on the severity of bus accidents. As intercity buses run higher than 100km/h, there is a high possibility of death or severe damage in a collision with a person. In addition, the higher the AADT, the more crowded it is. Consequently, it can cause secondary accidents continuously, so the damage caused by the accident is expected to increase.

Among the vehicle size(medium) of intercity buses, it was confirmed that 19% of bus accidents had a positive effect on the severity of the accident, and the remaining 81% had a negative effect. As it affects the number of passengers on board in proportion to the size of the vehicle, casualties may increase in the event of an accident. However, the higher the number of passengers on board, the stronger the driver’s sense of responsibility may induce the driver to drive safely.

The road condition(wet) increases the severity of bus accidents by about 9% of bus accidents, but the other 91% decreased. Road condition (wet) creates a slippery road environment, which can increase the risk of accidents due to chain collisions. Nevertheless, it can increase the driver’s concentration on safe driving based on real-time information transmission media for the road environment, such as weather forecasting and navigation.

Finally, intercity bus accidents caused by drowsiness increased the severity by about 75% while reducing it by 25%. Drowsiness can increase the severity of the accident due to lane departure. But, some accidents caused by drowsiness are likely to occur alone in the early morning when there is not much traffic volume, so unlike other conditions of drivers such as drunk, it is expected to have a negative impact on the severity of the accident.

As evidenced by the results of this study, the severity of intercity bus accidents has the effect of heterogeneous influencing factors for each observation, so unlike the existing safety policies, various policies will be needed to promote intercity bus safety by identifying the characteristics of each accident. Therefore, in the future, the advanced bus safety prediction model is expected to be developed by considering the heterogeneity of spatial and temporal aspects according to (routes and year) and factors affecting the severity of bus accidents.

Author Contributions: Conceptualization, J.H.; methodology, J.H. and K.K.; software, K.K.; validation, J.H., and K.K.; formal analysis, K.K.; investigation, J.H.; data curation, J.H.; writing—original draft preparation, K.K.;

writing—review and editing, J.H.; visualization, K.K.; supervision, J.H.; funding acquisition, J.H. All authors have read and agreed to the published version of the manuscript.

Funding: This research was supported by the Bisa Research Grant of Keimyung University in 2021(10371).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Data will be available on request.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Bhin, M.; Son, S. Analysis of factors influencing traffic accident severity according to gender of bus drivers. *Journal of Korean Society of Transportation*. 2018, 36(6), 440-451.
2. Kim, H.; Jeon, G.; Jang, J.A.; Yoon, I. Analysis of Factors Affecting Buses and Trucks Crash Severity Using Meta-Analysis. *Journal of Korean Society of Transportation*. 2020, 38(6), 520-535.
3. Bhin, M.; Son, S. The Analysis of Bus Traffic Accident to Support Safe Driving for Bus Drivers. *Journal of Korea Institute Intelligent Transportation System*. 2019, 18(1), 14-26.
4. Lee, K.; Lee, Y.T.; Chang, M.S. The Application and Development of Accident Model on Freeways. *Proceedings of the 36th KOR-KST Conference*. 1999, 117-122.
5. Samerei, S.Y.; Aghabayk, K.; Mohammadi, A.; Shiwakoti, N. Data mining approach to model bus crash severity in Australia. *Journal of Safety Research*. 2021, 76, 73-82.
6. Nguyen, T.C.; Nguyen, M.H.; Armoogum, J.; Ha, T.T. Bus Crash Severity in Hanoi, Vietnam. *Safety*. 2021, 7(3), 1-14.
7. Yoon, S.; Kho, S.Y.; Kim D.K. Effect of Regional Characteristics on Injury Severity in Local Bus Crashes: Use of Hierarchical Ordered Model. *Transportation Research Record Journal of the Transportation Research Board*. 2017, 2647(1), 1-8.
8. Shen, J.; Gu, H.; Feng, X.; Yu, M.; Zheng, C. Investigation of factors contributing to bus-crash severity based on extended hierarchical ordered probit model with heteroscedasticity. *Journal of Transportation Safety & Security*. 2022, 14(9), 1531-1551.
9. Wang, X.; Jiao, Y.; Huo, J.; Li, R.; Zhou, C.; Pan, H.; Chai, C. Analysis of safety climate and individual factors affecting bus drivers' crash involvement using a two-level logit model. *Accident Analysis & Prevention*. 2021, 154, 1-10.
10. Kaplan, S.; Prato, C.G. Risk factors associated with bus accident severity in the United States: A generalized ordered logit model. *Journal of Safety Research*. 2012, 43, 171-180.
11. Damsere-Derry, J.; Adanu, E.K.; Ojo, T.K.; Sam, E.F. Injury-severity analysis of intercity bus crashes in Ghana: A random parameters multinomial logit with heterogeneity in means and variances approach. *Accident Analysis & Prevention*. 2021, 160, 106323.
12. Anastasopoulos, P.C.; Mannering, F.L. An empirical assessment of fixed and random parameter logit models using crash-and non-crash-specific injury data. *Accident Analysis & Prevention*. 2011, 43(3), 1140-1147.
13. Russo, B.J.; Savolainen, P.T.; Schneider IV, W.H.; Anastasopoulos, P.C. Comparison of factors affecting injury severity in angle collisions by fault status using a random parameter bivariate ordered probit model. *Analytic methods in accident research*. 2014, 2, 21-29.
14. Fountas, G.; Anastasopoulos, P.C.; Abdel-Aty, M. Analysis of accident injury-severities using a correlated random parameter ordered probit approach with time variant covariates. *Analytic methods in accident research*. 2018, 18, 57-68.
15. Jalayer, M.; Shabanpour, R.; Pour-Rouholamin, M.; Golshani, N.; Zhou, H. Wrong-way driving crashes: A random-parameters ordered probit analysis of injury severity. *Accident Analysis & Prevention*. 2018, 117, 128-135.
16. Chen, F.; Song, M.; Ma, X. Investigation on the injury severity of drivers in rear-end collisions between cars using a random parameter bivariate ordered probit model. *International journal of environmental research and public health*. 2019, 16(14), 2632.
17. Azimi, G.; Rahimi, A.; Asgari, H.; Jin, X. Severity analysis for large truck rollover crashes using a random parameter ordered logit model. *Accident Analysis & Prevention*. 2020, 135, 105355.
18. Shao, X.; Ma, X.; Chen, F.; Song, M.; Pan, X.; You, K. A random parameter ordered probit analysis of injury severity in truck involved rear-end collisions. *International journal of environmental research and public health*. 2020, 17(2), 395.
19. Xie, S.; Ji, X.; Yang, W.; Fang, R.; Hao, J. Exploring risk factors with crash severity on China two-lane rural roads using a random-parameter ordered probit model. *Journal of advanced transportation*. 2020, 2020, 1-14.

20. Darban Khales, S.; Kunt, M.M.; Dimitrijevic, B. Analysis of the impacts of risk factors on teenage and older driver injury severity using random-parameter ordered probit. *Canadian Journal of Civil Engineering*. 2020, 47(11), 1249-1257.
21. Okafor, S.; Adanu, E.K.; Lidbe, A.; Jones, S. Severity analysis of single-vehicle left and right run-off-road crashes using a random parameter ordered logit model. *Traffic injury prevention*. 2023, 24(3) 251-255.
22. Kockelman, K.M.; Kweon, Y.J. Driver injury severity: an application of ordered probit models. *Accident Analysis & Prevention*. 2002, 34(3), 313-321.
23. Rifaat, S.M.; Chin, H.C. Accident severity analysis using ordered probit model. *Journal of advanced transportation*. 2007, 41(1), 91-114.
24. Xie, Y.; Zhang, Y.; Liang, F. Crash injury severity analysis using Bayesian ordered probit models. *Journal of Transportation Engineering*. 2009, 135(1), 18-25.
25. Lemp, J.D.; Kockelman, K.M.; Unnikrishnan, A. Analysis of large truck crash severity using heteroskedastic ordered probit models. *Accident Analysis & Prevention*. 2011, 43(1), 370-380.
26. Ye, F.; Lord, D. Investigation of effects of underreporting crash data on three commonly used traffic crash severity models: multinomial logit, ordered probit, and mixed logit. *Transportation Research Record*. 2011, 2241(1), 51-58.
27. Chiou, Y.C.; Hwang, C.C.; Chang, C.C.; Fu, C. Reprint of "Modeling two-vehicle crash severity by a bivariate generalized ordered probit approach". *Accident Analysis & Prevention*. 2013, 61, 97-106.
28. Kardar, A.; Davoodi, S.R. A generalized ordered probit model for analyzing driver injury severity of head-on crashes on two-lane rural highways in Malaysia. *Journal of Transportation Safety & Security*. 2020, 12(8), 1067-1082.
29. Roy, U.; Dissanayake, S. Comparison of factors associated with run-off-road and non-run-off-road crashes in Kansas. In *Journal of the Transportation Research Forum*. 2011, 50, 69-86.
30. Kang, C.; Chung, Y.; Chang, Y.J. Injury severity analysis of truck-involved crashes on Korean freeway systems using an ordered probit model. *KSCE Journal of Civil and Environmental Engineering Research*. 2019, 39(3), 391-398.
31. Wang, K.; Bhowmik, T.; Yasmin, S.; Zhao, S.; Eluru, N.; Jackson, E. Multivariate copula temporal modeling of intersection crash consequence metrics: a joint estimation of injury severity, crash type, vehicle damage and driver error. *Accident Analysis & Prevention*. 2019, 125, 188-197.
32. Dong, C.; Richards, S. H.; Huang, B.; Jiang, X. Identifying the factors contributing to the severity of truck-involved crashes. *International journal of injury control and safety promotion*. 2015, 22(2), 116-126.
33. Chen, H.; Cao, L.; Logan, D.B. Analysis of risk factors affecting the severity of intersection crashes by logistic regression. *Traffic injury prevention*. 2012, 13(3), 300-307.
34. Tay, R.; Rifaat, S.M. Factors contributing to the severity of intersection crashes. *Journal of Advanced Transportation*, 2007, 41(3), 245-265.
35. Anowar, S.; Yasmin, S.; Tay, R. Factors influencing the severity of intersection crashes in Bangladesh. *Asian transport studies*. 2014, 3(2), 143-154.
36. Prato, C.G.; Kaplan, S. Bus accident severity and passenger injury: evidence from Denmark. *European transport research review*. 2014, 6(1), 17-30.
37. Zhu, X.; Srinivasan, S. A comprehensive analysis of factors influencing the injury severity of large-truck crashes. *Accident Analysis & Prevention*. 2011, 43(1), 49-57.
38. Rifaat, S.M.; Chin, H.C. Accident severity analysis using ordered probit model. *Journal of advanced transportation*. 2007, 41(1), 91-114.
39. Wang, Y.; Luo, Y.; Chen, F. Interpreting risk factors for truck crash severity on mountainous freeways in Jiangxi and Shaanxi, China. *European transport research review*. 2019, 11, 1-11.
40. Anastasopoulos, P.C.; Shankar, V.N.; Haddock, J.E.; Mannering, F.L. A multivariate tobit analysis of highway accident-injury-severity rates. *Accident Analysis & Prevention*. 2012, 45, 110-119.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.