

Article

Not peer-reviewed version

Colorimetric Quantification for Residual Poly- DADMAC in Water Treatment

Ilii Levakov , Ido Maor , Chen Barak , Yael Kirshenbaum , [Giora Rytwo](#) *

Posted Date: 20 September 2023

doi: 10.20944/preprints202308.1663.v2

Keywords: Cationic polyelectrolyte coagulant; fast green; spectrophotometric quantification; water treatment



Preprints.org is a free multidiscipline platform providing preprint service that is dedicated to making early versions of research outputs permanently available and citable. Preprints posted at Preprints.org appear in Web of Science, Crossref, Google Scholar, Scilit, Europe PMC.

Copyright: This is an open access article distributed under the Creative Commons Attribution License which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Disclaimer/Publisher's Note: The statements, opinions, and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions, or products referred to in the content.

Article

Colorimetric Quantification for Residual Poly-DADMAC in Water Treatment

Ilil Levakov ¹, Ido Maor ^{1,2,†}, Chen Barak ¹, Yael Kirshenbaum ² and Giora Rytwo ^{1,2,*}

¹ Environmental Physical Chemistry Laboratory, MIGAL-Galilee Research Institute, Kiryat Shmona, 1101602, Israel

² Environmental Sciences & Water Sciences Departments, Tel Hai College, Upper Galilee, 1220800 Israel

* Correspondence: rytwo@telhai.ac.il or giorarytwo@gmail.com; Tel.: +972-4-7700516

† Deceased.

Abstract: Poly-DADMAC (PD) is a commonly used organic polymer in water treatment, known for its effectiveness as a coagulant. However, its presence as a residue in water raises concerns related to membrane fouling and the potential formation of carcinogenic compounds. Therefore, fast and simple quantification is necessary to efficiently control and monitor the optimal dose of poly-DADMAC with minimal negative effects. This study introduces a new colorimetric quantification method for poly-DADMAC, based on complexation with a cationic dye (fast green- FG). The method was examined through varying conditions which included different analytical and commercial poly-DADMAC formulations and concentrations. The experiments confirm its effectiveness in quantifying poly-DADMAC with a detection limit of $3.22 \mu\text{g L}^{-1}$ (0.02 μM based on monomers' molecular weight), which is one order of magnitude lower than regulatory requirements ($50 \mu\text{g L}^{-1}$). To validate the method, the effect of pH was examined, and implementation demonstrations were conducted on cyanobacteria and cowshed polluted water samples. This research introduces a fast, cost-effective innovative method to accurately quantify poly-DADMAC, enhancing water treatment strategies for high-quality purification and water reuse.

Keywords: cationic polyelectrolyte coagulant; fast green; spectrophotometric quantification; water treatment

1. Introduction

Coagulation and flocculation are important preliminary steps in wastewater and potable water treatment facilities. The processes include the removal of non-dissolved and particulate matter, including algae, pathogens, organic materials, minerals, and others. This is achieved by the addition of materials such as ferric chloride, alum (aluminum sulfate), or organic polymers, which destabilize the colloids resulting in small suspended particles agglomerating into larger settleable flocs [1]. Poly-diallyl-dimethylammonium chloride (poly-DADMAC, PD, CAS 26062-79-3) is a homopolymer also known as polyquaternium-6, with a chemical formula of $(\text{C}_8\text{H}_{16}\text{NCl})_n$ (Figure 1). In commercial formulations, its molecular weight typically ranges from a few hundred to several thousand kDa, depending on the number of monomers (each with a molecular weight of 161.7 Da) [2]. PD is the most common polymer used in various coagulation processes [3], including in pulp and paper industry, either alone [4] or in combination with other polymers [5]. It was the first cationic polyelectrolyte approved by the Food and Drug Administration of the U.S.A (FDA) for use in potable water treatment [6]. Recent studies also test its influence when adsorbed on cellulose based products [7] or for the preparation of specific adsorbing matrices for per- and polyfluoroalkyl substances [8].

The wide utilization of PD and other organic polymers can be attributed to several advantages. These include their remarkable cationic properties, high charge density that leads to the formation of stronger and easily separable flocs, effective bridging capabilities allowing for higher solid content in the sludge phase, and minimal impact on pH levels, necessitating only a single pH adjustment during the process. However, a few disadvantages are associated with the use of PD as a coagulant, mainly regarding the residuals remaining after the process. While PD can serve as an effective

coagulant, its presence in the subsequent treatment process might cause severe fouling to the filtration membranes. Although novel membranes with better anti-fouling and anti-microbial properties have been developed [9,10], residual PD molecules of even low concentrations can desorb onto the membrane surface, potentially leading to pore blocking [11]. Fouling depends on the type, charge, size, and concentration of the polymer, and higher molecule-weight polymers have larger fouling potential [12,13]. Membrane fouling, particularly in processes like reverse osmosis, microfiltration, and nanofiltration, can lead to reduced water flux and increased energy consumption. It necessitates more frequent membrane cleaning or replacement, subsequently elevating operational costs in water treatment plants [14]. An additional disadvantage is the reaction of residual PD with disinfection by-products such as chloramine and ozonation, forming carcinogenic nitrosamines [15–19]. Therefore, several American and European standardization organizations have limited the residual amount of PD in drinking water at $\leq 50\text{ }\mu\text{g/L} \sim 0.310\text{ }\mu\text{M}$, which is considered to be also toxic to aquatic organisms [20].




Figure 1. Chemical structure of polyDADMAC (PD, polyquaternium-6, left) and fast green (FG, E143, right).

For these reasons, fast and simple quantification of residual PD is required at relatively low limits of detection (LOD), to control and monitor the optimal coagulant dose with minimal negative effects. Chromatography-based analytical methods for quantification of polymers are usually very sensitive to interferences by other organic molecules [21]. Indeed, a recent study presents a method based on ion-pair chromatography, which accurately measures residual DADMAC monomers [22] without measuring the amounts of the polymer. Other accurate methods such as gel permeation chromatography, epoxidation, fluorescent tagging, and co-precipitation required advanced, expensive, and long procedures [2,3,23–26]. A highly sensitive method was developed based on the use of gold nanoparticles [27], applied in South African treated water [28] and recently developed to Lovibond color filters [29], but the preparation of the nanoparticles requires a relatively complicated procedure.

Cationic polyelectrolytes such as PDs can bind to anionic molecules such as tannic acid or anionic dyes like rose Bengal, methyl-orange [23], Ponceau S [30], and acid orange [31] resulting in an insoluble polymer-anion complex that can be separated by centrifugation. This separation method allows the quantification of the polymer concentration by measuring the remaining dye. A similar method was used for quantification of the cationic biopolymer chitosan, based on complexation with Cibacron Brilliant Red 3B-A [32]. However, in all those studies LODs were two to three orders of magnitude higher than the requirement.

In this study we present a simple colorimetric quantification method based on addition of fast green (Figure 1, FG, ethyl-[4-[[4-[ethyl-[(3-sulfophenyl) methyl] aminophenyl]- (4-hydroxy- 2-sulfophenyl)methylidene]-1-cyclohexa-2,5-dienylidene]- [(3-sulfophenyl)methyl]azanium), and its complexation with PD. FG is an anionic tri-aryl methane food dye known also as “food green 3”, “green 1724” and “E143”. It is stable in a wide range of pH, and has a brilliant blue-green color with an absorption maximum at 624nm, and two additional smaller absorption bands at 420 and 304 nm [33]. The very high molar absorptivity ($\epsilon_{624} > 100000\text{ M}^{-1}\text{cm}^{-1}$) enables high sensitivity and yields a procedure suitable for trace quantification of PD with $\text{LOD} < 3\text{ }\mu\text{g L}^{-1}$ ($0.018\text{ }\mu\text{M}$)- one order of magnitude lower than regulation requirements. The primary objective of this research was to establish the proof of concept for the proposed quantification method in a simple, fast, and cost-

effective manner. This approach serves as the first step in mitigating PD's impact on membrane fouling and potential environmental risks. Additionally, we conducted preliminary implementations of the method under different conditions.

2. Materials and Methods

2.1. Materials

Analytical polydiallyl dimethylammonium chloride (PD; medium molecular weight, 200.000 to 350.000) and fast green (FG) were purchased from Sigma-Aldrich (Jerusalem, Israel). Commercial grade coagulant with 40% PD as an active ingredient manufactured by SNF Ltd. (FLOQUAT® FL-45) was purchased from Amgal-Depotchem Ltd. (Beer Tuvia, Israel). NC24 clay polymer nanocomposites were prepared as described in the literature [34–36] using 10 g/L sepiolite S9 provided by Tolsa S.A. (Madrid, Spain), and 45 g/L FL-45. DKG kaolinite clay polymer nanocomposites [37] were prepared in a similar way, using 10 g/L MPO kaolinite provided by Agat Minerals and Yehu Clays Ltd. (Yeruham, Israel) and 45 g/L FL-45. 1 mM HCl was prepared from 37% stock (Merck) and used for pH adjustment.

2.2. Complexation/calibration experiments description

In order to prepare calibration curves and demonstrate the method's applicability, several complexation experiments were conducted, including a wide range of analytic poly-DADMAC with fast green dye. Three separate experiments were conducted to examine different analytic PD concentrations. These concentrations included low, medium, and high PD ranges: 0.02-1 μ M (0.0322-0.1617 mg L⁻¹), 1-30 μ M (0.1617-4.851 mg L⁻¹), and 10-200 μ M (1.617-32.34 mg L⁻¹) PD solutions, all of which were dissolved in double-distilled water. To each PD range, 0.8, 20, and 100 μ M of FG were added to the solutions in the low, medium, and high series respectively. After the addition of FG, pH values were adjusted to 3-3.5 by adding 20 μ l of 1 mM HCl (see section 2.4). Subsequently, all samples were kept at room temperature (23 ± 1 °C) on an orbital shaker (200 rpm) for 1 hour. FG spectra were measured using a 1 cm cuvette in a Cary 60 UV-Vis spectrophotometer (Agilent Technologies, Santa Clara, CA, USA). Absorbance was determined using the absorption bands at 624 and 420nm with a molar absorptivity of 103500 and 11600 M⁻¹cm⁻¹ respectively. To enhance sensitivity, absorbances of the low range FG solutions were measured at 624 nm, utilizing a 5 cm cuvette. A visual representation of the preparation procedure and the experimental setup is available in Figure S1 of the Supplementary Material.

To confirm the formation of the PD-FG complexes, 50 ml samples containing 20 μ M FG and a range between 2.5-50 μ M PD solutions were prepared as described above, centrifuged, and the sediment was lyophilized (Christ Alpha 1-2 LD Plus, Germany) and measured for the attenuated total reflection-Fourier transform infrared (ATR-FTIR) spectra on a Nicolet iS10 FTIR (Nicolet Analytical Instruments, Madison, WI), using a SMART ATR device with a diamond crystal plate, within a range of wavenumber comprised from 4000 to 525 cm⁻¹ and analyzed with and OMNIC 9.3.32 software (Thermo Fisher Scientific, Madison, WI), including full spectra ATR correction.

2.3. Implementation in water with commercial PD

Commercial PD samples were examined in medium-range concentrations of 2-50 μ M (0.323-8.085 mg L⁻¹) PD dissolved in double-distilled water with the addition of 20 μ M FG. FG spectra were measured in the UV-Vis spectrophotometer using a 1 cm cuvette as described in section 2.2.

2.4. Influence of pH

To assess the performance of the quantification method in actual water samples, two coagulation-flocculation experiments were conducted. These experiments were carried out using water contaminated with cyanobacteria and cowshed effluents as test samples. The evaluation

involved testing both a commercial PD formulation and clay-PD nanocomposites developed within our research group.

2.5. Quantification of poly-DADMAC in coagulation water treatment samples

To evaluate the efficiency of the quantification method in “real” water samples, two coagulation experiments were performed, in cyanobacteria polluted water, and in cowshed effluents. Experiments included testing commercial PD formulation, and clay-PD nanocomposites developed in our research group [35–37].

The first coagulation experiment was performed on cyanobacteria culture suspension using concentrations of two poly-DADMAC-based coagulants: industrial PD and kaolinite-PD nanocomposites (DKG). The cyanobacteria suspension consisted of the *Microcystis* family, which was isolated from Lake Kinneret and cultivated in batch cultures using BG11 medium [38]. The experiments were carried out in 300 ml glass beakers and included two sets of PD and DKG coagulants. Each set comprised five distinct coagulant concentrations: 14, 28, 42, 53, and 71 μ M PD, either in its free form or adsorbed onto kaolinite clay particles (referred to as DKG coagulant). The coagulants were added to 250 ml cyanobacteria suspensions. After the addition, the suspensions were stirred thoroughly for 1 min and left to settle for 1 h.

The second coagulation experiment was performed on cowshed effluents. The wastewater was taken from Kfar Blum industrial cowshed (Upper Galilee, Israel) during July 2023. To determine the required amount of coagulant needed for neutralization [39] the electrokinetic colloidal charge of the wastewater was measured in a particle charge detector (PCD) (BTG Mütek, PCD-05, Eclépens, Switzerland). Three poly-DADMAC-based coagulants were tested: commercial PD, kaolinite-PD nanocomposite (DKG), and sepiolite-PD nanocomposite (NC). The doses were equivalent to 100% of the requirement to neutralize the colloids (4.3 mM charges). Each experiment was conducted in 300 ml glass beakers, with each treatment having 3 replicates. After the addition, the suspensions were thoroughly stirred for 1 min and allowed to settle for 1 h.

In both experiments, turbidity was measured with a LaMotte 2020i turbidimeter before and after the treatment to estimate the efficiency of clarification and coagulation. The residual PD concentrations were quantified using the complexation method as described in section 2.2. Specifically, 10 ml of the supernatant was sampled, and the pH values were adjusted to 3–3.5 by adding 20 μ l of 1 mM HCl. Subsequently, suitable volumes of FG from a 1000 μ M stock solution were added to each sample, yielding FG concentration of 20 μ M. Test tubes were placed on an orbital shaker (200 rpm) for 1 h, and samples were measured in the spectrophotometer as described in section 2.2.

3. Results

3.1. Quantification of analytical poly-DADMAC concentrations

As mentioned in section 2.2., three separate calibration experiments were conducted to quantify PD at different concentration levels: low, medium, and high. Each range included addition of different FG concentrations. The quantification method is based on the measurement of free fast-green molecules in the solution, according to its distinct absorption bands at wavelengths 420 and 624 nm. Figure 2 shows the measured absorbance values in specific wavelengths as a function of the known PD concentrations. To increase sensitivity at the medium and low PD range, the selected wavelength was 624 nm. To avoid the need for dilutions at the high range the 420 nm (with lower molar absorptivity) was selected. Linear regression calculations between absorbance and PD concentrations were performed for all three ranges (see Figure 2), showing excellent correlations ($R^2 > 0.982$) in the high and medium ranges (1–200 μ M, 0.1617–32.4 mg L⁻¹). According to the results, as PD concentration increases, absorbance values decrease, indicating the formation of a PD-fast green complex that reduces available fast green molecules in the solution. This inverse relationship between dye absorbance and PD concentration serves as the foundation for quantitatively analyzing PD through complexation with the FG dye, similar to the effect observed in the chitosan

quantification method [32]. The relatively low R^2 ($R^2=0.866$) in the 0.02-1 μM PD range is attributed to increased measurement noise and experimental variability at these low concentrations. The lower PD concentration used for the calibration experiment was determined as the detection limit of the method (0.02 μM).

As a confirmation step, the necessity of removing the PD-fast green complex from the solution by centrifugation was tested. The samples underwent centrifugation at 3000 rpm for 20 minutes, followed by spectrophotometer measurements. According to the results, centrifugation of the mixture solution after complexation did not affect the absorbance values (data not shown).




Figure 2. Absorbance values as a function of poly-DADMAC concentrations after complexation with fast green. (a) High PD range, OD₄₂₀ nm of 10-200 μM PD upon addition of 100 μM FG. (b) Medium PD range, OD₆₂₄ of 1-30 μM PD upon addition of 20 μM FG. (c) Low PD range, OD₆₂₄ of 0.02-1 μM PD upon addition of 0.8 μM FG. High and medium range were measured in a 1 cm cuvette, whereas low range- in 5 cm cuvette.

3.2. FTIR measurements of PD-FG complexes

Figure 3 shows the FTIR spectra of dried PD, FG, and sediments of samples with 20 μM FG complexed with 2.5 and 50 μM PD. The raw PD spectrum shows a distinct absorption band at 1464 cm^{-1} , attributed to quaternary ammonium bound to chloride anions [40]. Additionally, a broad peak associated with aliphatic secondary amines at 3100-3600 cm^{-1} [26] and bands related to C-H stretching vibrations of methine, methylene and methyl groups [41] at 3000-2800 cm^{-1} can be clearly observed. The raw FG dye spectrum exhibits a series of absorption bands related to aromatic structures and sulfonate vibrations [41] at 1340 and 1170 cm^{-1} . In both the FG-2.5 μM PD and FG-50 μM PD complexes, the vibrations associated with quaternary ammonium bound to chloride anions completely disappear, suggesting that the complexation occurs through the exchange of chloride ions with the anionic dye. The spectra also display distinct bands corresponding to the C-H and secondary amine groups of PD, along with aromatic and sulfonate bands from FG. These observations confirm the formation of the dye-coagulant complex. Similar spectra were recorded for all FG-PD complexes (results not shown).




Figure 3. FTIR spectra of dried polyDADMAC (PD, red line), raw fast green (FG, green line), sedimented complexes formed by 2.5 (PD 2.5 FG 20, blue line) and 50 μ M PD (PD 50 FG 20, purple line). Note that x-axis is split at 2000 cm^{-1} .

3.3. Influence of pH

Given that the accuracy of spectroscopy measurements relies on the stability of the spectrum, we conducted experiments to assess the impact of pH on FG spectra. Absorbance spectrum of FG was measured at different pH values ranging from 2 to 9.1 (Figure 4). The results indicate that within the pH range of 2 to 7, the spectrum of FG remained constant, with no changes in the molar absorptivity at any wavelength. This suggests that there were no significant alterations in the chromophore within this acidic to neutral pH range. However, as the pH increased above 7, the spectrum deviated from the constant trend observed in the acidic to neutral pH range. The large absorption band at 624 nm shifted hypsochromically (to lower wavelengths), and molar absorptivity slightly increased, while the absorption band at 420 nm disappeared. These findings are crucial to determine the pH requirements and limitations relevant when applying the quantification method presented hereby and highlight the importance of pH control to a range of 2-7 during the analysis process. In our study, the pH of all samples was adjusted to a range of 3-3.5 by adding very small volumes of HCl before measuring the spectrum





Figure 4. UV-Vis spectra of a 10 μ M FG solutions at different pH values (2.24-9.13).

3.4. Quantification of commercial poly-DADMAC

Complexation experiments were conducted with commercial PD in a range of 1-50 μ M polymer concentrations, with the addition of 20 μ M FG according to the medium range presented in section 3.1. Figure 5 shows absorbance of the remaining dye as a function of commercial PD concentrations, after the formation of the complexes at 420 (Figure 5a) and 624 nm (Figure 5b). To prevent any potential shift in the spectrum due to high pH, all samples were acidified with 20 μ l of 1mM HCl, as outlined in section 3.3. Full spectra of commercial PD samples after complexation with FG is shown in Figure S2 in the Supplementary Material. To verify the similarity of the measured spectra to that of FG, Pearson's correlation of all spectra with FG in the 300-800 range nm was evaluated using CORREL function in Excel®, yielding $R>0.993$.

Consistent linear relationships between absorbance and PD concentration were observed at both wavelengths ($R^2 = 0.9992$ for 420 nm and $R^2 = 0.9986$ for 624 nm), indicating a strong and reliable correlation, as illustrated in Figure 2 for analytical PD. It is noteworthy that examination of the linear regression equations in Figures 2b and 4b, a pronounced similarity emerges, both in terms of the intercept and slope values. Furthermore, the slope in Figure 2a and 5a are identical, although intercept differs due to levels of FG concentrations. These findings highlight the applicability of the complexation method in quantifying commercial PD concentrations.

**Figure 5.** Absorbance values at (a) 420nm and (b) 624nm, as a function of PD concentrations (1-50 μ M) after complexation with 20 μ M FG.

3.5. Quantification of poly-DADMAC in coagulation treatment samples

The method's applicability in practical field conditions was assessed by determining residual PD concentrations in cyanobacteria-contaminated water and cowshed effluents during coagulation and clarification treatments..

The cyanobacteria water samples were treated with commercial PD and kaolinite-PD nanocomposites (DKG). As mentioned in section 2.5, coagulants were added in amounts equivalent to the following PD concentrations: 14, 28, 42, 53, and 71 μ M (either in free form or adsorbed onto kaolinite clay particles). The initial turbidity value for the cyanobacteria suspension was 98.2 ± 3.67 NTU. Following the coagulant addition as detailed in section 2.5, 10 ml test tubes were used to sample the supernatants. These samples were then acidified, and concentrated FG solution was added, resulting in an FG concentration of 20 μ M. The absorbance was measured at 420 nm, and the residual PD concentration was determined using the calibration curve established in the previous section (Figure 5). Residual PD concentrations and turbidity values are shown in Figure 6. Based on the measured results, minimal turbidity is observed across the entire range of added PD-kaolinite, even up to 53 μ M of commercial PD. Additionally, there is a substantial clear phase, accounting for

approximately 90% of the volume, at the top of the vessels. However, increasing residual PD is clearly observed as the added amounts of coagulant increase. Furthermore, significant differences between the remaining PD concentrations were observed between the two coagulants, with lowest amounts of 1.9 and 4.1 μM for the nanocomposites and commercial PD, respectively. The lower residual PD values observed in the DKG samples are likely attributed to the PD binding to the kaolinite clay particles and the higher density of these clays. This, in turn, leads to the enhanced precipitation of excess coagulant materials. As the coagulant concentrations increased, no significant changes were observed in the turbidity values. However, higher turbidity was observed in the addition of 71 μM commercial PD indicating coagulant over-dose that disrupts the neutralization of the colloidal charge of the suspension [39].




Figure 6. Evaluated PD residual concentrations (bars) and measured turbidity (lines and dots) in cyanobacteria polluted water at different added PD doses, using commercial PD (blue, triangles) or kaolinite-PD nanocomposite (orange, circles).

As an additional test for the method, we conducted clarification and coagulation experiments using cowshed effluents. Such effluents are heavily polluted with total suspended solid (TSS) values that may reach 10 g L^{-1} , and turbidity $>4000 \text{ NTU}$ [42]. TSS removal is required as pretreatment, since wastewater treatment plants limit the maximum inflow value to $<0.4 \text{ g L}^{-1}$ [43]. In the samples collected at the Kfar Blum cowshed during July 2023, the initial turbidity of the effluents was $3355 \pm 226 \text{ NTU}$. Optimal coagulant doses were determined by measuring the colloidal particle charge as described in section 2.5. Following the coagulation process, turbidity decreased to 1.2-4.5% of the initial values (77, 152, and 43 NTU in the kaolinite-PD, sepiolite-PD, and commercial PD coagulant treatments, respectively). The figure below presents the residual PD concentrations in the three treatments (Figure 7). As in the cyanobacteria-polluted effluents, residual PD was considerably lower in the clay-PD coagulants ($\sim 25 \mu\text{M} = \sim 4.04 \text{ mg L}^{-1}$) than in the commercial PD ($37 \mu\text{M} = 5.98 \text{ mg L}^{-1}$), probably due to the high density of the clays and precipitation of excess coagulants.

Normalized spectra of cyanobacteria and cowshed water samples after treatment compared to spectrum of FG with commercial PD in clear water is presented in Figure S3 of the Supplementary Material. FG spectrum in cyanobacteria sample is almost identical to clear water (Pearson's correlation in the range 300-800 nm = 0.999). On the other hand, FG in the cowshed effluents differs from that in clear water (Pearson's correlation = 0.938) due to the presence of remaining color and turbidity. However, limiting the range to 600-800 nm increases Pearson's correlation to 0.977, indicating that differences do not interfere with the measurement of absorbance at 624 nm.

The results of both demonstration experiments highlight the method's applicability in real conditions, offering vital insights into optimal coagulation treatments in a convenient, cost-effective

manner. It should be mentioned that the removal of residual PD concentration from post-coagulation wastewater is essential for the prevention of extensive membrane fouling and negative environmental impact. Several studies examined different approaches in order to reduce the negative impact of PD by inhibiting the formation of carcinogenic by-products [19,44], but additional studies are required to examine possible complete removal techniques such as adsorption and ion exchange. Nevertheless, the first step to approach the problem is to improve the monitoring ability of PD in wastewater plant facilities.




Figure 7. Calculated residual PD in cowshed effluent coagulation experiments with commercial PD (blue), kaolinite-PD nanocomposites-DKG (orange), and sepiolite-PD nanocomposites- NC (grey).

4. Conclusions

- In this study, a colorimetric quantification method for poly-DADMAC through complexation with fast green dye was developed and evaluated.
- The method exhibited high sensitivity with a detection limit of $0.02 \mu\text{M}$ (0.0032 mg L^{-1}), meeting regulatory demands according to the world standard limitations.
- Quantification experiments of analytical PD concentrations including low, medium, and high ranges demonstrated a linear correlation between the absorbance and PD concentrations.
- The influence of pH on the quantification process was tested, revealing that the absorbance spectrum of FG remains unchanged within the pH range of 2 to 7, exhibiting an hypsochromic and hyperchromic shift at higher pH. Therefore, an acidification step (or accurate pH measurements) is essential before quantification to ensure the FG spectrum falls within the required range.
- The quantification method's feasibility was demonstrated in coagulation experiments, estimating remaining PD concentrations in treated water samples.
- The method's feasibility in estimating PD concentrations under actual coagulation conditions highlights its potential for efficient monitoring and control of coagulation processes. It offers a rapid, cost-effective, and sensitive tool for accurate PD concentration measurement. The colorimetric PD quantification holds promising potential for advancing water treatment systems and quality control.
- Further research may concentrate on upscaling the application of the quantification method for large-scale water treatment systems, as well as refining its adaptation and addressing limitations. This may include examining factors such as temperature, reaction time, and ionic strength.

Supplementary Materials: The following supporting information can be downloaded at the website of this paper posted on Preprints.org. Figure S1: Scheme of the experimental setup. Figure S2: Spectra of an initial $20 \mu\text{M}$ FG upon complexation with the increasing concentrations of commercial PD; Figure S3: Normalized spectra

of an initial 20 μM FG upon complexation with commercial PD in distilled water, cyanobacteria polluted water and cowshed effluents.

Author Contributions: Conceptualization, G.R.; methodology, G.R., I.L., B.C. and I.M.; software, I.L. and Y.K.; validation, G.R., I.L., and Y.K.; formal analysis, I.L.; investigation, G.R., I.L., B.C. and I.M.; resources, G.R.; data curation, I.L. and G.R.; writing—original draft preparation, G.R., I.L., and B.C.; writing—review and editing, I.L. and G.R.; visualization, I.L. and Y.K.; supervision, G.R.; project administration, G.R.; funding acquisition, G.R. All authors (except I.M. that deceased) have read and agreed to the published version of the manuscript.

Funding: This research was partially funded by CSO-MOH (Israeli Ministry of Health), in the frame of the collaborative international consortium (REWA) financed under the 2020 AquaticPollutants Joint call of the AquaticPollutants ERA-NET Cofund (GA N° 869178).

Data Availability Statement: All raw data are available from the authors.

Acknowledgments: We would like to dedicate this manuscript to the memory of the late Ido Maor. The authors would like to thank the European Commission and AKA (Finland), CSO-MOH (Israel), IFD (Denmark) and WRC (South Africa) for funding in the frame REWA international consortium (additional details in “funding” paragraph). REWA is an integral part of the activities developed by the Water, Oceans and AMR JPIs. The authors are also thankful to the Mr. Yehezkel Zwecher for growing the cyanobacteria suspension, Ms. Simmah Hendrickson for the English editing, and the whole team of the Hydrogeology and Examination of Soil Fertility Lab at MIGAL Research Institute.

Conflicts of Interest: The authors declare no conflict of interest.

Abbreviation list

- PD poly-dadmac (Poly-diallyl-dimethylammonium chloride)
- FG Fast-green
- LOD limit of detection
- DKG kaolinite-PD nanocomposites
- NC sepiolite- PD nanocomposites
- PCD particle charge detector
- NTU nephelometric turbidity unit
- TSS total suspended solids

References

1. Amuda, O.S.; Amoo, I.A. Coagulation/flocculation process and sludge conditioning in beverage industrial wastewater treatment. *J. Hazard. Mater.* **2007**, *141*, 778–783.
2. Dautzenberg, H.; Görnitz, E.; Jaeger, W. Synthesis and characterization of poly(diallyldimethylammonium chloride) in a broad range of molecular weight. *Macromol. Chem. Phys.* **1998**, *199*, 1561–1571.
3. Becker, N.S.; Bennett, D.; Bolto, B.; Dixon, D.; Eldridge, R.; Le, N.; Rye, C.. Detection of polyelectrolytes at trace levels in water by fluorescent tagging. *React. Funct. Polym.* **2004**, *60*, 183–193.
4. Razali, M.A.A.; Ahmad, Z.; Ahmad, M.S.B.; Ariffin, A. Treatment of pulp and paper mill wastewater with various molecular weight of polyDADMAC induced flocculation. *Chem. Eng. J.* **2011**, *166*, 529–535.
5. Ariffin, A.; Razali, M.A.A.; Ahmad, Z. PolyDADMAC and polyacrylamide as a hybrid flocculation system in the treatment of pulp and paper mills waste water. *Chem. Eng. J.* **2012**, *179*, 107–111.
6. Hamad, M.J.A.; Chirwa, E.M.N. Forward osmosis for water recovery using polyelectrolyte PolyDADMAC and DADMAC draw solutions as a low pressure energy saving process. *Desalination* **2019**, *453*, 89–101.
7. Sampl, C.; Schaubeder, J.; Hirn, U.; Spirk, S. Interplay of electrolyte concentration and molecular weight of polyDADMAC on cellulose surface adsorption. *Int. J. Biol. Macromol.* **2023**, *239*, 124286.
8. Ramos, P.; Singh Kalra, S.; Johnson, N.W.; Khor, C.M.; Borthakur, A.; Cranmer, B.; Dooley, G.; Mohanty, S.K.; Jassby, D.; Blotevogel, J.; et al. Enhanced removal of per- and polyfluoroalkyl substances in complex matrices by polyDADMAC-coated regenerable granular activated carbon. *Environ. Pollut.* **2022**, *294*, 118603.
9. Bhuyan, C.; Konwar, A.; Bora, P.; Rajguru, P.; Hazarika, S. Cellulose nanofiber-poly(ethylene terephthalate) nanocomposite membrane from waste materials for treatment of petroleum industry wastewater. *J. Hazard. Mater.* **2023**, *442*, 129955.

10. Gogoi, M.; Goswami, R.; Borah, A.; Sarmah, H.; Rajguru, P.; Hazarika, S. Amide functionalized DWCNT nanocomposite membranes for chiral separation of the racemic DOPA. *Sep. Purif. Technol.* **2021**, *279*, 119704.
11. Gabelich, C.J.; Ishida, K.P.; Bold, R.M. Testing of water treatment copolymers for compatibility with polyamide reverse osmosis membranes. *Environ. Prog.* **2005**, *24*, 410–416.
12. Wang, S.; Liu, C.; Li, Q. Fouling of microfiltration membranes by organic polymer coagulants and flocculants: Controlling factors and mechanisms. *Water Res.* **2011**, *45*, 357–365.
13. Zhang, B.; Tang, H.; Shen, Y.; Liu, G.; Shi, W. Comparative analysis of membrane fouling mechanisms induced by colloidal polymer: Effects of sodium and calcium ions. *J. Colloid Interface Sci.* **2022**, *608*, 780–791.
14. Guo, W.; Ngo, H.H.; Li, J. A mini-review on membrane fouling. *Bioresour. Technol.* **2012**, *122*, 27–34.
15. Uzun, H.; Kim, D.; Karanfil, T. Removal of wastewater and polymer derived N-nitrosodimethylamine precursors with integrated use of chlorine and chlorine dioxide. *Chemosphere* **2019**, *216*, 224–233.
16. Park, S.H.; Padhye, L.P.; Wang, P.; Cho, M.; Kim, J.-H.; Huang, C.-H. N-nitrosodimethylamine (NDMA) formation potential of amine-based water treatment polymers: Effects of in situ chloramination, breakpoint chlorination, and pre-oxidation. *J. Hazard. Mater.* **2015**, *282*, 133–140.
17. Park, S.H.; Wei, S.; Mizaikoff, B.; Taylor, A.E.; Favero, C.; Huang, C.H. Degradation of amine-based water treatment polymers during chloramination as N-nitrosodimethylamine (NDMA) precursors. *Environ. Sci. Technol.* **2009**, *43*, 1360–1366.
18. Huang, C.H.; Padhye, L.P.; Park, S.H. PolyDADMAC and dimethylamine as precursors of N-nitrosodimethylamine during ozonation. *Water Qual. Technol. Conf. Expo.* **2011**, *2011*, 2304–2315.
19. Atkinson, A.J.; Fischer, N.; Donovan, S.; Bartlett, J.; Alrehaili, O.; Sinha, S.; Kommineni, S.; Herckes, P.; Westerhoff, P. Purification and removal of the low molecular weight fraction of polyDADMAC reduces N-nitrosodimethylamine formation during water treatment. *Environ. Sci. Water Res. Technol.* **2020**, *6*, 2492–2498.
20. T Manickum Occurrence, Fate and Preliminary Environmental Risk Assessment of Residual Poly-Diallyldimethyl Ammonium Chloride, and Some Disinfection By-Products, in Treated (Potable), and Environmental, Waters in the Umgeni Water Catchment in Kwazulu-Natal. *SM J. Public Heal. Epidemiol.* **2017**, *3*.
21. Al Momani, F.A.; Örmeci, B. Measurement of polyacrylamide polymers in water and wastewater using an in-line UV-vis spectrophotometer. *J. Environ. Chem. Eng.* **2014**, *2*, 765–772.
22. Di Gaudio, F.; Barreca, S.; Orecchio, S. Diallyldimethylammonium Chloride (DADMAC) in Water Treated with Poly-Diallyldimethylammonium Chloride (PDADMAC) by Reversed-Phase Ion-Pair Chromatography—Electrospray Ionization Mass Spectrometry. *Separations* **2023**, *10*, 311.
23. John, W. Synthesis, properties and analysis of polydadmac for water purification. **2008**.
24. Mwangi, I.W.; Ngila, J.C.; Ndungu, P.; Msagati, T.A.M. Method Development for the Determination of Diallyldimethylammonium Chloride at Trace Levels by Epoxidation Process. *Water, Air, Soil Pollut.* **2013**, *224*, 1638.
25. Mwangi, I.W.; Catherine Ngila, J.; Ndungu, P.; Msagati, T. Preconcentration and spectrophotometric determination of polyDADMAC in treated water by in situ co-precipitation with naphthalene. *Phys. Chem. Earth, Parts A/B/C* **2014**, *72–75*, 54–60.
26. Mwangi, I.; Ngila, J.; Ndungu, P. A new spectrophotometric method for determination of residual polydiallyldimethylammonium chloride flocculant in treated water based on a diazotization-coupled ion pair. *Water SA* **2012**, *38*, 707–714.
27. Gumbi, B.; Ngila, J.C.; Ndungu, P.G. Gold nanoparticles for the quantification of very low levels of poly-diallyldimethylammonium chloride in river water. *Anal. Methods* **2014**, *6*, 6963.
28. Manickum, T.; John, W.; Toolsee, N.; Rajagopaul, R. Preliminary Performance Evaluation of the Gold Nanoparticle Method for Quantification of Residual Poly-(Diallyldimethyl Ammonium Chloride) in Treated Waters in the Umgeni Water Catchment, Kwazulu-Natal (South Africa). *Hydrol. Curr. Res.* **2015**, *06*.
29. Magubane, S.E.; Ntlhoro, S.; Sabela, M.; Kanchi, S.; Mlambo, M.; Onwubu, S.C.; Mdluli, P.S.; Inamuddin; Asiri, A.M. Novel on-site residual screening of poly-diallyldimethylammonium chloride in treated potable water using gold nanoparticle based lovibond color filters. *J. Taiwan Inst. Chem. Eng.* **2019**, *101*, 159–166.
30. Majam, S.; Thompson, P.A. Polyelectrolyte determination in drinking water. *Water SA* **2006**, *32*, 705–707.
31. Thilak Kumar, R.; Umamaheswari, S. FTIR, FTR and UV-Vis analysis of carbamazepine. *Res. J. Pharm. Biol. Chem. Sci.* **2011**, *2*, 685–693.

32. Mendelovits, A.; Prat, T.; Gonen, Y.; Rytwo, G. Improved colorimetric determination of chitosan concentrations by dye binding. *Appl. Spectrosc.* **2012**, *66*, 979–982.
33. Venkatesh, N.; Murugadoss, G.; Mohamed, A.A.A.; Kumar, M.R.; Peera, S.G.; Sakthivel, P. A Novel Nanocomposite Based on Triazine Based Covalent Organic Polymer Blended with Porous $\text{g-C}_3\text{N}_4$ for Photo Catalytic Dye Degradation of Rose Bengal and Fast Green. *Molecules* **2022**, *27*.
34. Rytwo, G.; Lavi, R.; Rytwo, Y.; Monchase, H.; Dultz, S.; König, T.N. Clarification of olive mill and winery wastewater by means of clay-polymer nanocomposites. *Sci. Total Environ.* **2013**, *442*, 134–142.
35. Rytwo, G. The Use of Clay-Polymer Nanocomposites in Wastewater Pretreatment. *Sci. World J.* **2012**, *2012*, 1–7.
36. Rytwo, G. Hybrid Clay-Polymer Nanocomposites for the Clarification of Water and Effluents. *Recent Pat. Nanotechnol.* **2017**, *11*, 181–193.
37. Rytwo, G. US20190152813 Method for production of potable water 2019.
38. Sukenik, A.; Beardall, J.; Hadas, O. Photosynthetic characterization of developing and mature akinetes of *Aphanizomenon ovalisporum* (Cyanoprokaryota). *J. Phycol.* **2007**, *43*, 780–788.
39. Rytwo, G.; Lavi, R.; König, T.N.; Avidan, L. Direct Relationship Between Electrokinetic Surface-charge Measurement of Effluents and Coagulant Type and Dose. *Colloids Interface Sci. Commun.* **2014**, *1*, 27–30.
40. Kozak, M.; Domka, L. Adsorption of the quaternary ammonium salts on montmorillonite. *J. Phys. Chem. Solids* **2004**, *65*, 441–445.
41. Coates, J. Interpretation of infrared spectra, a practical approach. In *Encyclopaedia of Analytical Chemistry*; Meyers, R.A., Ed.; John Wiley & Sons Ltd.: Chichester, UK, 2000; pp. 10815–10837.
42. Rytwo, G.; Malka, H. A pilot plant for the treatment of cowshed effluents. *Water Irrig.* **2013**, *530*, 6–9.
43. Inbar, Y. New Standards for Treated Wastewater Reuse in Israel. In Proceedings of the Wastewater Reuse-Risk Assessment, Decision-Making and Environmental Security; Zaidi, M.K., Ed.; Springer Netherlands: Dordrecht, 2007; pp. 291–296.
44. Zeng, T.; Li, R.J.; Mitch, W.A. Structural Modifications to Quaternary Ammonium Polymer Coagulants to Inhibit N-Nitrosamine Formation. *Environ. Sci. Technol.* **2016**, *50*, 4778–4787.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.