

Article

Not peer-reviewed version

Hydrogen Gas Compression for Efficient Storage: Balancing Energy and Density

[Alessandro Franco](#) * and [Caterina Giovannini](#)

Posted Date: 25 April 2024

doi: 10.20944/preprints202402.1220.v2

Keywords: Hydrogen storage; Gaseous Compression; Multi-Stage Configuration; Energy analysis; Efficiency



Preprints.org is a free multidiscipline platform providing preprint service that is dedicated to making early versions of research outputs permanently available and citable. Preprints posted at Preprints.org appear in Web of Science, Crossref, Google Scholar, Scilit, Europe PMC.

Copyright: This is an open access article distributed under the Creative Commons Attribution License which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Article

Hydrogen Gas Compression for Efficient Storage: Balancing Energy and Increasing Density

Alessandro Franco * and Caterina Giovannini

Department of Energy, Systems, Territory and Constructions Engineering, University of Pisa, Largo Lucio Lazzarino 56126 PISA, ITALY; caterina.giovannini@phd.unipi.it

* Correspondence: alessandro.franco@ing.unipi.it

Abstract: The article analyzes the processes of compressing hydrogen in the gaseous state, an aspect considered important to contribute to a greater diffusion of hydrogen in both the civil and industrial sectors. The study initiates by providing a concise overview and comparison of diverse hydrogen storage methodologies, laying the groundwork with an in-depth analysis of hydrogen's thermophysical properties. It scrutinizes plausible configurations for hydrogen compression, aiming to strike a delicate balance between energy consumption, derived from the fuel itself, and the requisite number of compression stages. Notably, to render hydrogen storage competitive in terms of volume, pressures of at least 350 bar are deemed essential, albeit at an energy cost amounting to approximately 10% of the fuel's calorific value. Multi-stage compression emerges as a crucial strategy, not solely for energy efficiency, but also to curtail temperature rise, with an upper limit set at 200°C. This nuanced approach is underlined by the exploration of compression levels commonly cited in the literature, particularly 350 bar and 700 bar. The study advocates for a three-stage compression system as a pragmatic compromise, capable of achieving high-pressure solutions while keeping compression work below 10 MJ/kg, a threshold indicative of sustainable energy utilization.

Keywords: hydrogen storage; gaseous compression; multi-stage configuration; energy analysis; efficiency

1. Introduction

Hydrogen, as widely acknowledged, serves as a crucial energy carrier, and its role in the energy transition is intricately tied to the ability to store energy harnessed from renewable sources. There is significant emphasis on hydrogen and its relevance. However, the prevailing perception is that the debate tends to be overly general, initially encompassing broad elements while potentially overlooking some crucial technical aspects, [1]. The discussion about hydrogen has been ongoing for over 40 years, yet the lack of compelling solutions for widespread applications is still tied to certain technical aspects related to materials and intrinsic challenges of hydrogen. Additionally, it is important to clarify that hydrogen is a carrier and as such needs to be integrated into an energy chain where energy balances must be respected, and the overall process efficiency must be high. The recent interest in hydrogen is primarily associated with its potential integration with the increasing penetration of renewable energy in energy systems. As outlined in Figure 1, illustrating how hydrogen can be integrated into a system, hydrogen, providing an additional opportunity to further incorporate renewable sources, especially intermittent ones like wind and PhotoVoltaic (PV) solar. Figure 1 illustrates in a quite simplified way the potential integration of hydrogen in a specific industrial context (for example an industry in the steel sector), highlighting the significance of energy storage as well. The significance of hydrogen lies in its potential to facilitate load leveling in systems anticipating an escalating integration of intermittent or non-programmable renewable sources.




Figure 1. Potential role of hydrogen storage in an industrial process.

Hence, it becomes imperative to address hydrogen storage in a comprehensive manner. Despite hydrogen's high specific energy per unit mass, 120 MJ/kg as Lower Heating Value (LHV), its low energy density per unit volume (about 10 MJ/m³) presents a challenge for achieving compact, cost-effective, and secure energy-dense storage solutions. The subject of hydrogen storage has been under scrutiny for an extended period, leading to the proposition of various storage methods at different junctures. However, determining an outright superiority among these methods remains elusive. Various storage methods exist, each with its own advantages and drawbacks, considering both cost and performance factors that depend on specific application requirements, [2].

Currently, there is not an ideal storage technology for most applications. Storage methods fall into two categories: physical storage, where elemental hydrogen is stored, and materials-based storage, where hydrogen is bound within other materials. Under a distinct perspective Hydrogen can be stored through three fundamental methods: Compressed Hydrogen Gas (CGH₂), Liquid Hydrogen (LH₂), and Solid Storage of Hydrogen (SSH₂). The latter, involving modification of hydrogen's physical state, [3].

Some recent papers cover a spectrum of hydrogen storage technologies, providing insights into their status, advancements, and the potential implications for a sustainable energy future. Arsad et al. (2022), in [4] explores the integration of hydrogen energy storage within hybrid renewable energy systems. The review provides a comprehensive analysis of current research trends and discusses future directions for this field. Wieliczko and Stetson in [5], emphasizes the importance of hydrogen as an energy carrier and discusses various technologies in this context. Usman in [6], presents a thorough review of hydrogen storage methods and their status. The paper shows strengths and limitations of different storage approaches. Hassan et al. in [7] contributes to the discourse on the hydrogen energy future by focusing on advancements in storage technologies and their implications for sustainability. Muthukumar, et al. in [8] review the worldwide developmental status of large-scale hydrogen storage using various technologies such as compressed, cryogenic, ammonia, liquid organic hydrogen carriers, and solid-state hydrogen storage.

In the literature it is possible to find mention to electrochemical compression too. This is a promising method that utilizes electrochemical reactions to compress hydrogen gas, that typically involves the use of proton exchange membrane (PEM) cells.

A theoretical advantage of electrochemical compression is its ability to achieve high compression ratios with low energy consumption compared to mechanical compression methods even if research in this area is ongoing. Despite electrochemical hydrogen compression being a promising field in theory, it is currently particularly challenging to consider it as a technology that could be available within a reasonable period.

Considering the more “conventional” methods, from the literature analysis, the conclusion drawn is that while each avenue can be considered, they all come with their own potentials and limitations, suggesting adaptability to specific contexts, [9].

Liquid storage of hydrogen is first highly energy-intensive due to the energy requirements associated with the liquefaction process. The process of converting gaseous hydrogen into liquid hydrogen involves cooling the gas to extremely low temperatures, typically below -240°C (in general -253°C). Moreover, storing hydrogen in a liquid phase demands the maintenance of extremely low temperatures (hydrogen transitions to a liquid state at 20 K under atmospheric pressure). The storage of hydrogen in liquid form demands considerable energy and technologically advanced transportation infrastructure, making it suitable for transporting massive quantities of hydrogen over long distances but less feasible for smaller-scale solutions. The storage and transportation of liquid hydrogen demand specialized and well-insulated containers to maintain the low temperatures required. This adds to the complexity and cost of the infrastructure. The complexity of the infrastructure is not offset by a significant increase in hydrogen density, considering that at 1 bar and -253°C it is about 70 kg/m^3 .

When considering liquefied natural gas as a comparison, operating at a temperature of -162°C , methane density is approximately 420 kg/m^3 , around 6 times higher than that of hydrogen. Consequently, from an energy standpoint, for an equal volume of the vessel, less than half the energy is transported, resulting in a ratio of approximately 5/2.

This energy requirement makes the overall hydrogen compression process less energy-efficient, as well outlined in the paper by Zhang et al., [10].

The challenges and energy costs associated with its compression, liquefaction, and storage make alternative compression methods, such as gaseous compression or solid-state storage, more attractive in certain applications.

Hydrogen storage through metal hydrides, holds conceptual promise but introduces additional challenges related to material stability, rendering its practical use complex.

In general, the choice of storage method depends on several factors such as application, scale, infrastructure, and geographical considerations. For example, while high-pressure storage might be suitable for stationary applications with existing infrastructure, solid-state storage could be more advantageous for mobile applications due to its potentially higher energy density and safety.

High-density storage methods such as liquefaction or high-pressure compression can require significant energy input for both storage and transportation. This energy input must be considered when evaluating the overall efficiency and sustainability of hydrogen as an energy carrier. Recent developments and the anticipated widespread utilization of hydrogen suggest that, for several reasons, gaseous compression remains the most promising, especially for medium and small-scale applications [2]. Various technologies are employed for hydrogen compression, each with its own advantages and limitations. Some common hydrogen compression technologies include piston compressors, diaphragm compressors, used for small and small to medium scale application and screw compressors, which use rotating screws to compress hydrogen, as evidenced by Sdanghi et al. in [11]. In the literature, the topic of compressing hydrogen in gaseous form has been extensively explored (Zheng et al., [12]). A paper from Barthelemy, [13], provides a historical and technical overview of hydrogen storage vessels and discusses the challenges and constraints of hydrogen energy applications. It explores the storage of hydrogen as a compressed or refrigerated liquefied gas, detailing the evolution of storage methods from seamless steel cylinders to aluminum cylinders and hoop-wrapped metallic cylinders. The development of fully wrapped composite tanks for high-pressure hydrogen storage is examined, along with the specific issues associated with these technologies. An interesting and synthetic analysis on the hydrogen compression in gaseous form is provided in [14]. Recent advancements in hydrogen compression technology focus on improving efficiency, reducing energy consumption, and enhancing safety. Research efforts also aim to address challenges such as material compatibility, system reliability, and cost-effectiveness. Among the others, mechanical compression is a widely used method for compressing hydrogen gas to higher pressures. This process typically involves the use of mechanical devices such as piston compressors,

diaphragm compressors, or screw compressors. In a piston compressor, hydrogen gas is drawn into a cylinder and compressed by a piston moving in a reciprocating motion.

Performance in hydrogen compression is evaluated based on factors such as energy efficiency, compression ratio, and safety. Achieving high compression ratios is crucial for storage and transportation applications. However, it is essential to balance this with energy efficiency to minimize energy consumption. The prevalent choices is orientend to consider two pressure levels (350 bar or 700 bar), but a criterion for defining an optimal compromise among various process parameters is lacking. Research and development efforts continue to improve the efficiency and economics of hydrogen compression technologies. Innovations aim to address challenges such as heat management during compression to enhance overall performance. However, it is crucial to note that even with the widespread adoption of gaseous compression, the limited density of hydrogen at ambient conditions requires pushing towards high pressures, typically exceeding 300 bar. The application of higher pressures brings thermodynamic advantages. An analysis of hydrogen's thermophysical properties reveals that, at environmental temperature and 500 bar pressure, the hydrogen density is around 30 kg/m^3 —approximately 300 times higher than ambient conditions. The density further increases to about 50 kg/m^3 under compression at 1000 bar. Nevertheless, the use of extremely high pressures introduces a myriad of challenges, necessitating the use of specialized materials with significant structural strength, resistance to embrittlement, and incurring a more substantial energy expenditure to meet specific requirements. This energy expenditure adds to a host of other factors, often rendering the hydrogen energy chain inefficient.

In addition to energy costs associated with the electrolysis phase, the substantial energy consumption during compression and end-use poses a risk of substantial reductions in overall process efficiencies. Despite the extensive history of dealing with hydrogen compression in gaseous form, identifying literature addressing the establishment of reasonable targets that strike a balance between various elements (compression work, storage system dimensions, physical characteristics, and associated costs) proves challenging. Hence, this work, following an in-depth analysis of the current state of gaseous hydrogen storage methods, aims to outline criteria utilizing a multi-objective optimization approach, seeking to define optimized storage systems tailored to specific applications.

The study analyzes the compression of hydrogen in gaseous form, aiming identify technological objectives with medium-term potential. It addresses material-related challenges, such as maximum temperature limits, and explores feasible technological solutions. Energy requirements and technological objectives are mainly evaluated considering that compressing H_2 to high pressures, results in an important loss of its heating value, which has an impact on the overall operation.

The paper is motivated by the fact that a comprehensive understanding of the storage phase, along with its associated energy requirements and density considerations, is crucial for the successful integration of hydrogen into energy systems. This understanding will enable policymakers, researchers, and industry stakeholders to make informed decisions regarding the development and deployment of hydrogen technologies.

The paper is organized as follows. Section 2 discuss the key thermophysical properties of hydrogen relevant to compression and outline the storage requirements for gaseous hydrogen; section 3 gives a concise review existing technological solutions for compressing gaseous hydrogen, examining their advantages and limitations. Section 4 presents a compression model for analyzing energy requirements, including a sensitivity analysis to explore variations in parameters, while section 5 discusses the results of the compression analysis, comparing the actual compression work required for different combinations of initial and final pressure. Conclusions summarize the key insights and implications for hydrogen compression technology and suggest areas for future research.

2. Thermophysical Properties of Hydrogen and Gas Compression Storage Requirements

Hydrogen stands out as an element renowned for its thoroughly documented thermophysical properties. Its allure lies in its energy potential, boasting a notably high lower calorific value of 120 MJ/kg ; this promising energy carrier encounters a limitation in the form of its diminished density,

particularly under atmospheric pressure conditions. Table 1 shows a comparison of the different volumetric energy densities of hydrogen compared to other gases typically used as fuels, such as natural gas and methane in typical environmental conditions. From the analysis of hydrogen’s thermophysical properties, it is evident that gas-phase compression is thermodynamically advantageous. Liquid-phase compression, on the other hand, requires at least the same amount of work, but since the fraction of liquid separated is smaller, as depicted in the figure for a generic Linde compression cycle, a huge portion of the calorific power would be subtracted from the process. This is shown in a schematic way in Figure 2.




Figure 2. Hydrogen compression as a gas or in liquid form: schematic representation in T-S diagram.

Table 1. Energy content of hydrogen and other fuels at environmental temperature and pressure.

Fuel	Energy per liter [MJ/l]
Hydrogen (ambient pressure)	0.0107
Natural gas (ambient pressure)	0.0364
Methane (ambient pressure)	0.0378

Thinking about a generic gas like hydrogen, in the T-p diagram, during Joule-Thomson transformations, there is a zone where the derivative of temperature with respect to pressure, while keeping enthalpy constant the Joule-Thomson coefficient, μ , is positive:

$$\mu = \left(\frac{\partial T}{\partial p}\right)_{h=const} > 0 \tag{1}$$

It represents the rate of change of temperature with respect to pressure for a fluid undergoing throttling or expansion without external work or heat transfer. This allows for the possibility of liquefying a gas through a simple expansion or, better, throttling. Indeed, if the coefficient μ is negative, then decreasing the pressure increases the temperature, whereas if μ is positive, decreasing the pressure in the expansion or throttling of Joule-Thomson also decreases the gas temperature, enabling its liquefaction. In the case of hydrogen, the zone of saturated vapors is well below the inversion zone (Figure 2).

So, it is necessary to both compress and cool the fluid to be liquefied. In the right side of Figure 2 a liquefaction process based on the Joule-Thomson effect is represented. As well evidenced in Figure 2, this not only involves significant energy requirement but also results in the separation of a small portion of hydrogen in liquid form, making it clear how compression in the liquid phase is unlikely

to be a convenient solution, mainly from an energy point of view. In general, whether one wants to store hydrogen in liquid form or in gaseous form, it will be necessary to significantly increase the gas pressure, which will allow for a significant increase in density. The thermophysical properties of hydrogen are quite disadvantageous that even high-pressure gas compression and liquefaction bring them closer to conventional fuels, albeit still at a certain distance. As can be observed from an analysis of Figure 3, the volumetric energy content of hydrogen expressed in MJ/l, even with a compression level of 700 bar, is still about 1/7 of that available with the main liquid fuels typically used in the energy sector. Even liquefaction, despite all the highlighted issues, does not solve the problem. The issue of compressing hydrogen in gaseous form encompasses various aspects, including the significant consideration of storage vessels. Historically, certain pressure levels, such as 350 bar and 700 bar, have been identified as structurally feasible, with four distinct types of containers available for storage.




Figure 3. Volumetric energy content of different fuels in different operating conditions.

To compress the gas, multi-stage compression is typically employed. However, this compression transformation does not occur adiabatically because it would result in remarkably high energy consumption. For this reason, compression is conducted in multiple stages, and between each stage, the hydrogen must be adequately cooled.

To better understand the issues associated with hydrogen compression, whether aimed at maintaining it in liquid or gaseous conditions, it is necessary to have a clear idea of the orders of magnitude associated with the two phases. The thermophysical properties of hydrogen can be and it can be found in several books and articles, as [15] and [16] and by NIST webbook database, [17].

Some relevant values are reported in Appendix A of the present paper. A substantial upswing in density is associated to the application of high pressure and a simultaneous reduction in temperature. This correlation underscores the dynamic interplay between these thermodynamic factors, providing valuable insights for optimizing hydrogen storage and utilization strategies. As it can be seen by consulting the data available in Appendix A, hydrogen density experiences a significant increase at higher pressure and lower temperatures. Density values cannot be easily calculated using the ideal gas equation of state, since hydrogen exhibits behavior quite clearly as a real gas, but it could be evaluated using the values of the compressibility factor (Z), a dimensionless quantity that reflects how much the gas deviates from ideal behavior.

Compressed hydrogen storage encompasses a spectrum of pressure levels tailored for diverse applications. Small-scale storage, utilizing spherical vessels, commonly operates at 20 bars. Medium-scale storage in pipelines typically involves a pressure of 100 bar, while industrial-scale storage utilizes pressures in the range of 200–300 bar up to 1000 bar. Determining the optimal compression pressure for storing hydrogen in gaseous form is a nuanced challenge, requiring a compromise

between energy considerations, aiming to minimize the impact on compression work, and economic and safety factors. The latter involves ensuring that containers do not incur an excessive cost due to structural requirements and materials. Identifying an optimum point among these diverse objectives becomes crucial for each application, underscoring the need for a tailored approach. It is evident that pursuing a specific objective aligned with the unique characteristics of each application is imperative to address the complexities inherent in hydrogen storage.

3. Gaseous Hydrogen Compression: Analysis of Technological Solutions Available

Hydrogen compression in gaseous form plays a crucial role in various applications, including hydrogen storage, transportation, and energy conversion. Various methods for hydrogen compression are used. Each of them has its own unique characteristics, advantages, and drawbacks, [18].

The major compression technologies used for hydrogen applications are summarized in Figure 4, schematically evidencing the kind of energy required for obtaining the desired pressure level, mechanical or thermal energy. The main relevant are surely the volumetric technologies (reciprocating piston compressors, diaphragm/hydraulic/ionic, and screw compressors), in which a volume of gas is compressed by a gradual reduction within a control volume and then discharged at an increased pressure. Another mechanical option is represented by Dynamic compression (using centrifugal or compressors), in which kinetic energy is added to the inlet gas stream. No industrial references were found on centrifugal compressors on pure hydrogen, even if this is an active field of development. A relevant interest is for non-mechanical compression too: in this case different principles such as electrochemistry or adsorption (or absorption) of hydrogen into porous materials can be used, [19,20]. Table 2 aims to summarize the primary features of the various methods, according to a different point of view. Diaphragm compressors use flexible diaphragms to compress the gas, while screw compressors utilize rotating screws to decrease the volume of the gas.




Figure 4. A schematic representation of the main hydrogen compression method in gaseous form.

Hydrogen compression presents not only an energy challenge but also a material integrity concern. Hydrogen can induce embrittlement in metallic materials, reducing their ductility despite maintaining their strength. This can lead to the instability of defects, posing potential fracture risks from a fracture mechanics or fit-for-service standpoint.

Despite some technologies are already commercial, there is large debate for the investigation of more widespread and more advanced products to reach up to even 80-100 MPa for both stationary and mobile applications. Small-scale storage using spherical vessels commonly operates at 2 MPa.

Medium-scale storage in pipes typically involves a pressure of 10 MPa [21,22]. Industrial-scale storage utilizes pressures in the range of 20–30 MPa [23]. High operational pressures for light- and heavy-duty road transport span from 35 to 70 MPa [24]. Hydrogen storage in large production areas to hydrogen refuelling stations and/or industrial users may require compressing hydrogen up to 100 MPa. The isobaric and isenthalpic curves of interest for the storage of H₂ in compressed gaseous form are qualitatively represented in Figure 5.




Figure 5. Zone of interest for the storage of H₂ in compressed gaseous form: isobaric (red lines) and isenthalpic (blue lines) curves and area of interest (green).

Table 2. Characteristics of hydrogen compression; strengths and limits.

Compression method	Characteristics	strengths	limits
Mechanical Compression	Uses mechanical devices such as piston, diaphragm or screw compressors.	widely used in some practical applications	energy intensive
Electrochemical Compression	Uses electrochemical reactions to compress hydrogen.	It can operate at low temperatures and pressures, reducing the need for external energy input	require high-purity hydrogen feedstocks, which can add complexity and cost to the system
Hydraulic Compression	Use hydraulic pumps to compress hydrogen	simpler in design compared to mechanical compression systems	Low efficiency and potential leakage issues
Sorption-based Compression	Adsorption or absorption of hydrogen onto solid materials to achieve compression		It is difficult to achieve compression ratios as high as those by mechanical methods

The area of interest is identified by the minimum and maximum pressure and temperature values of the compression solutions discussed in this paper, i.e., pressure in the range 0.1–100 MPa and temperature 15–215 °C (Figure 5). As can be seen from the data in Table 3, analyzing some compressors available on the marked reveals that the maximum pressure level reached is approximately 450 bar, with the most frequently used pressure being around 350 bar. Compressors are of the volumetric typology, typically have 3 or 4 stages, even if compressor with five stages are

available too and are of quite low power rate and reduced mass flow rate. Table 3 presents some data that can be extracted from technical catalogue by various manufacturers, as [25,26]. Compressor with maximum output pressure of 700 bar are not commercially available in the market. Considering the data provided in Table 3, rearranged from available commercial data and referencing a total compression ratio of 350, the specific work associated with compression varies from approximately 10 MJ/kg for larger-sized compressors to over 26 MJ/kg for smaller-sized compressors. The nominal power of the various available models ranges from 3 kW up to 230 kW and the number of stages is from 2 to 5. The values of the specific works required for compression are estimated in the last column of the Table and are estimated by the authors based on the data reported by the manufacturers. As can be seen, they are dependent on the overall compression ratio and are a decidedly significant fraction of the calorific value of the fuel.

Table 3. Specification of some compressors of the commercial type.

Type/number of stages	Inlet pressure [bar]	Maximum Outlet pressure [bar]	Pressure ratio (max value)	Volumetric Flow rate [m ³ /h]	Nominal power [kW]	Specific work compression (estimated) [MJ/kg]
2	2-8	300-360	6.3	3.3-15.9	3-5.5	15.2-39.4
2	2-6	300-360	7.2	13.5-37.2	9.2-11	13.0-29.5
3	25-30	270-350	2.3	7-100	4-25	11.0-24.8
4	1.05-1.2	150-350	4.1	26-76	15-38	21.7-25.0
Up to 5	1.05-20	100-450	1.9	350-1000	132-230	10.1-16.3

Data for converting flow rate in kg/h: 1 m³/h (20 °C, 1013 hPa) = 0.083 kg/h [17].

4. Compression Model and Energy Requirements for Hydrogen Compression: Sensitivity Analysis

Compressing hydrogen into gaseous form is conceptually quite simple, but it demands a significant energy input. In this section, we explore the modeling of hydrogen compression, focusing on the comparison between idealized isothermal compression and real-world compression processes. We begin by examining the theoretical framework of isothermal compression, where the compression process occurs at constant temperature. Under ideal conditions, isothermal compression requires a minimal amount of energy input, as dictated by the ideal gas law. However, real-world compression systems deviate from ideal behavior due to factors such as friction, heat transfer, and inefficiencies inherent in mechanical components. Through mathematical modeling and simulation, we investigate how these deviations impact the energy requirements of hydrogen compression. By comparing the energy expenditure of idealized isothermal compression with real-world compression processes, we aim to quantify the efficiency losses associated with practical compression systems. This analysis provides valuable insights into the thermodynamic limitations and performance characteristics of hydrogen compression technologies. Considering a thermodynamic perspective, the process of isothermal reversible compression requires the least amount of work, and this can be computed under the assumption of ideal gas behavior from the thermodynamic state 1 to the thermodynamic state 2 with the following equation, [10]:

$$w_{iR,id} = R \cdot T_1 \cdot \ln\left(\frac{P_2}{P_1}\right) \quad (2)$$

So, the energy required to obtain a final pressure of 700 bar, starting from temperature of 300 K, is about 8.17 MJ/kg, while it is 7.30 MJ/kg for a compression at 350 bar.

$$w_{iR,id} = R \cdot T_1 \cdot \ln\left(\frac{P_2}{P_1}\right) = 4.157 \cdot 300 \cdot \ln\left(\frac{700}{1}\right) = 8170 \text{ kJ/kg} \quad (3)$$

The evaluation provided by equation (2) only gives a rough estimation of the minimum energy required to achieve the desired pressure, as it does not account for the non-ideal behavior of the gas.

This non-ideal behavior becomes more pronounced as the final pressure increases. From a technical point of view, two pressure levels are known at which compressions are made: 350 bar, in the case of small and medium-sized applications and 700 bar in the case of larger-sized applications. Obviously, none of these pressures can be obtained with a single compression step since, from a technological point of view, it is difficult to think of going beyond a compression ratio of 7. Therefore, starting from the atmospheric pressure, to obtain a final value of 350 bar at least 3 stages are necessary. To reach 700 bars, at least 4 compression levels are required. However, since the compressions are irreversible adiabatic and cause an increase in temperature, it is necessary to remain below a certain temperature level (200 °C). In practical scenarios, the temperature of hydrogen undergoes a considerable increase even when utilizing advanced multi-stage intercooling technology during compression. As a result, it is more accurate to characterize the compression process as a polytropic compression. The energy consumption for this type of process can be determined by the following equation, using a polytropic exponent, n , that accordingly with the most diffused textbooks of Thermodynamics can be assumed, according to the considerations contained in [10] to be $n=1.36$.

$$w_{pol} = \frac{n}{n-1} \cdot R \cdot T_1 \left[\left(\frac{P_2}{P_1} \right)^{n-1/n} - 1 \right] \tag{4}$$

The use of a polytropic index lower than 1.4 is also in line with the idea that the cooling system can be active during compression. As evidenced by the data presented in Table 4, the findings indicate a significant overestimation of compression work, particularly noticeable when targeting higher pressures. This underscores the necessity for a multi-stage compression approach with intercooling, rather than a simple polytropic compression with index n , which would result in excessively high specific work requirements and compression temperatures well above ambient levels. Moreover, the result reported in the fourth column of Table 4 is an underestimated value of the specific work required for compression as it does not consider the compressibility factor Z which would make the specific work even higher.

Table 4. Specific work for ideal isothermal compression and polytropic compression (with $n=1.36$) of hydrogen from 300 K and 0.1 MPa to a final pressure.

Final H ₂ pressure [MPa]	Density [kgH ₂ /m ³]	$w_{IT,id}$ [MJ/kgH ₂]	w_{pol} [MJ/kgH ₂]
2	1.6	3.73	5.7
10	7.8	5.74	11.2
20	14.7	6.61	14.4
30	20.8	7.11	16.6
35	23.8	7.30	17.5
70	40.0	8.17	22.0
100	49.4	8.61	24.6

If one approaches the evaluation of the compression process as if it were isothermal, two crucial elements are overlooked. On one hand, there might be a temptation to increase the compression pressure, leading to a significant rise in hydrogen density. On the other hand, the full understanding of the energy expenditure associated with the storage process would not be fully grasped. Due to the limitation of a pressure ratio of approximately 7 for each stage, achieving a pressure level of 350 bar necessitates three to five compression stages, while reaching 700 bars would require at least four stages. So, considering Equation (3), assuming perfect intercooling, where the gas is cooled to the initial temperature before each subsequent stage, literature estimates indicate that the minimum compression work can quickly escalate to 10.2 MJ/kg (calculated using a polytropic index $n=1.36$, assumed considering the contemporary action of refrigeration system), according to the analysis

referred in [10]. This value is 25% higher than that needed for an ideal isothermal process. However, an additional complication arises due to the real gas behavior.

Considering both the number of compression stages, N , the compressibility factor of hydrogen, Z , and an isentropic efficiency of compression, η_{is} , the compression work can be better evaluated with:

$$w_{m-s} = N \cdot \left(\frac{k}{k-1} \right) \cdot \left(\frac{Z}{\eta_{is}} \right) \cdot R \cdot T_{in} \left[\left(\frac{P_{st}}{P_{in}} \right)^{\frac{k-1}{Nk}} - 1 \right] \quad (5)$$

The practical energy consumption for hydrogen compression in real application, typically exceeds the theoretical minimum by at least 2.5 times. Consequently, in the case of reaching 700 bars, it can be higher than 20 MJ/kg, marking an unsustainable level, especially when considering it constitutes more than 15% of the calorific value. A more accurate assessment can be made by considering the differences in enthalpy at various compression stages, considering plausible values for isentropic efficiency.

Figure 6 shows the temperature-entropy diagram of an intercooled multi-stage compression with four stages of compression, where p_1 is the initial pressure of hydrogen to store and p_8 equals the storage pressure desired (p_{st}). The work of compression per kg of hydrogen in an intercooled multi-stage process (w_{m-s}) can be evaluated by the sum of the enthalpy changes between the stages. In an intercooled multi-stage compression, the specific work (w_{m-s}) can be evaluated, as schematically referred in Figure 6 by the isentropic efficiency (η_{is}) of the compressor, where referring to four compression stages:




Figure 6. Temperature-entropy diagram of an intercooled four stages compression.

$$w_{m-s} = \frac{(h_{2is}-h_1)+(h_{4is}-h_3)+(h_{6is}-h_5)+(h_{8is}-h_7)}{\eta_{is}} \quad (6)$$

and in general

$$w_{m-s} = (h_2 - h_1) + (h_4 - h_3) + (h_6 - h_5) + (h_8 - h_7) \quad (7)$$

The power of compressor is estimated considering the mass flow rate, m as:

$$W = m \cdot w_{m-s} \quad (8)$$

In general, to estimate the compression work, it is necessary to define the intermediate pressures (p_{int}), i.e., the pressures at which the gas is intercooled between two stages.

Thus, for example, $p_{int,1}$ equals the final pressure of the first stage and the initial pressure of the second stage of compression. The intermediate pressures can be selected using:

$$P_{int,i} = \left(\frac{P_{st}}{P_{in}} \right)^{\frac{i}{N}} \quad \text{with } i=1, 2, \dots, (N-1), \quad (2)$$

Considering N as the total number of compression stages and the initial compression pressure (P_{in}) equals 1 bar.

This choice can minimize the maximum temperature reached in compression and the specific work (w_{m-s}) necessary as the storage pressure and the number of stages vary. To reach a well-defined pressure, the compression work is minimum when all the stages have the same compression ratio (β), so that:

$$\beta = \left(\frac{p_{st}}{p_{in}} \right)^{\frac{1}{N}} \quad (3)$$

Therefore, the intermediate pressures minimizing the work of a multistage intercooled compression that has stages with the same isentropic efficiency can be defined as:

$$p_{int,i} = p_{in} \cdot \beta^i \quad \text{with } i=1, 2, \dots, (N-1) \quad (4)$$

In the context of hydrogen gas compression processes, it is important to consider that if hydrogen is introduced at environmental pressure (1 bar) the maximum compression ratio β cannot exceed 7. This means that to achieve a pressure level of 350 bar, at least three compression stages are required (1-7, 7-49, 49-343 bar). However, another significant factor to consider is the maximum temperature during compression, which should ideally not exceed 150-200 °C to avoid hydrogen embrittlement issues. Consequently, the maximum compression ratio between stages should not exceed five. Therefore, in practical technical solutions, reaching a pressure level of 350 bar is commonly associated with the use of at least 4 compression stages, theoretically allowing for pressure levels of approximately 620-625 bar (1-5, 5-25, 25-125, 125-625 bar). To reach pressure level of 700 bar or more requires at least 5 stages of compression.

5. Analysis of the Real Compression Work with Respect to the Various Combination of Initial and Final Pressure

In this section, the authors present some evaluations based on the model developed in Section 4, aimed at understanding the energy cost of compression processes under conditions as close to real as possible. To achieve this, it is necessary to assume about a plausible value for the isentropic compression efficiency. There is limited literature available concerning isentropic efficiency for H_2 compressors, but depending on the compressor type, size (scale) and design, this value varies in the range of ~55-80% for most compressor designs, according to [11,14,22]. So, considering an isentropic compression efficiency of 0.8 and assuming perfect intercooling, along with the initial pressure of the hydrogen and the desired pressure at the end of the process, as well as the maximum temperature achievable due to structural constraints, it follows the need to determine the optimal number of compression stages. As observed in Table 5, in terms of the specific work required for gas compression, the difference between using 2, 3, or 4 compression stages is not particularly relevant. However, what is noteworthy is the maximum temperature: while with two stages it reaches approximately 217 °C, 3 or 4 stages allow for much greater limitation of the maximum temperature. Similar considerations can be made if a final gas pressure of 10 MPa is required; in this scenario, it is not feasible to use with only two compression stages since the compression ratio would be approximately 10 (Table 6). The situation becomes more complicated if aiming to achieve a final pressure of 350 bar. In this case, maintaining reasonable value of maximum temperature requires 4 or 5 compression stages. The compression work required is about 11 MJ/kg, a value that is approximately 10% of the fuel's calorific value. Table 7 shows the data related to the two cases with 4 or 5 compression stages. Obviously, the specific energy required for compression increases as the isentropic compression efficiency decreases. Table 8 illustrates the specific work necessary if the

isentropic efficiency is 0.7. In this case maximum temperature, and the specific work of compression increases with respect to the cases analyzed in Tables 5-7.

Table 5. Specific work for multistage compression to 2 MPa (η_{is} =0.80): T_{in} = 20 °C, p_{in} = 0.1 MPa.

Number of stages	β	T_2 [°C]	T_4 [°C]	T_6 [°C]	T_8 [°C]	W_{m-s} [MJ/kg _{H2}]	$W_{m-s}/W_{iT,id}$
2	4.5	216.7	214.8			5.7	1.56
3	2.7	140.5	142.6	140.8		5.3	1.45
4	2.1	106.8	109.5	107.6	107.3	5.1	1.40

Table 6. Specific work for multistage compression to 10 MPa (η_{is} =0.80): T_{in} = 20 °C, p_{in} = 0.1 MPa.

Number of stages	β	T_2 [°C]	T_4 [°C]	T_6 [°C]	T_8 [°C]	W_{m-s} [MJ/kg _{H2}]	$W_{m-s}/W_{iT,id}$
3	4.6	220.2	222.9	222.8		8.8	1.59
4	3.2	164.6	162.7	162.5	162.8	8.3	1.49

Table 7. Data for intercooled multi-stage compression (η_{is} =0.80) from 0.1 MPa, 20 °C to 35 MPa.

Number of stages	β	T_2 [°C]	T_4 [°C]	T_6 [°C]	T_8 [°C]	T_{10} [°C]	W_{m-s} [MJ/kg _{H2}]	$W_{m-s}/W_{iT,id}$
4	4.3	209.5	211.4	211.4	212.5		11.3	1.61
5	3.2	164.6	167.0	166.7	166.7	167.6	10.9	1.54

Table 8. Optimized specific work of compression from 20 °C and 0.1 MPa. Multistage intercooled compression with η_{is} =0.70, varying the storage pressure and the number of stages.

p^{st} [MPa]	Three stages		Four stages		Five stages	
	T_{max} [°C]	W_{m-s} [MJ/kg]	T_{max} [°C]	W_{m-s} [MJ/kg]	T_{max} [°C]	W_{m-s} [MJ/kg]
2	160	6.0	122	5.8	100	5.7
10			185	9.5	147	9.2
20			214	11.4	171	10.9
30			232	12.5	185	12.0
35			242	13.0	191	12.4
70					219	14.5
100					235	15.8

As shown in Table 8, decreasing the isentropic efficiency from 0.8 to 0.7 results in both an increase in the specific work required for compression and a rise in the maximum temperature. The evaluations we have made up to this point take into consideration, for a question of homogeneity, the initial pressure of the hydrogen equal to 1 bar. The use of initial compression pressure higher than 1 bar can be helpful to reduce the specific compression work and the maximum temperatures. Considering the production of hydrogen using electrolyzers, the inlet pressure in the compression system can be even higher; in particular, considering commercial electrolyzers, the pressure of the hydrogen produced varies in the range between 1 and 35 bar. Considering a higher inlet pressure determines a reduction in the work removed in the compression process and potentially in the number of stages. Considering for example inlet pressure of 30 bar (available for hydrogen after electrolysis process), it is possible to reduce in a relevant way both the specific work of compression and the maximum temperature as well as the number of stages required. Table 9 shows for example

the date relative to three different values of the final pressures particularly, p_{st} = 350, 700 or 1000 bar, typical values for high size storage infrastructures, like hydrogen re-fueling stations, as discussed in section 3. Referring the sensitivity analysis previously developed, we have established that the compression of hydrogen necessitates of an additional energy input, particularly noteworthy when dealing with substantial pressures increase, amounting to approximately 10% of the calorific value of hydrogen if a pressure ratio of 700:1 is considered. This factor gains even more significance when considering that a portion of the energy has already been dissipated during the electrolysis process. It is crucial to emphasize, however, that the energy expenditure during the compression phase does not escalate significantly in relation to the compression ratio.

Table 9. Intercooled multistage compression (η_{is} =0.80) with three stages from initial condition of 20 °C and 3 MPa.

p_{st} [MPa]	β	T_{max} [°C]	W_{m-s} [MJ/kg _{H2}]	$W_{m-s}/LHV_{H2} \cdot 100$ [%]	$W_{m-s}/W_{iT,id}$
35	2.3	119	4.5	3.8	1.49
70	2.9	152	6.2	5.2	1.61
100	3.2	171	7.2	6.0	1.67

This implies that the selection of an optimal compromise between enhancing density and minimizing work input might be contingent on other critical factors. These factors include the maximum number of compression stages, the upper limit on compression temperature, and the maximum compression ratio associated with a single stage. Balancing these elements becomes important in determining the overall efficiency and feasibility of hydrogen compression processes. Analyzing all the data related to the specific work for compressing hydrogen in gaseous form, W_{m-s} , it can be observed that this is estimable, depending on the case, at a percentage ranging between 40% and 67% higher than the ideal work achievable in an isothermal compression according to Equation 2, $W_{iT,id}$.

Comparing the values reported in the previous tables and the values reported in the commercial systems available on the market, one cannot fail to observe the fact that the value of the specific compression works that can be estimated from the catalog data (see Table 3) are decidedly higher than those that can be estimated with theoretical evaluations such as those we have made. This leads us to think that in fact the isentropic compression efficiency may be lower than those considered in these evaluations (0.7-0.8), i.e., of the order of 0.5-0.55. It is clear, however, that the achievement of higher isentropic efficiencies can be linked to larger compressors and is therefore conceivable.

As relevant concluding remarks of the analysis we can summarize the following main elements. Compression of hydrogen in the gaseous form requires relevant energy input, and for significant pressures, this energy input is approximately 10% of the calorific value of hydrogen. This is particularly notable, especially considering that a portion of the energy is already dissipated for hydrogen production, as for example in the electrolysis process. It is important to highlight that the energy spent during the compression phase does not increase proportionally with the compression ratio. This suggests that the choice of an optimal compromise between increasing density and minimizing work input depends on several factors beyond the compression ratio itself.

The selection of an optimal compromise hinges on other relevant elements such as the maximum number of compression stages also involves considerations of the maximum compression temperature and the maximum compression ratio associated with a single stage. Balancing all those elements is crucial for determining the overall efficiency and feasibility of hydrogen compression processes. This underscores the need for a nuanced approach that considers multiple factors in achieving an effective and sustainable compression strategy for hydrogen.

Finally, we have seen how reaching a maximum pressure level of 700 bar is quite reasonable: lower pressure levels do not seem particularly advantageous, considering that the energy extracted from the process is not significantly higher than that required to achieve a pressure level of 350 bar.

Of course, we must also consider that the energy expended for compression is energy withdrawn from the energy chain. Indeed, thinking about a system like the one depicted in Figure 1, hydrogen storage can be justified only by the need to introduce greater flexibility into the energy system and gaseous storage appears to be the most relevant. However, in terms of energy balance, of the 120 MJ contained in one unit of hydrogen mass, at least 40 MJ are dissipated in the electrolysis process (Franco and Giovannini, in [27]) and 10-15 MJ are additionally consumed in the compression phase. This means that more than 40-45% of the renewable energy converted is lost in the chain before utilization. The quantity would certainly be higher when considering storage in liquid form. Therefore, optimizing techniques for storing hydrogen in gaseous form is certainly an important objective, but it is still important to keep in mind that the use of storage must always be carefully evaluated.

6. Conclusions

This study examined the issue of hydrogen compression in gaseous form from a thermodynamic perspective. After outlining the context and analyzing some of the commercially available technical solutions, several cases of practical technical interest were evaluated. The specific work for compression depends on the desired final pressure and the maximum achievable temperature. Limiting the temperature to 150-200 °C requires restricting the compression ratio between successive stages. Employing multiple compression stages is necessary to achieve high final pressures: for instance, to attain a pressure of 350 bar, at least 4 compression stages are required. The specific compression work is about 11 MJ/kg, approximately 10% of the lower heating value of the fuel. This should be considered in assessing the overall energy efficiency. However, the achievable increase in density is significant, which may offset the energy cost of compression. Significant reductions in specific work can be achieved by using higher hydrogen inlet pressures, such as 30 bar. In this scenario, besides obtaining a substantial reduction in compression work, it is possible to limit the temperature to slightly above 100 °C. For example, using 5 compression stages, it is feasible to compress up to 1000 bar with an energy expenditure of approximately 6 MJ/kg, equivalent to around 5% of the fuel's lower heating value. Here is a concise summary of the provided information.

Examining the compression work required for different pressure combinations highlights the importance of optimizing compression stages. Data in Tables 7 and 8 underscore that while the number of compression stages affects temperature control, the specific work required remains consistent. Achieving a pressure of 700 bar appears reasonable, considering marginal energy gains for lower pressures. However, it is vital to recognize that energy expended during compression detracts from overall energy efficiency. Approximately 40% of renewable energy is lost in the chain before utilization, with compression contributing significantly to this loss. The energy expended during compression does not increase proportionally with the compression ratio, necessitating a nuanced approach to balancing efficiency and feasibility. The choice of compression strategy must consider factors like the number of compression stages, maximum compression temperature, and compression ratio. Achieving an optimal compromise between increasing density and minimizing work input is crucial for efficient hydrogen compression.

In summary, while optimizing compression techniques is crucial for hydrogen storage, careful evaluation of storage utilization remains essential, considering its impact on overall energy efficiency.

Author Contributions: Conceptualization, A.F.; formal analysis, A.F. and C.G.; methodology, A.F. and C.G.; data curation, A.F. and C.G.; supervision, A.F.; writing—original draft preparation, A.F., writing, review, and editing, A.F. and C.G. funding acquisition, A.F., All authors have read and agreed to the published version of the manuscript.

Funding: This work was supported by the National Recovery and Resilience Plan (NRRP), Mission 4 Component 2 Investment 1.3—Call for tender No. 1561 of 11.10.2022 of Ministero dell'Università e della Ricerca (MUR); project funded by the European Union—NextGenerationEU. Award Number: Project code PE0000021, Concession Decree No. 1561 of 11.10.2022 adopted by Ministero dell'Università e della Ricerca (MUR), CUP

I53C22001450006, according to attachment E of Decree No. 1561/2022, Project title “Network 4 Energy Sustainable Transition—NEST”.

Data Availability Statement: The main data presented in the paper are reported.

Acknowledgments: The data presented in this study are available upon request from the corresponding author

Conflicts of Interest: The authors declare no conflicts of interest.

Nomenclature

h	specific enthalpy, kJ/kg
i	Generic i -th stage
k	Exponent of adiabatic transformation
LHV	lower heating value, MJ/kg
m	Hydrogen mass flow rate, kg/s
n	Exponent of polytropic transformation
N	Number of compression stages
P, p	pressure, Pa (bar, MPa)
s	specific entropy, kJ/(kg K)
R	Gas constant, J/(kg K)
T	temperature, K or °C
v	specific volume, m ³ /kg
W	Compressor power, kW (MW)
Z	Compressibility factor
w	specific work of compression, MJ/kg
β	Pressure ratio
ρ	density, kg/m ³
η	Efficiency
μ	Joule-Thomson coefficient, K/Pa

Subscripts, Superscripts, Acronyms, and Abbreviations

CGH ₂	Compressed hydrogen gas
id	Ideal value
in	Inlet value
int	Intermediate
is	Isentropic
iT	Isothermal
LH ₂	hydrogen in liquid form
max	Maximum value
m-s	intercooled multi-stage
pol	Polytropic
PV	PhotoVoltaic
SSH ₂	Solid storage of hydrogen
st	Storage

Appendix A: The Particular Behavior of Hydrogen and Its Thermophysical Properties

This appendix reports the main thermophysical properties used in this work and taken from the literature. Table A1 and Figure A1 presents various density values as a function of typical combination of pressure and temperature, considering a field of interest in the range between -100 °C and 125 °C. Analyzing the data in the table and in the figure, we observe how the value of the hydrogen density increases significantly from values of approximately 0.08 kg/m³ at atmospheric conditions and reaches values higher than 20 kg/m³, only if the pressure exceeds 300 bars.




Figure A1. Hydrogen density as a function of Temperature and Pressure.

Table A1. Hydrogen density (kg/m³) at Different Temperatures (°C) and Pressures (MPa).

T [°C]	0.1 MPa	1 MPa	5 MPa	10 MPa	30 MPa	50 MPa	100 MPa
-100	0.1399	1.3911	6.7608	12.992	32.614	46.013	66.660
-75	0.1223	1.2154	5.9085	11.382	29.124	41.848	62.322
-50	0.1086	1.0793	5.2521	10.141	26.336	38.384	58.503
-25	0.0976	0.9708	4.7297	9.1526	24.055	35.464	55.123
0	0.0887	0.8822	4.3036	8.3447	22.151	32.968	52.115
25	0.0813	0.8085	3.9490	7.6711	20.537	30.811	49.424
50	0.0750	0.7461	3.6490	7.1003	19.149	28.928	47.001
75	0.0696	0.6928	3.3918	6.6100	17.943	27.268	44.810
100	0.0649	0.6465	3.1688	6.1840	16.883	25.793	42.819
125	0.0609	0.6061	2.9736	5.8104	15.944	24.474	41.001

While the behavior of most gases can be approximated using the ideal gas law, the behavior of H₂ deviates significantly from ideal gas model predictions. Hydrogen, other things being equal, takes up more space than the ideal gas law predicts. This deviation is accounted for using the compressibility factor (Z): Z=1 for an ideal gas.

By analyzing the behavior of hydrogen and other gases, we can observe that for pressures lower than 600 bar, Z is greater for H₂ compared to other gases such as CH₄, O₂ and CO₂. So compressing H₂. from 1 bar to 700 bar, the density increases less than 500 times going at a temperature of 0 °C from 0.0887 kg/m³ to 42.9 kg/m³. The direct dependence on Z leads to a higher compression power demand for H₂.

Table A2 and Figure A2, provides the values of the compressibility factor (Z), a dimensionless quantity that reflects how much the gas deviates from ideal behavior, with the similar values of pressure and temperature. As it can be observed, the compressibility factor Z, which measures the deviation between the behavior of the ideal gas and the real gas, if it is close enough to 1 for pressures up to around 100 bar (it still remains less than 1.05-1.06), becomes rather relevant for pressure values above 500 bar, when it exceeds values of 1.25-1.3 (at temperatures below 100°C).




Figure A2. Hydrogen Compressibility (Z) at Different Temperatures and Pressures.

Table A2. Compressibility factor Z of Hydrogen at Different Temperatures (°C) and Pressures (MPa).

T [°C]	0.1 MPa	1 MPa	5 MPa	10 MPa	30 MPa	50 MPa	100 MPa
-100	1.0007	1.0066	1.0356	1.0778	1.2880	1.5216	2.1006
-75	1.0007	1.0068	1.0355	1.0751	1.2604	1.4620	1.9634
-50	1.0007	1.0067	1.0344	1.0714	1.2377	1.4153	1.8572
-25	1.0006	1.0065	1.0329	1.0675	1.2186	1.3776	1.7725
0	1.0006	1.0062	1.0313	1.0637	1.2022	1.3462	1.7032
25	1.0006	1.0059	1.0297	1.0601	1.1879	1.3197	1.6454
50	1.0006	1.0056	1.0281	1.0567	1.1755	1.2969	1.5964
75	1.0005	1.0053	1.0266	1.0536	1.1644	1.2770	1.5542
100	1.0005	1.0050	1.0252	1.0507	1.1546	1.2596	1.5175
125	1.0005	1.0048	1.0240	1.0481	1.1458	1.2441	1.4852

Finally, Figure A3, readapted and rearranged from the original reported by Gstrein and Klell [15] and Klell [16] provides an overview of hydrogen thermophysical properties in a T-s diagram, in particular the correlation among pressure (p), density (r) and enthalpy (h) in the range between 0 and 325 K.




Figure A3. Hydrogen thermophysical properties in a T-s diagram. (Readapted and Rearranged from the original reported by Gstrein and Klell [15] and Klell [16]).

References

1. Ajanovic, A., Sayer, M., & Haas, R. (2024). On the future relevance of green hydrogen in Europe. *Applied Energy*, 358, 122586.
2. Makridis, S. (2017). Hydrogen storage and compression. arXiv preprint arXiv:1702.06015
3. Bossel U, Eliasson B, Energy and the hydrogen economy, US DOE, EERE, http://www.afdc.energy.gov/pdfs/hyd_economy_bossel_eliasson.pdf

4. Arsad, A. Z., Hannan, M. A., Al-Shetwi, A. Q., Mansur, M., Muttaqi, K. M., Dong, Z. Y., & Blaabjerg, F. (2022). Hydrogen energy storage integrated hybrid renewable energy systems: A review analysis for future research directions. *International Journal of Hydrogen Energy*, 47(39), 17285-17312. <https://doi.org/10.1016/j.ijhydene.2022.03.208>
5. Wieliczko, M., & Stetson, N. (2020). Hydrogen technologies for energy storage: A perspective. *MRS Energy and Sustainability*, 7, E41. <https://doi.org/10.1557/mre.2020.43>
6. Usman, M. R. (2022). Hydrogen storage methods: Review and status. *Renewable and Sustainable Energy Reviews*, 167, 112743. <https://doi.org/10.1016/j.rser.2022.112743>
7. Hassan, Q., Sameen, A. Z., Salman, H. M., Jaszczur, M., & Al-Jiboory, A. K. (2023). Hydrogen energy future: Advancements in storage technologies and implications for sustainability. *Journal of Energy Storage*, 72, 108404. <https://doi.org/10.1016/j.est.2023.108404>
8. Muthukumar, P., Kumar, A., Afzal, M., Bhogilla, S., Sharma, P., Parida, A., ... & Jain, I. P. (2023). Review on large-scale hydrogen storage systems for better sustainability. *International Journal of Hydrogen Energy*.
9. Tang, D., Tan, G. L., Li, G. W., Liang, J. G., Ahmad, S. M., Bahadur, A., Humayun, M., Ullah H, Khan A., & Bououdina, M. (2023). State-of-the-art hydrogen generation techniques and storage methods: A critical review. *Journal of Energy Storage*, 64, 107196.
10. Zhang, J., Fisher, T. S., Ramachandran, P. V., Gore, J. P., & Mudawar, I. (2005). A review of heat transfer issues in hydrogen storage technologies. *Journal of Heat Transfer* DECEMBER 2005, Vol. 127 / 1391 <https://doi.org/10.1115/1.2098875>
11. Sdanghi, G., Maranzana, G., Celzard, A., & Fierro, V. (2019). Review of the current technologies and performances of hydrogen compression for stationary and automotive applications. *Renewable and Sustainable Energy Reviews*, 102, 150-170. <https://doi.org/10.1016/j.rser.2018.11.028>
12. Zheng, J., Liu, X., Xu, P., Liu, P., Zhao, Y., & Yang, J. (2012). Development of high-pressure gaseous hydrogen storage technologies. *International journal of hydrogen energy*, 37(1), 1048-1057. <https://doi.org/10.1016/j.ijhydene.2011.02.125>
13. Barthélémy, H. (2012). Hydrogen storage-Industrial perspectives. *International journal of hydrogen energy*, 37(22), 17364-17372.
14. Khan, M.A., Young, C., MacKinnon, C. and Layzell, D. (2021). The Techno-Economics of Hydrogen Compression. *Transition Accelerator Technical Briefs*, 1(1), 1-36.
15. Gstrein, G., & Klell, M. (2004). Properties of hydrogen. Institute for Internal Combustion Engines and Thermodynamics, Graz University of Technology.
16. Klell, M. (2010). Storage of hydrogen in the pure form. *Handbook of hydrogen storage*, 1-37.
17. NIST. Thermophysical Properties of Fluid Systems. Available online at: <https://webbook.nist.gov/chemistry/fluid/> (last access: January 2024).
18. Bosu, S., & Rajamohan, N. (2024). Recent advancements in hydrogen storage-Comparative review on methods, operating conditions and challenges. *International Journal of Hydrogen Energy*, 52, 352-370.
19. Zou, J., Han, N., Yan, J., Feng, Q., Wang, Y., Zhao, Z., Fan J., Zeng L., Li H. & Wang, H. (2020). Electrochemical compression technologies for high-pressure hydrogen: current status, challenges and perspective. *Electrochemical Energy Reviews*, 3, 690-729.
20. Durmus, G. N. B., Colpan, C. O., & Devrim, Y. (2021). A review on the development of the electrochemical hydrogen compressors. *Journal of Power Sources*, 494, 229743.
21. Witkowski, A., Rusin, A., Majkut, M., & Stolecka, K. (2017). Comprehensive analysis of hydrogen compression and pipeline transportation from thermodynamics and safety aspects. *Energy*, 141, 2508-2518. <http://dx.doi.org/10.1016/j.energy.2017.05.141>
22. Tahan, M. R. (2022). Recent advances in hydrogen compressors for use in large-scale renewable energy integration. *International Journal of Hydrogen Energy*, 47(83), 35275-35292. <https://doi.org/10.1016/j.ijhydene.2022.08.128>
23. Barthélémy, H., Weber, M., & Barbier, F. (2017). Hydrogen storage: Recent improvements and industrial perspectives. *International Journal of Hydrogen Energy*, 42(11), 7254-7262. <http://dx.doi.org/10.1016/j.ijhydene.2016.03.178>
24. Elberry, A. M., Thakur, J., Santasalo-Aarnio, A., & Larmi, M. (2021). Large-scale compressed hydrogen storage as part of renewable electricity storage systems. *International journal of hydrogen energy*, 46(29), 15671-15690. <https://doi.org/10.1016/j.ijhydene.2021.02.080>
25. Sauer Compressors: Hydrogen compressors catalogue. Available at: <https://www.sauercompressors.com/gases/technical-gases/hydrogen-compressors> (last access: 17 March 2024).
26. Coltri Compressors: Booster hydrogen catalogue. Available at: <https://coltri.com/en/download/catalogs/hydrogen-booster-catalog/> (last access: 20 April 2024).
27. Franco, A., & Giovannini, C. (2023). Recent and Future Advances in Water Electrolysis for Green Hydrogen Generation: Critical Analysis and Perspectives. *Sustainability*, 15(24), 16917. <https://doi.org/10.3390/su152416917>

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.