

**Article** 

Not peer-reviewed version

# Influence of Land Use and Land Cover on the Quality of Surface Waters in the Miranda River Watershed, Brazilian Pantanal

Wesley dos Santos Carvalho , <u>Fernando Jorge Corrêa Magalhães Filho</u>\*, Lucia Ribeiro Rodrigues , Cristina Sousa Coutinho Calheiros\*

Posted Date: 14 May 2024

doi: 10.20944/preprints202405.0938.v1

Keywords: wetland; water quality; water management; correlation; river basin



Preprints.org is a free multidiscipline platform providing preprint service that is dedicated to making early versions of research outputs permanently available and citable. Preprints posted at Preprints.org appear in Web of Science, Crossref, Google Scholar, Scilit, Europe PMC.

Disclaimer/Publisher's Note: The statements, opinions, and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions, or products referred to in the content.

Article

# Influence of Land Use and Land Cover on the Quality of Surface Waters in the Miranda River Watershed, Brazilian Pantanal

Wesley dos Santos Carvalho <sup>1</sup>, Fernando Jorge Corrêa Magalhães Filho <sup>2\*</sup>, Lucia Ribeiro Rodrigues <sup>2</sup>, Cristina Sousa Coutinho Calheiros <sup>3,\*</sup>

- Dom Bosco Catholic University, Av. Tamandaré, 6000, Campo Grande, MS 79117-010, Brazil; wesleysc352@gmail.com
- <sup>2</sup> Institute of Hydraulic Research (IPH). Federal University of Rio Grande do Sul, Av. Bento Gonçalves 91501-970, Porto Alegre, Brazil; fernando.magalhaes@ufrgs.br; luciarrodrigues@gmail.com
- <sup>3</sup> Interdisciplinary Centre of Marine and Environmental Research (CIIMAR/CIMAR), University of Porto, Novo Edifício do Terminal de Cruzeiros do Porto de Leixões, Avenida General Norton de Matos, S/N, 4450-208 Matosinhos, Portugal; cristina.sc.calheiros@gmail.com
- \* Correspondence: FJCMF: fernando.magalhaes@ufrgs.br; CSCC: cristina.sc.calheiros@gmail.com

Abstract: Water quality assessment stands as a fundamental step in water resource management. In addition to substances and organisms present in the water, land use and land cover are two factors affecting also water quality. This study analyzed the correlation and influence between water quality and land use and land cover in the Miranda River Basin (MRB) and the natural wetlands in the Pantanal Biome. Using a watershed-wide approach, results suggested that water quality management policies can be considered in terms of sub-basins (smaller planning units). The Water Quality Index (WQI) was considered GOOD or EXCELLENT throughout the MRB. It was observed that the natural wetlands have the capacity to contribute to improve WQI, with reductions in thermotolerant coliforms and turbidity; however, high values were found for thermotolerant coliforms, a temporal increasing trend of biochemical oxygen demand (BOD), and a reduction in dissolved oxygen and total phosphorus. Conversely, it was found in these flooded areas a trend of decrease in dissolved oxygen and an increase in BOD concentrations. Natural wetlands play important hydrological and ecological roles in water quality, storing, removing, and cycling nutrients. They are highly relevant areas for defining watershed management and conservation strategies, environmental protection, and providing ecosystem services.

Keywords: wetland; water quality; water management; correlation; river basin

# 1. Introduction

The demand for water, both in quantitative and qualitative terms, is increasingly significant having in consideration the population growth and economic development. Therefore, it is essential to manage water resources and other natural resources to guarantee access to water under suitable usage conditions [1]. Given this importance, the United Nations (UN) within the framework of Agenda 2030 prioritizes drinking water and sanitation as one of the 17 Sustainable Development Goals (SDGs) for a global sustainable development agenda by 2030. SDG 6 aims to ensure the availability and sustainable management of water and sanitation for all. Its main objectives involve improving water quality, integrated water resource management, universal access to basic sanitation, water use efficiency, and the protection and restoration of aquatic ecosystems such as forests, rivers, lakes, aquifers, and wetlands [2]. The assessment of water quality, and mitigation of major sources of pollution, is one of the pillars adopted by Brazil to fulfill SDG 6. This assessment is one of the steps in water resources management and is carried out through monitoring physical, chemical, and

microbiological parameters via measurements of dissolved substance concentrations, physical properties, and analysis of pathogenic microorganisms [3].

The spatial distribution of land use is a key factor that affects water quality, where industrial, urban, and agricultural land uses generally pose relatively high pollution risks compared to other types of land use such as forests and wetlands [4]. In addition to land use, water quality can also be influenced by quantity, as it directly depends on the amount of water available to dissolve, dilute, and transport substances, whether beneficial or harmful to living organisms [5]. Hence, water quality may be perceived as the outcome of both natural processes and human activities within the watershed, with land use and cover therein acting as determining factors. Understanding its relationship with land use and cover can be useful for identifying potential risks to water quality and coordinating water resource management with other uses of environmental resources [3].

The Miranda River Watershed (MRW) is one of the main hydrographic regions within the Pantanal Biome, located in the state of Mato Grosso do Sul, Brazil, and entirely falls within the Upper Paraguay Basin (UPB). It is formed by the Miranda River as its main course and the Aquidauana River, and is situated in the transition zone between the Cerrado and Pantanal biomes, as well as the transition from the Plateau to the Pantanal Plain. Natural wetland areas are environments with high biodiversity associated with permanently or seasonally flooded areas. They are responsible for groundwater recharge due to their slow flow and long water retention time above ground, serving as "buffer zones" upstream and downstream of their territory, slowing down water flow and nourishing other ecosystems during dry periods. These areas retain large amounts of sediment and chemicals, improving water quality and the entire biological dynamics downstream. A considerable amount of pollutants that enter wetland areas are captured by vegetation and microorganisms or adhere to suspended particles. Consequently, sedimentation in wetlands contributes positively to water quality [6].

Understanding the relationship between land use and water quality would help assess water quality in unmonitored basins, as monitoring is often costly and time-consuming. Additionally, this knowledge would provide guidelines for watershed managers and policymakers to prioritize future land use development [7]. Thus, conducting an analysis of the relation between water quality and different types of land use and cover is an important step in the management of natural resources, developing conversion strategies, and guiding the sustainable use of these resources. In this regard, studies have analyzed the influence of land use and cover on water quality through multiple approaches; utilizing correlation coefficients between quality and land use [8], comparative analysis between input and output [9], through the use of regression equations [10], and multivariate analysis [11]. Although many approaches are being evaluated to analyze the influence of land use on water quality, most studies rely on limited time series data, often from only a single year or a single monitoring point, or few parameters. The MRW has a monitoring network with 28 stations distributed across the main rivers of the basin, as well as a quality and consistent historical data series available to the general public. However, few studies are reported with emphasis on this specific area. Overall, there are still few studies on the capacity of removal/retention of substances in natural wetland areas of tropical and subtropical regions, especially in South America [12]. The fact is that the number of parameters and the monitoring frequency have been continuously expanded, generating water quality data from an important transition region between the Pantanal and Cerrado Biomes, as it is also located in the transition region from the Plateau to the Pantanal Plain. Therefore, analyzing the relationship between land use and water quality by jointly considering the temporal dimension with the spatial dimension is essential to understand the dynamics of water quality and land use in the region's natural wetlands.


The objective of this study was to analyze the correlation between land use and land cover and the quality of surface waters in a natural wetland area in the MRW, in Mato Grosso do Sul, Brazil. For that it was identified which quality parameters were the most relevant (key factors) and the dynamics of substance concentrations along the main watercourses of the basin. Additionally, it aimed to analyze the influence of natural wetland areas on water quality, considering how these areas are capable of improving water quality.

-

#### 2. Materials and Methods

## 2.1. Study Area

The study area is the MRW and its natural wetland area. The watershed covers nearly 43,000 km<sup>2</sup> with its headwaters in the Plateau area (Cerrado Biome) and its mouth in a portion of flooded area in the Pantanal Biome (Figure 1). In the MRW, there are a total of 28 monitoring points distributed along the main streams and rivers of the basin.



**Figure 1.** Miranda River Watershed with selected Water Quality Monitoring Stations (Sub-basins: 1-17) and the natural wetland area.

#### 2.2. Delimitation of Influence Areas

For the analysis of land use and cover and water quality, the MRW was subdivided into 17 subbasins. For that, the 28 monitoring stations existing in the MRW were rearranged into these 17 Influence Areas, where monitoring stations very close to each other along the same watercourse were grouped into the same Influence Area. They were thus considered Influence Areas in relation to the location of water quality monitoring stations along the main watercourses of the basin. The spatial scale used in this study is the "sub-basin" scale. This scale was employed for analyzing variations in water quality parameters and their relationship with land use and cover (correlation coefficient). These influence areas or sub-basins were delineated considering the "theoretical outlet" as the 17 main water quality monitoring stations, indicating the upstream influence area of that point.

#### 2.3. Land Use and Land Cover in the Miranda River Watershed

For the assessment of land use and land cover in the MRW, multitemporal data from the Collection 6.0 of Land Cover and Use from MapBiomas between the years 2005 to 2018 were used [13] for the entire watershed and for the 17 Influence Areas. The data was provided by MapBiomas and accessed through the Google Earth Engine platform in raster structure (TIFF format), with a spatial resolution of 30 meters where each pixel has an integer numerical value corresponding to a specific type of land use and land cover. MapBiomas utilizes a total of 25 thematic classes related to land use and land cover for the entire national territory. In the study area, the original classes used by MapBiomas were adapted to seven thematic classes of land use and land cover in order to simplify and reduce the number of variables in the study: Native Vegetation, Wetlands, Agriculture (temporary or perennial), Pasture, Urban Area, Non-Vegetated Area, and Water Bodies.

The MapBiomas classes labeled "Forest Formation", "Savanna Formation", and "Grassland Formation" were grouped into the class "Native Vegetation." Classes with anthropic crops (perennial or temporary) such as "Planted Forests", "Soybeans", "Sugarcane and "Other Temporary Crops" were adapted to the "Agriculture" class. The "Pasture" class from MapBiomas remained with the denomination "Pasture," similarly to the classes of "Wetlands", "Other Non-Vegetated Areas", "Urban Infrastructure", "Rivers and Lakes" adopted by MapBiomas were renamed to "Wetlands", "Non-Vegetated", "Urbanized Area", and "Water Bodies" respectively.

#### 2.4. Water Quality Data Collection

The historical series of water quality data was obtained through consultation of the "Monitoring Reports of Surface Water Quality in Mato Grosso do Sul" available on the IMASUL website [14]. The study period comprised data from the year 2005 to the year 2018. This time frame was chosen due to the consistency of the data, as from the year 2005, the main parameters began to be systematically and continuously analyzed, with quarterly and/or semiannual collections until the year 2018 when the data from the historical series were already fully processed. For the analysis of temporal and spatial variation of water quality in the MRW, the annual average and standard deviation of each water quality parameter were calculated in the 17 proposed Influence Areas in the study.

Nine water quality parameters with consistent data between 2005-2018 were analyzed. The parameters were also analyzed considering the reference values for the classification of water bodies for Class 2 (Table 1).

Table 1. Quality	y parameters and	reference	values for	Class 2	classification	Deliberation	CECA No.
36/2012.							

Parameter	Unit	Analytical Method	Class 2 Limit Value	
pН	-	4500-H [15]	6-9	
Dissolved Oxygen (DO)	mg/L	ASTM D888-12 [16]	>5.0	
Biochemical Oxygen Demand (5-day BOD Test)	mg/L	5210-D [15]	≤5.0	
Fecal coliforms	MPN. 100 m/L	9221–E [15]	≤200	
Total Nitrogen (TN)	mg/L	NBR 13796 [17]	-	
Total Phosphorus (TP)	mg/L	4500 P-B, E [15]	≤0.1	
Total Solids (TS)	mg/L	2540 – C [15]	-	
Turbidity (Tu)	NTU	2130-B [15]	≤100	
Water Quality Index (WQI)	-	Calculated	-	

#### 2.5. Correlation between Land Use and Land Cover and Water Quality

Correlations were calculated between land use classes and water quality parameters. Initially, the Overall Correlation was calculated considering the entire MRW, and subsequently, individual

4

5

$$\rho = 1 - \frac{6\sum d^2}{n(n^2 - 1)} \tag{1}$$

Where d is the difference between the positions of corresponding values of X and Y; n is the number of pairs of data values.

The Spearman's Rank Correlation Coefficient measures the degree of linear correlation between two non-parametric variables. The value of  $\rho$  ranges from -1 to +1, where values closer to +1 indicate a perfect positive correlation between two variables, meaning that the units of the variables increase together; values closer to -1 indicate a perfect negative correlation, as one variable increases, the other decreases; and values closer to 0 indicate that both variables are not linearly dependent on each other.


# 2.6. Influence of Wetlands on Water Quality in the Miranda River Watershed

The analysis of the influence of wetlands on water quality was carried out based on monitoring stations located within the delineation of the Pantanal Biome according to [18]. In this region, the main land use and land cover class corresponds to wetlands formed by characteristic flooded fields of the Pantanal biome. Monitoring stations located on the Aquidauana River and Miranda River, in the Pantanal area and its vicinity, were considered (Table 2). These stations were subdivided into START stations, positioned at the entrance of the Pantanal (upstream); INTERMEDIATE, those stations in the middle part of the watercourses present in the Pantanal of the MRW; and at the MOUTH of the Miranda River with the Paraguay River (Figure 2).

**Table 2.** Existing water quality monitoring stations in the natural wetland, in the Pantanal Biome of the Miranda river watershed.

Position	Station code [19]	Name (Influence Areas)	River
Start	00MS23AQ2284	IA07	Aquidauana
Start	00MS23MI1292	IA14	Miranda
Intermediate	00MS23AQ2000	IA15	Aquidauana
Intermediate	00MS23MI2147	IA16	Miranda
Mouth	00MS23MI2000	IA17	Mouth of Miranda

The influence of wetlands was analyzed by comparing the annual mean values and trends of each water quality parameter at START (entrance), INTERMEDIATE (midstream), and MOUTH (exit) points, considering the dry season (April to October) and rainy season (November to March).




**Figure 2.** Monitoring stations in the natural wetland area of the Miranda river watershed, in the Pantanal Biome (IA: Influence Areas).

# 3. Results and Discussion

# 3.1. Changes in Land Use and Land Cover in the Miranda River Watershed

Over the analyzed period, the areas of Native Vegetation decreased from 1,695,580.20 hectares to 1,558,072.61 hectares, representing a decrease of approximately 8.11% over 14 years (Figure 3). This trend of reduction in native vegetation has been observed over time, as noted by Ferraz [20] when analyzing changes within the Miranda River Watershed regarding deforestation rates between 1973 and 2006. According to the author, in 2006, areas with natural coverage occupied 35.8% of the basin area, while in 1973, this percentage represented 72%.




**Figure 3.** Land use and land cover data in the Miranda river watershed between the period of 2005 to 2018 (IA: Influence Area).

According to Padovani [21], these changes in natural coverage in the Pantanal basin can be explained by the issuance of State Decree No. 14,273/2015, which regulated ecologically sustainable exploitation and alternative land use in the Restricted Use Areas of the Pantanal floodplain in Mato Grosso do Sul. The author explains that the issuance of the decree may have stimulated the conversion of native vegetation for anthropogenic use. Additionally, population growth, followed by increases in economic indicators, may be factors that led to this reduction in natural vegetation. The areas under agriculture increased from 373,430.33 hectares to 620,952.67 hectares between 2005 and 2018, representing an increase of 66.28%. There is also a reduction in pasture areas, from 1,950,383.39 hectares to 1,760,624.88 hectares, a decrease of 9.73% over the period. The reduction in pastures and the increase in agricultural areas is a trend observed in the national scenario as surveyed by Landau et al. [22]. The authors explain that the intensification of Brazilian livestock production, coupled with the ease of converting pastures to agricultural crops, explains the reduction in the total pasture area. According to Lamas [23], many degraded pasture areas have been converted to agricultural cultivation. There is also an increase in urbanized areas and non-vegetated areas in the basin. Variability in wetland areas and water bodies was also observed, common in the Pantanal region, with periods of drought and rainfall causing fluctuations throughout the year, associated to the mechanisms of droughts and floods.

# 3.2. Water Quality in the Miranda River Watershed

A multitemporal and spatial analysis of water quality was conducted in the 17 Areas of Influence for the parameters DO, pH, BOD, thermotolerant coliform, TN, TP, TS, Tu, and WQI. The quality parameters were analyzed following the classification metrics for Class 2 (Figure 4), according to CONAMA Resolution No. 375/05 and IMASUL's CECA-MS Deliberation No. 36/12.




**Figure 4.** Percentage of compliance with water quality parameters according to Brazilian legislation in the Miranda Basin between the period from 2005 to 2018.

The results showed that compliance with water quality parameters according to Brazilian legislation in the Miranda Basin between the period from 2005 to 2018 is similar, both for wetland areas and for the Cerrado. It is observed that most samples collected for thermotolerant coliforms and TP do not comply with the legislation, both for wetland areas and for the Cerrado, with a compliance rate below 32.14%. However, an improvement is observed for thermotolerant coliforms compliance with the legislation when wetland areas are compared to the Cerrado. On the other hand, it is observed that pH has the best compliance rate, reaching 100% in wetland areas.

For DO, a reduction in compliance with the legislation is observed, where in the Cerrado was achieved 88.1% of samples within the allowed limit, while in wetland areas there is a reduction to 76.47%. The reduction in DO in Pantanal wetland areas is related to the natural phenomenon known as "dequada" or "decoada," where floodwaters promote the decomposition of submerged organic matter, reducing the availability of DO in the water column [24]. Wetland areas have large amounts of stored organic matter, about 50% of which is carbon. Carbon associated with other nutrients such as Phosphorus and Nitrogen can reduce the amount of DO due to its demand in biochemical reactions involving these elements [25].

# 3.3. Water Quality Index

The WQI was analyzed temporally and spatially, where it was found that in the 17 Areas of Interest, the WQI was considered GOOD or EXCELLENT (Figure 5). In the analysis conducted by [26] in the Rio Vermelho basin, in the Upper Paraguay Basin in Mato Grosso, the author also obtained similar WQI values, between 51 and 70, considered as "AVERAGE" quality, equivalent to the "GOOD" range of the IQACETESB [27]. In the Diamantino Basin in Mato Grosso, Lima [28] found similar WQI values ranging from 58 to 91.



**Figure 5.** Variation of the Average of the Water Quality Index (WQI) in the Miranda River Watershed subdivided into 17 Influence Areas.

# 3.4. Correlation between Land Use and Land Cover and Water Quality

Through the overall correlation analysis across the entire MRW (Figure 6), it is observed that the highest values for positive correlation occurred between the "Native Vegetation" class and "Total Nitrogen" (corr=+0.8) and "Native Vegetation" with "Total Solids" (corr=+0.75), considered high correlation. Meanwhile, the highest negative correlation occurred between "Wetlands" and "Total Nitrogen" (corr=-0.80) and "Native Vegetation" with "WQI" (corr=-0.75).

# **General Correlation Miranda River Watershed**





Figure 6. Correlogram of land use and land cover with water quality in the Miranda river watershed. Note: Class: Agri=Agriculture, Hidro=Water Body, Not\_Veg=Non-Vegetated, Past=Pasture, Wet=Wetland Areas, Urb=Urban Area, Veg\_Nat=Native Vegetation. Water quality parameters: DO=dissolved oxygen, BOD= biochemical oxygen demand, Therm. Coli.= Thermotolerant coliforms, TN= total nitrogen, TP=total phosphorus, TS=total solids, Tu=turbidity, WQI=water quality index.

In light of these observations, it is important to highlight that the arrangement of native vegetation, location, shape, and the presence of riparian forests influence the water quality in adjacent watercourses. Therefore, the presence of native vegetation in strategic points can positively affect water quality, especially when located in the riparian zone of watercourses [11,29]. In the study by Menezes et al. [8] in the Ribeirão Vermelho Basin in Lavras, Minas Gerais, where the springs and main tributaries are located in the urban region of Lavras, it was found that natural vegetation correlated negatively with Nitrogen (corr=-0.43). Additionally, they did not identify a correlation between "Native Vegetation" and "Total Solids" (corr=0.06).

The correlation values found in this study suggest that each study region has its own peculiarities, as shown in Figure 7, since the expected correlations may not repeat from one study area to another.




**Figure 7.** Correlogram of land with water quality by influence area in the Miranda river watershed. Note: IA: Influence Areas. Water quality parameters: DO=dissolved oxygen, BOD= biochemical oxygen demand, Therm. Coli.= Thermotolerant coliforms, TN= total nitrogen, TP=total phosphorus, TS=total solids, Tu=turbidity, WQI=water quality index.

In the study conducted by Chen et al. [30], the authors analyzed the correlation between land use and land cover and water quality parameters. The authors found that there is some spatial heterogeneity among the sub-basins studied, so the relationship between land use and water quality is not the same among them, as observed in the delineated Areas of Influence for the MRW in this study. The literature suggests that other relationships should be investigated for a better understanding of the relationship between land use and water quality, such as the type of scale adopted, region topography, and hydrological regime [10,31].

According to the multi-temporal analysis of land use and land cover, IA17 has the highest proportion of wetland areas due to its spatial location close to the mouth of the Miranda River with the Paraguay River. It is observed that over time in IA17, there is a variation in the quantity of "Wetland Areas" from year to year. This variation can be explained by the effect of multi-year flood and drought cycles, where periods of consecutive years of floods alternate with years of drought. With the increase in water covering the soil, there is a reduction in the quantity of other land use classes [32].

When analyzing the correlations between the land use "Wetland Areas" and water quality parameters in IA17, low correlations were observed, lower than corr=±0.5, except for the parameter "Total Nitrogen," which showed a high coefficient (corr=-0.82). Yu et al., [33] evaluated 40 small wetland areas in the Blue Ridge ecoregion, South Carolina, United States, where they found that total dissolved nitrogen depends on both the hydrological connection between wetland areas and the surrounding land use (Figure 8).

# **Wetland Areas Correlation Miranda River Watershed**




**Figure 8.** Correlogram of wetland areas with water quality by influence area in the Miranda river watershed. Note: Class: Agri=Agriculture, Hidro=Water Body, Not\_Veg=Non-Vegetated, Past=Pasture, Umide=Wetland Areas, Urb=Urban Area, Veg\_Nat=Native Vegetation. Water quality parameters: DO=dissolved oxygen, BOD= biochemical oxygen demand, Therm. Coli.= Thermotolerant coliforms, TN= total nitrogen, TP=total phosphorus, TS=total solids, Tu=turbidity, WQI=water quality index.

These low correlations can be explained by the non-linear variation in the quantity of Wetland Areas over the study period, resulting from the seasonality of interannual periods of drought and flood in the Pantanal. The dynamics of land use and land cover in this region do not behave linearly over the study period, showing higher variance compared to other Influence Areas in the MRW. Because of this, the relationship between land use and land cover and water quality may not be well explained by linear correlations, suggesting that non-linear correlations should be investigated in future studies.

## 3.5. Influence of Wetlands on Water Quality

## 3.5.1. Thermotolerant Coliforms

When comparing Thermotolerant Coliforms at the inlet and outlet of the Pantanal region, a pronounced downward trend is observed in most of the years studied. Additionally, it is also noted that the values for Thermotolerant Coliforms were above the permissible limit for Class 2 at the inlet stations, so that at the mouth of the Miranda River with the Paraguay River, the values remained below the limit of 200 MPN.100m/L (Figure 9).




**Figure 9.** Spatial variation of the average Thermotolerant Coliforms (MPN/1000mL) at the monitoring stations in the Pantanal (IA07, IA14, IA15, IA16, IA17).

The results corroborate those found by [34] who analyzed the effectiveness of natural wetlands in retaining nutrients, sediments, and microbial pollutants in two wetland areas, one natural and the other channelized (anthropized), located in a region of intense agropastoral use. The authors found that the natural wetland area reduced about 68% of *E. coli* between the inlet and outlet of the natural wetland area, while the channelized wetland area retained 25% of the coliforms between the inlet and outlet. Wilcock et al [35] found an average reduction of 79% between the years 2007 and 2010 at the outlet of the wetlands in the Toenepi basin, a region predominantly characterized by dairy farming in the North of New Zealand.

The retention and reduction of coliforms and other types of microorganisms in wetlands may be associated with sedimentation along with suspended particulate matter and also with adsorption to aquatic vegetation. The infiltration of contaminated floodwaters into firm soil is another factor that reduces the quantity of these microorganisms in surface waters. Exposure of organisms to ultraviolet solar radiation present in the water column significantly reduces the quantity of these organisms, especially in shallow waters [34,35].


#### 3.5.2. Dissolved Oxygen and Biochemical Oxygen Demand Assessment

When comparing DO at the inlet and outlet of the Pantanal region, a downward trend is observed in most of the years studied. In the majority of the years studied, the DO values were above 5.0 mg/L, the minimum limit for Class 2 (Figure 10). It was also observed that DO values are higher during the driest times of the year.



**Figure 10.** Spatial variation of the average Dissolved Oxygen (mg/L) at the monitoring stations in the Pantanal (IA07, IA14, IA15, IA16, IA17).

The BOD concentration showed an increase at the inlet and outlet of the wetland area of the MRW for 6 years, and a decrease for 4 years. These values correlate with DO, where a decrease in concentration was observed in the wetland area of the Pantanal (Figure 11).



**Figure 11.** Spatial variation of the measurement of Biochemical Oxygen Demand BOD (mg/L) at the monitoring stations in the Pantanal (IA07, IA14, IA15, IA16, IA17).

The reduction of DO and the increase in BOD in the wetlands of the Pantanal may be related to the natural phenomenon known as "dequada" or "decoada", as mentioned before [36]. Dise [25] highlights that wetlands have large amounts of stored organic matter, about 50% of which is carbon. Carbon associated with other nutrients such as phosphorus and mainly nitrogen can reduce the amount of dissolved oxygen due to its demand in biochemical reactions involving these elements.

In a study conducted by Jeng and Hong [37] in the wetlands existing in the urban area of St. Bernard County, Louisiana, United States, the authors found low DO values, ranging from 3.0 mg/L to 1.8 mg/L. P. L. Silva et al. [38] also observed levels considered low of DO, from 1.37 to 5.37 mg/L in two bays of the Paraguay River in Cáceres (MT). During the "dequada" in the Paraguay River in Cáceres/MT, [39] found that the average dissolved oxygen declined from 6.37 mg/L (October 2018) to about 3.0 mg/L (April 2019), returning to normal in the following months.


Oliveira et al. [40] conducted an analysis of "dequada" events along the Paraguay River and its tributaries. The authors found that in the region from the confluence of the Miranda and Aquidauana rivers to the mouth with the Paraguay River (the area studied in this work), there is a reduction in DO and an increase in the concentration of Carbon Dioxide released during the decomposition of organic matter causing "dequada" events, considered of medium to high magnitude. Thus, it is relatively common to find low values of DO in wetlands, due to the low speed of the water, which reduces natural aeration in these areas. Especially in tropical areas with an abundance of herbaceous vegetation, DO levels can drop to 2.0 mg/L during the decomposition of organic matter, as floodwaters advance in the floodplain area [37,40].

The higher concentrations of BOD and the reduction of DO in the studied area may be associated with the decomposition of dead natural organic matter, resulting from seasonal flooding cycles. Oliveira et al. [40] further add that the magnitude of these events (intensity and duration) varies from

year to year, occurring from December to May in the tributaries, and from February to June in the main channel of the Paraguay River.

# 3.5.3. Total Nitrogen Assessment

An increase in TN values was observed over 7 years between the input and output in the wetland area of the Pantanal. In the years 2005, 2007, and 2015, there is a stability in the trend; however, for the years 2007, 2009, 2013, and 2014, there was a reduction in concentrations. Thus, it is observed that there is no clearly defined pattern of behavior for Nitrogen in the studied Pantanal wetland areas. It is also noted that, in general, the highest concentration values occur during the rainy seasons (Figure 12).



**Figure 12.** Spatial variation of the mean Total Nitrogen (mg/L) at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).

Uuemaa et al. [41] estimated the performance in the input and output of a wetland area in removing Nitrogen loads originating from upland pastures in the watershed in Waikato, New Zealand. The authors found that the concentrations of TN were consistently lower at the outlet of the wetland area, regardless of flow conditions or seasonality. This is due to water infiltration through saturated layers of anoxic organic sedimentary material and plant debris with high denitrification potential, so that high denitrification rates are common in wetlands and riparian zones rich in organic matter [41]. Dias & Baptista [9] also observed the reduction of TN in the wetland area of Riacho Fundo, Brasília, Brazil. The authors found an average retention of 36.7% for TN between the inlet and outlet of the wetland area.

In the literature review conducted by Fisher and Acreman [12] on the Nitrogen retention capacity in wetlands around the world, the authors confirm that most wetlands retain Nitrogen, however, about 13% of the wetlands studied showed an increase in Nitrogen in the aquatic

environment. Nitrogen can also be deposited in wetlands through atmospheric processes of molecular Nitrogen (N<sub>2</sub>) fixation, carried out by fixing bacteria. Additionally, the decomposition of dead organic matter can also release nitrogenous forms into the water mass. Most wetlands can function as effective reservoirs of Nitrogen in tropical zones, accounting for two-thirds of all globally fixed atmospheric Nitrogen [42]. White and Reddy [42] highlighted that some factors affect Nitrogen fixation in wetlands such as low N:P ratios in sediment, inputs of wastewater, reducing conditions (redox potential), photosynthetic activity, availability of molybdenum, iron, and dissolved organic matter. On the other hand, nitrification reactions, denitrification, ammonia volatilization, and plant absorption help to keep Nitrogen levels low in the water column. The contribution of each of these reactions will depend on a series of environmental factors, which can effectively optimize or minimize the relative rates of each reaction in soil and wetland areas [42].


The capacity of wetlands to remove nutrients from water varies with climatic seasonality, increased nutrient loads, and different types of vegetation. Vegetation production and seasonality influence the amounts of organic matter and carbon in wetland sediments and the oxygen concentration in sediment [43]. Therefore, the variability of Nitrogen concentrations in the studied area can be explained by the regime of wetland areas during dry and flood periods and by the Nitrogen cycle that occurs fully in wetlands, thanks to the presence of air, water, sediment, land, and live biomass. Additionally, the Nitrogen cycle occurs jointly with the other biogeochemical cycles of Carbon, Phosphorus, and Oxygen [43].

# 3.5.4. Total Phosphorus Assessment

The spatial behavior of TP concentrations varied from year to year in the studied area. Four years of decrease in upstream/downstream concentrations are observed (2006, 2010, 2015, 2017), and seven years of increase in upstream/downstream concentrations (2005, 2007, 2009, 2013, 2014, 2018). It is also noted that TP values were higher during rainy seasons compared to the drier period (Figure 13).

The spatial behavior of Total Phosphorus concentrations varied year to year in the study area. There are six years of decline in upstream/downstream concentrations (2006, 2008, 2010, 2011, 2015, 2017) and seven years of increase in upstream/downstream concentrations (2005, 2007, 2009, 2013, 2014, 2018). It is also noted that Total Phosphorus values were higher in rainy seasons compared to the drier period (Figure 13).

17



**Figure 13.** Spatial variation of the mean Total Phosphorus (mg/L) at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).


In the study conducted by Dias & Baptista [9] in the wetland area of Riacho Fundo, Brasília, Brazil, an average retention of 34% for TP between the inlet and outlet points analyzed by the authors was observed. After an extensive literature review on nutrient removal in wetlands, Fisher and Acreman [12] identified that 84% of the studied wetlands showed Phosphorus retention, 10% indicated an increase in Phosphorus, and in 6% of the studied areas, there was no difference between the input and output of wetlands. Studies in the literature associate wetlands with Phosphorus retention mechanisms [44,45]. These mechanisms combine biological, physical, and chemical factors such as absorption and release by vegetation, periphyton, and microorganisms; sorption and exchange reactions with soils and sediments; chemical precipitation in the water column; and sedimentation and transport [46,47].

In wetlands, Phosphorus is removed from surface waters and transferred to sediments and plants. Phosphorus removal can be limited by the concentration of iron, aluminum, or calcium in sediments [43]. The variability in Phosphorus concentrations found in the studied area may be associated with the processes of assimilation and release of P in aquatic plants in the Pantanal. According to Neves and Santos [48] the Pantanal is one of the Brazilian regions with the highest diversity of aquatic macrophytes due to the diversity of habitats in the Pantanal plain, with annual variations in water levels, temperature, and air humidity. Most of these species, for example, die in the dry season, releasing biomass rich in nutrients. Aquatic vegetation in wetlands plays a significant role in Phosphorus assimilation, as it absorbs P directly from the water column. Due to rapid turnover, P storage is short-term in short-cycle emergent plants, such as macrophytes, and much of the P is released back into the water column after vegetative decomposition, providing short-term storage. Unlike macrophytes, woody tree formations in wetlands provide long-term storage, with absorption rates ranging from 1 to 15 kg.ha-1.year-1 [46]. Periphyton may play an important role in

regulating P concentrations in the water column, as it assimilates organic and inorganic forms of P and can induce marked changes in pH and oxygen concentration in the water column and in the soil-water interface of flooding. These alterations can potentially influence P solubility by precipitating Phosphorus along with CaCO<sub>3</sub> [46,49]. Thus, quantifying P cycling in wetlands proves to be a major challenge in terms of measuring the many physicochemical forms of Phosphorus, as well as the vast array of biological and chemical processes that control the absorption, storage, and release of this element in wetlands [50].

#### 3.5.5. Total Solids Assessment

For TS, there was a trend of increasing values from upstream to downstream in the Pantanal area between the years 2005 and 2014. However, it is observed that from the year 2015 onwards, there has been a progressive reduction in the concentration of TS in the Pantanal wetland area (Figure 14).




**Figure 14.** Spatial variation of Total Solids (mg/L) at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).

Chang et al., [49] found that the restoration of natural wetland areas in the urban basin of the Tualatin River, Oregon, United States, was effective in reducing TS concentrations between the years 2001 and 2016. On the other hand, in the study conducted in the wetlands of the Duck Creek basin, Alaska, United States, no significant difference was found for TS at the inlet and outlet of the wetlands [52]. Plain wetlands, like those in this study, slow down the speed of water and retain it for longer in the floodplain, resulting in downstream solids reduction through sedimentation [51]. TS still play an important role in the cycle and transport of aquatic nutrients. Free Phosphorus is generally associated with suspended sediments in the water column, bottom sediments, or aquatic microbiota in organic form, so that water flows along with TS favor the transport of Phosphorus in the aquatic environment [52]. Understanding the influence of fluctuations in solid transport in Pantanal wetlands is highly

relevant, as transported sediments can be a limiting factor to primary biological productivity downstream, reducing the fertility of wetland areas and affecting their support capacity. The loss of flood pulse fertilization services has been documented in several natural systems worldwide, mainly associated with dam constructions that regulate the natural flow of sediments downstream [54].

# 3.5.6. Turbidity Assessment

Turbidity in the wetlands of the Pantanal of the MRW met the maximum limit of 100 NTU for Class 2 in all years studied. There is also a reduction in Turbidity values at the inlet and outlet of the Pantanal, where values during the dry season are lower than during the rainy season (Figure 15).



**Figure 15.** Spatial variation of the average Turbidity (NTU) at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).


In a study conducted by the local government in the wetlands of the Duck Creek basin, Alaska, United States, a reduction in Turbidity from upstream to downstream was also observed, not exceeding more than 30 NTU for that location [50]. Wetlands are known to be responsible for numerous ecosystem functions, among which the retention and deposition of sediments stand out. This process improves water quality by reducing turbidity, while retaining nutrients and pollutants [55].

Turbidity in wetlands affects the distribution of aquatic plants, such as submerged macrophytes, as they depend on light penetrating the water column for photosynthesis. When turbidity is high, the presence of macrophytes is limited due to the low availability of light in the water column [57]. In the aquatic environment, turbidity increases with higher solids load, reducing the depth at which sunlight penetrates the water. The higher the turbidity, the greater this effect. The depth at which light penetrates is the photic depth of the water body. Below this depth, there is not enough light for plants to photosynthesize. The depth of the photic zone is small in highly turbid wetlands, with

primary production limited to floating or emergent plants and benthic, planktonic, or submerged plants only within the shallow photic zone. Primary production is then limited to the upper layers of water, and in the lower layers, the composition of the microbiota is altered [57]. The results found for Turbidity in this study suggest that the composition of aquatic biota may be relatively different between the inlet and outlet in the wetland area of the Miranda River due to the availability of light along the water column.

#### 3.5.7. pH Assessment

Regarding pH, it was observed that, in general, there is an increasing trend between the inlet and outlet of the Pantanal, but remaining close to neutrality between 7.0 and 7.5 (Figure 16).



**Figure 16.** Spatial variation of the average pH at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).


This trend towards alkalinity was observed by Reid and Mosley [58] when comparing the contributions of geochemistry, microbial metabolism, and aquatic photosynthesis to the alkalinity of pH in ephemeral wetlands in southeastern Australia. In the study, the authors highlight that in that locality, the abundant growth of aquatic plants modifies the chemical composition of the water through the absorption of nutrients, such as calcium and magnesium. These nutrients absorbed by the plants are not available in the water column, so they do not form solid calcium and magnesium carbonates like calcite, which normally buffer the pH within a certain fixed range [58]. In the study conducted by Gitau [59] in the wetlands of Limuru, Kenya, the author identified low variation in pH at the inlet and outlet, also noting a slight trend of increasing alkalinity.

pH influences the mobility of Phosphorus in the aquatic environment [50]. Photosynthesis and respiration in the aquatic environment can trigger significant changes in the pH of the water column on a diurnal basis, increasing the pH to up to 10, depending on the buffering capacity of the water

column, and precipitating a significant portion of Phosphorus from the water column as calcium phosphate, where dissolved  $Ca^{+2}$  is available [46]. Oliveira et al. [40] highlight that in the Pantanal, pH is altered to values below 5.0 and DO <2.0 mg/L during the "decoada" period when a large amount of dead organic matter decomposes, releasing soluble  $CO_2$  (favoring acidification). During the study period, pH values outside the range of 6 to 9, allowed for Class 2, were not identified. Although a pattern of reduction in DO was identified in the wetlands of the Miranda River, it was observed that the average DO values were above 5.0 mg/L.

## 3.5.8. Water Quality Index (WQI)

When analyzing the WQI in the wetlands of the Pantanal, an increase in WQI values is observed. Additionally, it is noted that the index is better during drier periods compared to rainy periods. The influence of coliform removal may explain the significant improvement in WQI between the inlet and outlet of the wetlands in the Miranda basin (Figure 17). According to Oliveira et al. [40], understanding the phenomenon of "decoada" is important for interpreting the WQI, as the reduction in dissolved oxygen levels can negatively influence the index. Thus, the authors recommend caution in using DO as an indicator of quality in the Pantanal, considering that "decoada" phenomena are natural and promote significant changes in the dynamics of the entire ecosystem.



**Figure 17.** Spatial variation of the Water Quality Index (WQI) at the monitoring stations of the Pantanal (IA07, IA14, IA15, IA16, IA17).

#### 4. Conclusions

The study demonstrated changes in land use and land cover patterns and water quality standards in the MRW from 2005 to 2018. It is possible to observe changes in land cover such as the reduction of native vegetation, as well as a decrease in livestock and an increase in agricultural plantations. Additionally, there was variability in the quantity of wetland areas in the MRW,

23

characterizing multi-year cycles of drought and flood. Water quality parameters such as BOD, DO, pH, and Turbidity as well as the WQI, remained within the permissible reference limit for classification in Class 2, except for Thermotolerant Coliforms and Total Phosphorus, which showed values above the allowed range. The study also revealed a trend of increasing BOD values, indicating a higher input of organic matter into the water bodies of the basin, although in all the studied Influence Areas, the WQI was considered "GOOD" or "EXCELLENT". This indicates, overall, satisfactory levels of water quality for the basin. On the other hand, although Total Phosphorus exceeded the allowed limit, there was a gradual decreasing trend over the study period.

When analyzing correlations in the MRW, it was observed that when using a general approach for the entire basin, the indices showed low correlation. However, when correlations were analyzed by Influence Area (sub-basins), the correlation values increased, both for positive and negative correlations, indicating that policies for water quality management can be developed in terms of sub-basins, smaller planning units.

Comparing the behavior of water quality parameters concerning the wetland areas of the MRW, there is a significant improvement in WQI, and for Thermotolerant Coliforms and Turbidity. However, there is a downward trend in DO values in wetland areas and an increase in BOD. For pH, it is observed that values tend to increase, making the water more alkaline, rarely exceeding the range of 7.5. Regarding TP, TN, and TS, it was found that the values showed variability over the years, with periods of increase or decrease. Considering the climatic seasonality in the wetland areas of the MRW, it was observed that DO, Turbidity, and WQI values are higher in the driest times of the year, and COD, TN, and TP presented higher concentrations in the rainy season.

Wetland areas play important hydrological and ecological functions for flora and fauna, and especially for the water quality of the region. They are effective in the removal, storage, and cycling of nutrients, such as Nitrogen and Phosphorus, as well as improving and controlling quality parameters downstream. Therefore, they are highly relevant areas for defining strategies for watershed management and conservation, environmental protection, and the provision of ecosystem services.

**Author Contributions:** Conceptualization, F.J.C.M.F. and W.S.C.; methodology, F.J.C.M.F. and W.S.C.; formal analysis, C.S.C.C.; investigation, F.J.C.M.F. and W.S.C.; resources, F.J.C.M.F.; data curation, W.S.C.; writing—original draft preparation, L.R.R., C.S.C.C.; writing—review and editing, L.R.R., C.S.C.C.; visualization, F.J.C.M.F.; supervision, F.J.C.M.F.; project administration, F.J.C.M.F.; funding acquisition, F.J.C.M.F. All authors have read and agreed to the published version of the manuscript.

**Funding:** This research was funded by Ministério Público Estadual Do Mato Grosso do Sul (MPMS) "State Public Ministry of Mato Grosso do Sul", through the project Centro Integrado de Proteção e Pesquisa Ambiental (CEIPPAM) "Integrated Center for Environmental Protection and Research".

**Institutional Review Board Statement:** Not applicable.

**Informed Consent Statement:** Not applicable.

Acknowledgments: Fernando J.C.M.F. is thankful to Brazilian National Council for the Improvement of Higher Education (CAPES), the Brazilian National Council of Scientific and Technological Development (CNPq), National Institute of Science and Technology in Nature-based Solutions — INCT "NbS" (CAPES/CNPq/Research Support Foundation of the State of Rio Grande do Sul – FAPERGS); and Calheiros S.C.C. is thankful to Fundação para a Ciência e Tecnologia (FCT) within the scope of UIDB/04423/2020, UIDP/04423/2020

**Conflicts of Interest:** The authors declare no conflicts of interest.

# References

- 1. Arenas-Sánchez, A., Rico, A., Vighi, M. Effects of water scarcity and chemical pollution in aquatic ecosystems: State of the art. *Science of The Total Environment* **2016**, 572, 390–403. https://doi.org/10.1016/j.scitotenv.2016.07.211
- 2. Ipea-Objetivos do Desenvolvimento Sustentável, 2022. Available online: https://www.ipea.gov.br/ods/index.html (accessed on 6 May 2024)

- 3. Von Sperling, M., Chernicharo, C.A.L. Biological wastewater treatment in warm climate regions. Volume 1. Publisher: IWA Publishing, UK, 2005, p. 1496. http://www.iwapublishing.com/open-access-ebooks/3567
- 4. Song, Y., Song, X., Shao, G., Hu, T. Effects of Land Use on Stream Water Quality in the Rapidly Urbanized Areas: A Multiscale Analysis. *Water* **2020**, *12*, 1123. https://doi.org/10.3390/w12041123
- 5. Braga, B., Hespanhol, I., Conejo, J.L., Mierzwa, J.C., Barros, M.T. de, Spencer, M., Porto, M., Nucci, N., Juliano, N., Eiger, S., Gallardo, A., Boneccarrere, J., Souza, T. de, Contrera, R. Introdução à engenharia ambiental, 3th Edition. Editor: Simone de Fraga, Publisher: Bookman, Brasil, 2021, pp 392
- 6. Da Silva, J.D.S.V., De Moura, A.M., Pott A., De Arruda, M.R. Fragile ecosystem: the Brazilian Pantanal wetland. In: Sanchez L.E., editor. Area Studies-Brazil: Regional Sustainable Development Review. Oxford, United Kingdom: Eolss Publishers Co. Ltd., 2009 pp 302-339
- 7. Giri, S., Qiu, Z. Understanding the relationship of land uses and water quality in Twenty First Century: A review. *Journal of Environmental Management* **2016**, 173, 41–48. https://doi.org/10.1016/j.jenvman.2016.02.029
- 8. Menezes, J.P.C., Bittencourt, R.P., Farias, M. de S., Bello, I. P., Fia, R., Oliveira, L.F.C. de. Relação entre padrões de uso e ocupação do solo e qualidade da água em uma bacia hidrográfica urbana. *Engenharia Sanitaria e Ambiental* **2016**, 21, 519–534. https://doi.org/10.1590/S1413-41522016145405
- Dias, R.Z., Baptista, G.M.de M. Wetland nutrient retention and multitemporal growth Case study of Riacho Fundo's Wetland. Acta Limnologica Brasiliensia 2015, 27, 254–264. https://doi.org/10.1590/S2179-975X0114
- 10. Mello, K. de, Valente, R.A., Randhir, T.O., dos Santos, A.C.A., Vettorazzi, C.A. Effects of land use and land cover on water quality of low-order streams in Southeastern Brazil: Watershed versus riparian zone. *CATENA* **2018**, *167*, 130–138. https://doi.org/10.1016/j.catena.2018.04.027
- 11. Shi, P., Zhang, Y., Li, Z., Li, P., Xu, G. Influence of land use and land cover patterns on seasonal water quality at multi-spatial scales. *CATENA* **2017**, *151*, 182–190. https://doi.org/10.1016/j.catena.2016.12.017
- 12. Fisher, J., Acreman, M.C. Wetland nutrient removal: A review of the evidence. *Hydrology and Earth System Sciences* **2004**, *8*, 673–685. https://doi.org/10.5194/hess-8-673-2004
- 13. Projeto MapBiomas Coleção 6 da Série Anual de Mapas de Cobertura e Uso da Terra do Brasil. Available online: http://brasil.mapbiomas.org/ (accessed on 28 March 2024)
- 14. IMASUL. Relatórios de Monitoramento da Qualidade das Águas Superficiais de Mato Grosso do Sul, 2020. Available online: http://www.imasul.ms.gov.br/relatorios-de-monitoramento-da-qualidade-das-aguas-superficiais/ (accessed on 28 March 2024)
- 15. American Public Health Association, American Water Works Association, Water Environment Federation. Lipps WC, Braun-Howland EB, Baxter TE, eds. Standard Methods for the Examination of Water and Wastewater. 24th ed. Washington DC: APHA Press; 2023.
- 16. ASTM International. ASTM D888-12e1, "Standard Test Methods for Dissolved Oxygen in Water" West Conshohocken, United States
- 17. ABNT: Associação Brasileira de normas técnicas. ABNT NBR 13796:1997-04-30: água-Determinação de nitrogênio orgãnico, kjeldahl e total Métodos macro e semimicro Kjeldahl
- 18. IBGE: Instituto Brasileiro de Geografia e Estatística. Biomas e Sistema Costeiro-Marinho do Brasil-PGI. Available online: https://www.ibge.gov.br/apps/biomas/#/home (accessed on 28 March 2024)
- 19. Plano de Recursos Hídricos da Região Hidrográfica do Paraguai PRH Paraguai, Produto Parcial PP-04 Definição das Metas do PRH Paraguai e Diretrizes e Estudos para os Instrumentos de Gestão. Agência Nacional de Águas Brasília: ANA/SPR, ENGECORPS ENGENHARIA S.A., 2017
- 20. Ferraz, R.G.B. Antropização da bacia hidrográfica do Rio Miranda: alterações climáticas, recursos naturais e desenvolvimento. 2006. Dissertação de Mestrado, orientação do Prof. Dr. Reginaldo Brito da Costa-Campo Grande-MS, UCDB, Brasil
- 21. Padovani, C.R. Conversão da vegetação natural do Pantanal para uso antrópico de 1976 até 2017 e projeção para 2050. *Comunicado Técnico* **2017**, *109*, 1–6
- 22. Landau, E.C., Resende, R.M.S., Matos Neto, F. da C. Evolução da área ocupada por pastagens. In: Landau, E.C.; Silva, G.A. Da; Moura, L.; Hirsch, A.; Guimarães, D. P. (Ed.). Dinâmica da produção agropecuária e da paisagem natural no Brasil nas últimas décadas: produtos de origem animal e da silvicultura. Brasília, DF: Embrapa, 2020. v. 3, cap. 46, p. 1555-1578. Available online: http://www.alice.cnptia.embrapa.br/handle/doc/1122718 (accessed on 28 March 2024)

- 23. Lamas, F. M. Artigo-A dinâmica da agricultura em Mato Grosso do Sul. EMBRAPA 2021. Available online: https://www.embrapa.br/busca-de-noticias/-/noticia/65083174/artigo---a-dinamica-da-agricultura-emmato-grosso-do-sul (accessed on 28 March 2024)
- 24. Bergier, I., Assine, M.L. (Edt.). Dynamics of the Pantanal Wetland in South America (Vol. 37). 2016. Springer International Publishing. https://doi.org/10.1007/978-3-319-18735-8
- Dise, N. B. Biogeochemical Dynamics III: The Critical Role of Carbon in Wetlands. Em E. Maltby & T. Barker (Orgs.), The Wetlands Handbook, 2009). (p. 249-265). Wiley-Blackwell. https://doi.org/10.1002/9781444315813.ch11
- 26. Souza, A.V.V. Avaliação da influência dos usos e ocupação do solo na qualidade da água do rio Vermelho no sudeste de Mato Grosso. Dissertação, 2015, Programa de Pós-Graduação em Geografia. Universidade Federal de Mato Grosso. Rondonópolis, p. 82.
- 27. CETESB, Environmental Sanitation Technology Company Relatório de qualidade das águas interiores do Estado de São Paulo. São Paulo, Brazil. 2008. Available online: http://cetesb.sp.gov.br/aguas-interiores/wpcontent/uploads/sites/12/2013/11/relatorio\_2008.zip (accessed on 28 March 2024)
- 28. Lima, A. F. Dinâmica da qualidade da água na bacia Paraguai/Diamantino Mato Grosso. 2017. Dissertação Mestrado (Ambiente e Sistema de Produção Agrícola), Universidade Estadual do Mato Grosso, Tangará da Serra-MT, pp: 51
- 29. Santos, J. P. dos. Influências da composição e estrutura da paisagem sobre a qualidade da água em múltiplas extensões espaciais na unidade hidrológica do Rio Doce em Minas Gerais. Dissertação de Mestrado 2020, Brasil. Available online: https://repositorio.ufmg.br/handle/1843/36487 (accessed on 28 March 2024)
- 30. Chen, D., Elhadj, A., Xu, H., Xu, X., Qiao, Z. A Study on the Relationship between Land Use Change and Water Quality of the Mitidja Watershed in Algeria Based on GIS and RS. *Sustainability* **2020**, *12*, 3510. https://doi.org/10.3390/su12093510
- 31. Ullah, K., Jiang, J., Wang, P. Land use impacts on surface water quality by statistical approaches. *Global Journal of Environmental Science and Management* 2018, 4. https://doi.org/10.22034/gjesm.2018.04.02.010
- 32. Padovani, C.R. Dinâmica espaço-temporal das inundações do pantanal. Tese de Doutorado, 2010. Ecologia de Agroecossistemas, Universidade de São Paulo, Piracicaba, Brasil. doi:10.11606/T.91.2010.tde-14022011-170515.
- 33. Yu, X., Hawley-Howard, J., Pitt, A.L., Wang, J.-J., Baldwin, R.F., Chow, A.T. Water quality of small seasonal wetlands in the Piedmont ecoregion, South Carolina, USA: Effects of land use and hydrological connectivity. *Water Research* 2015. 73, 98-108. https://doi.org/10.1016/j.watres.2015.01.007
- 34. Knox, A.K., Dahlgren, R.A., Tate, K.W., Atwill, E.R. Efficacy of Natural Wetlands to Retain Nutrient, Sediment and Microbial Pollutants. *Journal of Environmental Quality* **2008**, 37, 1837–1846. https://doi.org/10.2134/jeq2007.0067
- 35. Wilcock, R.J., Müller, K., van Assema, G.B., Bellingham, M.A., Ovenden, R. Attenuation of Nitrogen, Phosphorus and E. coli Inputs from Pasture Runoff to Surface Waters by a Farm Wetland: The Importance of Wetland Shape and Residence Time. *Water, Air, & Soil Pollution* **2012**, 223, 499–509. https://doi.org/10.1007/s11270-011-0876-8
- 36. Calheiros, D.F., Ferreira, C.J.A. alterações limnológicas no rio paraguai ("dequada") e o fenômeno natural de mortandade de peixes no Pantanal Mato-Grossense. MS. Corumbá. MS: EMBRAPA-CPAP, 1996. 51p. (EMBRAPA-CPAP. Boletim de Pesquisa, 7).
- 37. Jeng, H., Hong, Y.-J. Assessment of a Natural Wetland for use in Wastewater Remediation. *Environmental Monitoring and Assessment* **2005**, *111*, 113–131. https://doi.org/10.1007/s10661-005-8217-2
- 38. Silva, P.L., Muniz, C. C., Rieder, A., & Carvalho, A. M. Variação da concentração dos teores de oxigênio dissolvido na água na baia negra e salobra, Rio Paraguai, Cáceres, Alto Pantanal, Mato Grosso, Brasil. 2004. Available online: https://www.cpap.embrapa.br/agencia/simpan/sumario/resumos/asperctos/pdf/abiotico/102AB-Correlacao%20baias%20odPLS1-OK.PDF (accessed on 28 March 2024)
- 39. Menezes Junior, M.Q. de M., Junior, E.S.O., Souza, C.A. de. The "decoada" phenomenon effect on the Paraguay river water quality, Northern Pantanal. *Revista Ibero-Americana de Ciências Ambientais* **2020**, *11*, 5. https://doi.org/10.6008/CBPC2179-6858.2020.005.0055
- 40. Oliveira M.D. de, Calheiros D.F., Padovani C.R. Mapeamento e descrição das áreas de ocorrência dos eventos de decoada no Pantanal. Embrapa Pantanal, Corumbá. Boletim de Pesquisa e Desenvolvimento,

- 121, 2013, Available online: https://ainfo.cnptia.embrapa.br/digital/bitstream/item/83348/1/BP121.pdf (accessed on 28 March 2024)
- 41. Uuemaa, E., Palliser, C., Hughes, A., Tanner, C. Effectiveness of a Natural Headwater Wetland for Reducing Agricultural Nitrogen Loads. *Water* **2018**, *10*, 287. https://doi.org/10.3390/w10030287
- 42. White, J.R., Reddy, K.R. Biogeochemical Dynamics I: Nitrogen Cycling in Wetlands. Em E. Maltby & T. Barker (Edt.), The Wetlands Handbook. 2009, p. 213-227. Wiley-Blackwell. https://doi.org/10.1002/9781444315813.ch9
- 43. Fisher, J., Stratford, C.J., Buckton, S. Variation in nutrient removal in three wetland blocks in relation to vegetation composition, inflow nutrient concentration and hydraulic loading. *Ecological Engineering* **2009**, 35, 1387–1394. https://doi.org/10.1016/j.ecoleng.2009.05.009
- 44. Walton, C.R., Zak, D., Audet, J., Petersen, R.J., Lange, J., Oehmke, C., Wichtmann W., Kreyling J., Grygoruk M., Jaboska E., Kotowski W., Winiewska M.M., Ziegler R., .Hoffmann, C. C. Wetland buffer zones for nitrogen and phosphorus retention: Impacts of soil type, hydrology and vegetation. *Science of the Total Environment* 2020, 727, 138709.
- 45. Gericke, A., Nguyen, H.H., Fischer, P., Kail, J., Venohr, M. Deriving a bayesian network to assess the retention efficacy of riparian buffer zones. *Water* **2020**, *12*, 617.
- 46. Reddy, K.R., Kadlec, R.H., Flaig, E., Gale, P.M. Phosphorus Retention in Streams and Wetlands: A Review. *Critical Reviews in Environmental Science and Technology* **1999**, 29, 83–146. https://doi.org/10.1080/10643389991259182
- 47. Marois, D.E., Mitsch, W.J., Song, K., Miao, S., Zhang, L., Nguyen, C. T. Estimating the importance of aquatic primary productivity for phosphorus retention in Florida Everglades mesocosms. *Wetlands* **2015**, *35*, 357–368.
- 48. Neves, A., Santos, F. Nem tudo são flores no Pantanal. Ciência Hoje 2008. 245, 71-73. Available online: https://www2.ib.unicamp.br/profs/fsantos/refer/CH-2008-41-245-71.pdf (accessed on 28 March 2024)
- 49. Dodds, W.K. The role of periphyton in phosphorus retention in shallow freshwater aquatic systems. *Journal of Phycology* **2003**, *39*, 840–849.
- 50. Richardson, C.J., Vaithiyanathan, P. Biogeochemical Dynamics II: Cycling and Storage of Phosphorus in Wetlands. E. Maltby and T. Barker (Edt.), The Wetlands Handbook, 2009. (p. 228-248). Wiley-Blackwell. https://doi.org/10.1002/9781444315813.ch10
- 51. Chang, H., Makido, Y., Foster, E. Effects of land use change, wetland fragmentation, and best management practices on total suspended solids concentrations in an urbanizing Oregon watershed, USA. *Journal of Environmental Management* **2021**, 282, 111962. https://doi.org/10.1016/j.jenvman.2021.111962
- 52. Juneau Watershed Partnership. Final Report Duck Creek Nancy Street Wetland Water Quality Assessment 2018. https://dec.alaska.gov/media/17146/2018-duck-creek-nancy-st-wetland-assessment.pdf
- 53. Reddy, K.R., Wetzel, R.G., Kadlec, R.H. Biogeochemistry of Phosphorus in Wetlands. Em Phosphorus: Agriculture and the Environment 2005. (p. 263-316). John Wiley & Sons, Ltd. https://doi.org/10.2134/agronmonogr46.c9
- 54. Schmutz, S., Moog, O. Dams: Ecological Impacts and Management. Em S. Schmutz & J. Sendzimir (Edt), Riverine Ecosystem Management: Science for Governing Towards a Sustainable Future, 2018. (p. 111-127). Springer International Publishing. https://doi.org/10.1007/978-3-319-73250-3\_6
- 55. Sánchez-Carrillo, S., Álvarez-Cobelas, M., Angeler, D.G. Sedimentation in the semi-arid freshwater wetland las tablas de Daimiel (Spain). *Wetlands* **2001**, 21, 112–124. https://doi.org/10.1672/0277-5212(2001)021[0112:SITSAF]2.0.CO;2
- Madsen, J.D., Chambers, P.A., James, W.F., Koch, E.W., Westlake, D.F. The interaction between water movement, sediment dynamics and submersed macrophytes. *Hydrobiologia* 2001, 444, 71–84. https://doi.org/10.1023/A:1017520800568
- 57. Crossetti, L.O., Cardoso, L. de S., Callegaro, V.L.M., Silva, S.M.A. da, Werner, V.R., Rosa, Z. M., Marques, D.M.L. da M. Influence of the hydrological changes on the phytoplantkton structure and dynamics in a subtropical wetland-lake system. 2007. Acta limnologica brasiliensia. São Paulo, SP. Vol. 19, n.3, p.315-329. https://lume.ufrgs.br/handle/10183/249605
- 58. Reid, R.J., Mosley, L.M. Comparative contributions of solution geochemistry, microbial metabolism and aquatic photosynthesis to the development of high pH in ephemeral wetlands in South East Australia. *Science of The Total Environment* **2016**, 542, 334–343. https://doi.org/10.1016/j.scitotenv.2015.10.040

59. Gitau, J.K. Effectiveness of natural wetland in waste water treatment: A case study of tibia wetland, Limuru Municipality, Kenya. 2014. https://ir-library.ku.ac.ke/handle/123456789/12070

**Disclaimer/Publisher's Note:** The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.

27